MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM, (NONPOLARIZED, PLAIN FOIL), 85°C (VOLTAGE DERATED TO 125°C), ESTABLISHED RELIABILITY, STYLE CLR37

This amendment forms a part of Military Specification Sheet MIL-C-39006/4C, dated 10 January 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following preamble, add:

" FAILURE RATE LEVEL 'L' INACTIVE FOR DESIGN AFTER 27 May 1976 "

" CASE SIZE E1 INACTIVE FOR DESIGN AFTER 20 Oct 1978 "

FIGURE 1 (dimension table): Add G1 case size

G1	.688 (17.48)	.188 (4.78)	.219 (5.56)	1.188 (30.18)

PAGES 2 AND 3

* TABLE I, following part no. M39006/04-: Add "1/".

* TABLE I, part number column: Add "-" following numbers 1245 through 1424 to denote optional random vibration part numbers.

* TABLE I: Add the new G1 case size units

Rated voltage (85°C)	Cap.	Cap. tolerance	DC leakage (max) 25°C	DC leakage (max) 85°C 125°C	Derated voltage (125°C)	Surge voltage (85°C)	Impedance (max)	Case size	Part no. M39006/04- 1/ Failure rate level (%/1,000 hr) L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
15	2.5	±20	1	2	10	17.2	893	G1	2700	2711-	2722-	2733-	2744-
25	1.5	±20	1	3	15	28.8	1487	G1	2701	2712-	2723-	2734-	2745-
30	1.4	±20	2	5	20	34.5	1594	G1	2702	2713-	2724-	2735-	2746-
50	0.8	±20	1	4	30	57.5	2790	G1	2703	2714-	2725-	2736-	2747-
75	0.5	±20	1	4	50	86.2	4460	G1	2704	2715-	2726-	2737-	2748-
100	0.4	±20	1	3.5	65	115.0	5580	G1	2705	2716-	2727-	2738-	2749-
150	0.25	±20	1	4	100	172.0	8909	G1	2706	2717-	2728-	2739-	2750-

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:15Z
Check the source to verify that this is the current version before use.

* TABLE I (Continued): Add the new G1 case size units

"

Rated voltage (85°C)	Cap.	Cap. tolerance	DC leakage (max) 25°C	DC leakage (max) 85°C 125°C	De-rated voltage (125°C)	Surge voltage (85°C)	Impedance (max)	Case size	Part no. M39006/04- 1/ Failure rate level (%/1,000 hr) L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
200	0.15	±15	4	25	150	230.0	14000	G1	2707	2718-	2729-	2740-	2751-
250	0.15	±15	6	32	165	287.0	13000	G1	2708	2719-	2730-	2741-	2752-
300	0.12	±15	4	25	200	345.0	17500	G1	2709	2720-	2731-	2742-	2753-
375	0.1	±15	8	80	250	431.0	23500	G1	2710	2721-	2732-	2743-	2754-

"

* Following Table I: Add "1/ Dash number for failure rate level M, P, R, and S parts will include the letter 'H' to indicate the optional random vibration requirement or '-' will be deleted."

PAGE 4

* Following vibration requirement, add new Random vibration requirement:
"Random vibration (when applicable): Method 214 of MIL-STD-202, test condition II-E (18.7 g)."

Temperature cycling: Delete "Temperature cycling: Method 102 of MIL-STD-202, condition D" and substitute "Thermal shock: Method 107 of MIL-STD-202, condition A."

PAGE 5

Life at 85°C: Delete "240-hr (group B)" requirement in its entirety; also delete "10,000-hr (group C)" and substitute "10,000-hr (group B)".

Add the following new requirement under "Life at 125°C":

"10,000-hr (group B):
DCL (125°C) - 125% (max) of table I value.
DCL (25°C) - See table I.
ΔCap. - Within ±50% of initial measurement for E1 and G1 cases; within ±25% of initial measurement for all other cases.
DF - 40% (max) for E1 and G1 cases; 20% (max) for all other cases.
DWV - 2,000 Vdc, min.
IR - 100 megohms, min."

Marking: Delete requirement in its entirety and substitute: "Marking: In accordance with MIL-C-39006."

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:15Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Air Force - 17, 85, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA-ES

Preparing activity:
Navy - EC

(Project 5910-1404-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:15Z
Check the source to verify that this is the current version before use.