MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM,
(POLARIZED, SINTERED SLUG) (EXTENDED RANGE),
85°C (VOLTAGE DERATED TO 125°C),
ESTABLISHED RELIABILITY,
STYLE CLR69

This amendment forms a part of Military Specification sheet MIL-C-39006/21, dated 25 January 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*Following title, add:

"

INACTIVE FOR NEW DESIGN AFTER 23 JUNE 1981. FOR NEW DESIGN, USE MIL-C-39006/22.

"

NOTE: The above entry consolidates all previous specification action concerning inactivation. Failure rate level "L" was made inactive for new design on 27 May 1976. All other failure rate levels were inactivated by Notice 1 and 2 dated 9 October 1981 and 11 June 1982, respectively.

PAGE 4

* Terminals, delete and substitute:

"Terminals - Axial-wire lead:
Anode (type N4 or N5 of MIL-STD-1276).
Cathode (type C4 or C5 of MIL-STD-1276)."

Temperature cycling: Delete "Temperature cycling: Method 102 of MIL-STD-202, condition D" and substitute "Thermal shock: Method 107 of MIL-STD-202, condition A".

PAGE 5

Life at 85°C: Delete "ΔCap." requirement for 2,000-hr (qualification) measurement and substitute:
"ΔCap. - Within +10 to -25% of initial measurement for 6-volt units;
- within +10 to -20% of initial measurement for 8- and 10-volt units;
- within +10 to -15% of initial measurement for 15-volt units; and
- within ±10% of initial measurement for all other units."
Make this change in "Life at 125°C".

Life at 85°C: Delete "240-hr (group B)" requirement in its entirety; also delete "10,000-hr (group C)" and substitute "10,000-hr (group B)".

Add the following new requirement under "Life at 125°C":
"10,000-hr (group B):
DCL (125°C) - 125% (max) of table I value.
DCL (25°C) - See table I.
ΔCap. - Within +10%, -50% of initial measurement.
DF - 200% (max) of table I value.
DWV - 2,000 V dc, min.
IR - 100 megohms, min."

Marking: Delete requirement in its entirety and substitute:
"Marking: In accordance with MIL-C-39006.
Polarity - Series of plus (+) symbols encircling positive end (see figure 1)."

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:17Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Navy - SH
Air Force - 17, 85
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1516-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:17Z
Check the source to verify that this is the current version before use.