INCH-POUND
MIL-PRF-39006/21A
AMENDMENT 1
16 January 2003

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM (POLARIZED, SINTERED SLUG) (EXTENDED RANGE), 85°C (VOLTAGE DERATED TO 125°C), ESTABLISHED RELIABILITY, STYLE CLR69

This amendment forms a part of MIL-PRF-39006/21A, dated 17 April 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Delete the table on page 2 of slash sheet 21 in its entirety and replace it with the following:

Case size	Dimensions			
	Basic case		Insulated case	
	L 1/ 2/ +.031 (0.79) -.016 (0.41)	D ±.016 (0.41)	D max	E ±.250 (6.35)
T1	.453 (11.51)	.188 (4.78)	.219 (5.56)	1.500 (38.10)
T2	.641 (16.28)	.281 (7.14)	.312 (7.92)	2.250 (57.15)
T3	.766 (19.46)	.375 (9.53)	.406 (10.31)	2.250 (57.15)
T4	1.062 (26.97) 2/	.375 (9.53)	.406 (10.31)	2.250 (57.15)

1/ Length of basic case; sleeving shall be as specified in MIL-PRF-39006.
2/ For the T4 case size only, the negative L dimension tolerance is -.023 (0.58)

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5910-2219)

Review activities:
Navy - AS, MC, OS
Air Force – 19

AMSC N/A FSC 5910
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:17Z
Check the source to verify that this is the current version before use.