INCH-POUND
MIL-PRF-39006/22F
AMENDMENT 1
24 September 2002

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM (POLARIZED, SINTERED SLUG), 85°C (VOLTAGE DERATED TO 125°C), ESTABLISHED RELIABILITY, STYLE CLR79

This amendment forms a part of MIL-PRF-39006/22F, dated 17 April 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGES 3 thru 8

Table I column headers, change from "PIN 39006/22- 4/ 5/ noncompression test" and "PIN 39006/22- 4/ 5/ compression test", change to "PIN 39006/22- 4/ 5/ noncompression seal" and "PIN 39006/22- 4/ 5/ compression seal"

PAGE 11

Thermal shock: After number of cycles: delete "300 for qualification and group C; 30 for group B." and replace with "In accordance with MIL-PRF-39006, the following shall apply."

PAGE 14

Resistance to soldering heat change from condition "G" to condition "C".

PAGE 18

Table III, after the line in the table that reads:

- - -	- - -	- - -	- - -	7114	7195	7277	7360	7442	0219	0439	0659	0879	7027	7030	7033	7036	7039

Insert the following:

0201	0421	0641	0861	6189	6394	6599	6804	7009	0220	0440	0660	0880	7028	7031	7034	7037	7040
0202	0422	0642	0862	6190	6395	6600	6805	7010					7121	7203	7285	7367	7449

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5910-2198)

Review activities:
Navy - AS, MC, OS
Air Force – 19

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.