INCH-POUND
MIL-PRF-39006/25B
AMENDMENT 1
24 September 2002

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM
(POLARIZED, SINTERED SLUG), (EXTENDED RANGE),85°C (VOLTAGE DERATED TO 125°C),
ESTABLISHED RELIABILITY, STYLE CLR81

This amendment forms a part of MIL-PRF-39006/25B, dated 17 April 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Thermal shock: After Number of cycles: delete "300 for qualification and group C; 30 for group B." and replace with "In accordance with MIL-PRF-39006, the following shall apply."

PAGE 10

Resistance to soldering heat change from condition "G" to condition "C".

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Review activities:
Navy - AS, MC, OS
Air Force – 19

Preparing activity:
DLA - CC

(Project 5910-2199)

AMSC N/A FSC 5910
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:19Z
Check the source to verify that this is the current version before use.