
INCH-POUND
MIL-PRF-39006/25G
12 April 2023
SUPERSEDING
MIL-PRF-39006/25F
21 March 2018

PERFORMANCE SPECIFICATION SHEET

# CAPACITOR, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM (POLARIZED, SINTERED SLUG), EXTENDED RANGE, +85°C (VOLTAGE DERATED TO +125°C), ESTABLISHED RELIABILITY, STYLE CLR81

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39006.




NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in millimeters and are in parentheses.
3. Metric equivalents are given for general information only.
4. The weld shall not be enclosed in the end seal.
5. CLR81 capacitors are replacements for the inactive CLR69s (MIL-PRF-39006/21), silver cased wet slug capacitors.
6. CLR81 capacitors have higher capacitance values than CLR79s (MIL-PRF-39006/22) of the same case size and voltage rating.
7. Low ESR versions of CLR81s may be found in MIL-PRF-39006/31 (CLR91).

FIGURE 1. Style CLR81 capacitors.


DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

| Case size | Dimensions in inches (mm) | | | |
|---|---|---|---|---|
| | Basic case | | Insulated case | |
| | L 1/<br>+.031 (0.79)<br>-.016 (0.41) | D<br>± .016 (0.41) | D<br>max | E<br>± .250 (6.35) |
| T1 | .453 (11.51) | .188 (4.78) | .219 ( 5.56) | 1.500 (38.10) |
| T2 | .641 (16.28) | .281 (7.14) | .312 ( 7.92) | 2.250 (57.15) |
| T3 | .766 (19.46) | .375 (9.52) | .406 (10.31) | 2.250 (57.15) |
| T4 | 1.062 (26.97) | .375 (9.52) | .406 (10.31) | 2.250 (57.15) |

1/ Length of basic case sleeving shall be as specified in MIL-PRF-39006.

FIGURE 1. Style CLR81 capacitors - Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case type: Tantalum, tubular, insulated.

Seal type: Hermetic (glass-to-tantalum anode).

Terminals: Axial-wire lead: Cathode and anode (type N32, N51, or N52 of MIL-STD-1276).

Rated temperature: -55°C to +85°C, voltage derated to +125°C (see figure 2).





FIGURE 2. Voltage derating with temperature.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

Rated voltage: See table I.

Capacitance (Cap.) nominal (nom): See table I.

Cap. tolerance: ± 10 percent or ± 20 percent (see table I).

Failure rate level: M, P, R, and S (see table I).

DC leakage (DCL) (max) (at +25°C): See table I.

Cap. (nominal): MIL-STD-202-305.

Dissipation factor (DF) (max): See table I.

Seal: MIL-STD-202-112, conditions A or D, and C.

Shock (specified pulse): MIL-STD-202-213, condition I (100 g's) or condition D (500 g's), as applicable.

Vibration, high frequency: MIL-STD-202-204, condition D (20 g's) or condition H (80 g's), as applicable.

Random vibration (as applicable): MIL-STD-202-214, test condition II-K (53.79 g's).

Thermal shock: MIL-STD-202-107, condition A (with step 3 at +125°C). The following shall apply:

Number of cycles: In accordance with MIL-PRF-39006.

DCL: 200 percent (max) of +25°C value of table I for qualification and group C.

DCL: 125 percent (max) of +25°C value of table I for group B.

ΔCap: Within ± 5 percent of initial measurement.

DF: 115 percent (max) of initial requirement.

Salt atmosphere (corrosion): MIL-STD-202-101, condition B (48 hours).

Solderability: MIL-STD-202-208.

Terminal strength:

Pull: MIL-STD-202-211, condition A.

Wire-lead bend: In accordance with MIL-PRF-39006.

Surge voltage: See table I.

Moisture resistance: MIL-STD-202-106.

DCL: 125 percent (max) of +25°C value of table I.

ΔCap: Within ±8 percent of initial measurement.

DF: 115 percent (maximum) of initial requirement.

Dielectric withstanding voltage (DWV): MIL-STD-202-301. 2,000 V dc, minimum.

Insulation resistance (IR): MIL-STD-202-302, condition B. 100 megohms, minimum.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

Low temperature (storage): Method 502 of MIL-STD-810.

DCL: See table I.

ΔCap: Within ± 5 percent of initial measurement.

DF: See table I.

Stability at low and high temperatures:

Step 1 (+25°C):

DCL: See table I.

ΔCap: Within tolerance of table I value.

DF: See table I.

Step 2 (-55°C):

Impedance. See table I.

ΔCap: See table I.

Step 3 (+25°C):

DCL: See table I.

ΔCap: Within ± 5 percent of step 1 value.

DF: See table I.

Step 4 (+85°C):

DCL: See table I.

ΔCap: See table I.

DF: See table I.

Step 5 (+125°C):

DCL: See table I.

ΔCap: See table I.

DF: See table I.

Step 6 (+25°C):

DCL: See table I.

ΔCap: Within ± 5 percent of step 1 value.

DF: See table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

Reverse voltage: As specified in MIL-PRF-39006.

DCL: See table I.

ΔCap: Within tolerance of table I value.

DF: See table I.

Life at +85°C: MIL-STD-202-108.

2,000 hours (qualification):

DCL: See table I.

ΔCap: Within ± 10 percent of initial measurement.

DF: See table I.

10,000 hours (group B) and extended life:

DCL (+85°C): 125 percent (max) of table I value.

DCL (+25°C): See table I.

ΔCap: Within +10 percent, -20 percent of initial measurement.

DF: 200 percent (max) of table I value.

DWV: 2,000 V dc, minimum.

IR.: 100 megohms, minimum.

AC ripple life at +85°C (qualification and group C):

Test ripple current: See table I.

Test voltage: 66.67 percent of rated voltage (see table I).

DCL: See table I.

ΔCap: Within ± 10 percent of initial measurement.

DF: See table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

Life at +125°C: MIL-STD-202-108.

DCL: See table I.

ΔCap: Within ± 10 percent of initial measurement.

DF: See table I.

DWV: 2,000 V dc, minimum.

IR.: 100 megohms, minimum.

2,000 hours (group C):

DCL (+125°C): 125 percent (max) of table I value.

DCL (+25°C): See table I.

ΔCap: Within +10 percent, -20 percent of initial measurement.

DF: 200 percent (max) of table I value.

DWV: 2,000 V dc, minimum.

IR.: 100 megohms, minimum.

Barometric pressure: MIL-STD-202-105, condition E (150,000 feet) (45,720.1 m).

Test voltage: Rated voltage.

Resistance to soldering heat: MIL-STD-202-210, condition C.

DCL: See table I.

ΔCap: Within ± 5 percent of initial measurement.

DF: See table I.

Marking: In accordance with MIL-PRF-39006.

Polarity of all parts: Series of (+) symbols encircling positive end (see figure 1).

Voltage groups (+85°C rated voltage):

I ---------- 6 V through 15 V

II ---------- 25 V through 75 V.

III ---------- 100 V and 125 V.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

| Cap. | Cap. tolerance | DC leakage (max) | | Dissipation factor (max) | ESR at +25°C (max) 2/ | Impedance (max) | Capacitance change at | | | Max +85°C 40 kHz ripple current 3/ | Case size | Part or Identifying Number (PIN) M39006/25- 4/ | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | +25°C | +85°C +125°C | | | | -55°C | +85°C | +125°C | | | Failure rate level (%/1,000 hrs) | | | |
| µF | ±% | µA | µA | % | Ohms | Ohms | % | % | % | mA rms | | M(1.0) | P(0.1) | R(0.01) | S(0.001) |
| 6 $V_{dc}$ at +85°C 1/ | | | | | | | 4 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 6.9 $V_{dc}$ | | | | |
| 220 | ±20 | 2 | 9 | 50 | 3.02 | 36 | -64 | +13 | +16 | 1,000 | T1 | 0001- | 0089- | 0177- | 0265- |
| 220 | ±10 | 2 | 9 | 50 | 3.02 | 36 | -64 | +13 | +16 | 1,000 | T1 | 0002- | 0090- | 0178- | 0266- |
| 820 | ±20 | 3 | 14 | 155 | 2.51 | 18 | -88 | +16 | +20 | 1,500 | T2 | 0003- | 0091- | 0179- | 0267- |
| 820 | ±10 | 3 | 14 | 155 | 2.51 | 18 | -88 | +16 | +20 | 1,500 | T2 | 0004- | 0092- | 0180- | 0268- |
| 1,500 | ±20 | 5 | 20 | 172 | 1.52 | 18 | -90 | +20 | +25 | 1,900 | T3 | 0005- | 0093- | 0181- | 0269- |
| 1,500 | ±10 | 5 | 20 | 172 | 1.52 | 18 | -90 | +20 | +25 | 1,900 | T3 | 0006- | 0094- | 0182- | 0270- |
| 2,200 | ±20 | 6 | 24 | 170 | 1.03 | 13 | -90 | +25 | +30 | 2,300 | T4 | 0007- | 0095- | 0183- | 0271- |
| 2,200 | ±10 | 6 | 24 | 170 | 1.03 | 13 | -90 | +25 | +30 | 2,300 | T4 | 0008- | 0096- | 0184- | 0272- |
| 8 $V_{dc}$ at +85°C 1/ | | | | | | | 5 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 9.2 $V_{dc}$ | | | | |
| 180 | ±20 | 2 | 9 | 41 | 3.02 | 45 | -60 | +13 | +16 | 1,000 | T1 | 0009- | 0097- | 0185- | 0273- |
| 180 | ±10 | 2 | 9 | 41 | 3.02 | 45 | -60 | +13 | +16 | 1,000 | T1 | 0010- | 0098- | 0186- | 0274- |
| 680 | ±20 | 3 | 14 | 130 | 2.54 | 22 | -83 | +16 | +20 | 1,500 | T2 | 0011- | 0099- | 0187- | 0275- |
| 680 | ±10 | 3 | 14 | 130 | 2.54 | 22 | -83 | +16 | +20 | 1,500 | T2 | 0012- | 0100- | 0188- | 0276- |
| 1,500 | ±20 | 5 | 20 | 170 | 1.50 | 18 | -90 | +20 | +25 | 1,900 | T3 | 0013- | 0101- | 0189- | 0277- |
| 1,500 | ±10 | 5 | 20 | 170 | 1.50 | 18 | -90 | +20 | +25 | 1,900 | T3 | 0014- | 0102- | 0190- | 0278- |
| 1,800 | ±20 | 7 | 25 | 138 | 1.02 | 14 | -90 | +25 | +30 | 2,300 | T4 | 0015- | 0103- | 0191- | 0279- |
| 1,800 | ±10 | 7 | 25 | 138 | 1.02 | 14 | -90 | +25 | +30 | 2,300 | T4 | 0016- | 0104- | 0192- | 0280- |
| 10 $V_{dc}$ at +85°C 1/ | | | | | | | 7 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 11.5 $V_{dc}$ | | | | |
| 150 | ±20 | 2 | 9 | 34 | 3.01 | 54 | -55 | +13 | +16 | 900 | T1 | 0017- | 0105- | 0193- | 0281- |
| 150 | ±10 | 2 | 9 | 34 | 3.01 | 54 | -55 | +13 | +16 | 900 | T1 | 0018- | 0106- | 0194- | 0282- |
| 560 | ±20 | 3 | 16 | 106 | 2.51 | 27 | -77 | +16 | +20 | 1,450 | T2 | 0019- | 0107- | 0195- | -0283- |
| 560 | ±10 | 3 | 16 | 106 | 2.51 | 27 | -77 | +16 | +20 | 1,450 | T2 | 0020- | 0108- | 0196- | 0284- |
| 1,200 | ±20 | 5 | 20 | 137 | 1.51 | 18 | -88 | +20 | +25 | 1,850 | T3 | 0021- | 0109- | 0197- | 0285- |
| 1,200 | ±10 | 5 | 20 | 137 | 1.51 | 18 | -88 | +20 | +25 | 1,850 | T3 | 0022- | 0110- | 0198- | 0286- |
| 1,500 | ±20 | 7 | 25 | 114 | 1.01 | 15 | -88 | +25 | +30 | 2,300 | T4 | 0023- | 0111- | 0199- | 0287- |
| 1,500 | ±10 | 7 | 25 | 114 | 1.01 | 15 | -88 | +25 | +30 | 2,300 | T4 | 0024- | 0112- | 0200- | 0288- |
| 15 $V_{dc}$ at +85°C 1/ | | | | | | | 10 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 17.2 $V_{dc}$ | | | | |
| 100 | ±20 | 2 | 9 | 30 | 3.98 | 72 | -44 | +13 | +16 | 900 | T1 | 0025- | 0113- | 0201- | 0289- |
| 100 | ±10 | 2 | 9 | 30 | 3.98 | 72 | -44 | +13 | +16 | 900 | T1 | 0026- | 0114- | 0202- | 0290- |
| 390 | ±20 | 3 | 16 | 74 | 2.52 | 31 | -66 | +16 | +20 | 1,450 | T2 | 0027- | 0115- | 0203- | 0291- |
| 390 | ±10 | 3 | 16 | 74 | 2.52 | 31 | -66 | +16 | +20 | 1,450 | T2 | 0028- | 0116- | 0204- | 0292- |
| 820 | ±20 | 6 | 24 | 111 | 1.80 | 22 | -77 | +20 | +25 | 1,800 | T3 | 0029- | 0117- | 0205- | 0293- |
| 820 | ±10 | 6 | 24 | 111 | 1.80 | 22 | -77 | +20 | +25 | 1,800 | T3 | 0030- | 0118- | 0206- | 0294- |
| 1,000 | ±20 | 8 | 32 | 92 | 1.22 | 17 | -77 | +25 | +30 | 2,300 | T4 | 0031- | 0119- | 0207- | 0295- |
| 1,000 | ±10 | 8 | 32 | 92 | 1.22 | 17 | -77 | +25 | +30 | 2,300 | T4 | 0032- | 0120- | 0208- | 0296- |
| 25 $V_{dc}$ at +85°C 1/ | | | | | | | 15 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 28.8 $V_{dc}$ | | | | |
| 68 | ±20 | 2 | 9 | 22 | 4.29 | 90 | -40 | +12 | +15 | 850 | T1 | 0033- | 0121- | 0209- | 0297- |
| 68 | ±10 | 2 | 9 | 22 | 4.29 | 90 | -40 | +12 | +15 | 850 | T1 | 0034- | 0122- | 0210- | 0298- |
| 270 | ±20 | 3 | 16 | 55 | 2.70 | 33 | -62 | +13 | +16 | 1,400 | T2 | 0035- | 0123- | 0211- | 0299- |
| 270 | ±10 | 3 | 16 | 55 | 2.70 | 33 | -62 | +13 | +16 | 1,400 | T2 | 0036- | 0124- | 0212- | 0300- |
| 560 | ±20 | 7 | 28 | 76 | 1.80 | 24 | -72 | +20 | +25 | 1,750 | T3 | 0037- | 0125- | 0213- | 0301- |
| 560 | ±10 | 7 | 28 | 76 | 1.80 | 24 | -72 | +20 | +25 | 1,750 | T3 | 0038- | 0126- | 0214- | 0302- |
| 680 | ±20 | 8 | 32 | 63 | 1.23 | 19 | -72 | +25 | +30 | 2,100 | T4 | 0039- | 0127- | 0215- | 0303- |
| 680 | ±10 | 8 | 32 | 63 | 1.23 | 19 | -72 | +25 | +30 | 2,100 | T4 | 0040- | 0128- | 0216- | 0304- |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

| Cap. | Cap. tolerance | DC leakage (max) | | Dissipation factor (max) | ESR at +25°C (max) 2/ | Impedance (max) | Capacitance change at | | | Max +85°C 40 kHz ripple current 3/ | Case size | PIN M39006/25- 4/ | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | +25°C | +85°C +125°C | | | | -55°C | +85°C | +125°C | | | Failure rate level (%/1,000 hrs) | | | |
| µF | ±% | µA | µA | % | Ohms | Ohms | % | % | % | mA rms | | M(1.0) | P(0.1) | R(0.01) | S(0.001) |
| 30 $V_{dc}$ at +85°C 1/ | | | | | | | 20 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 34.5 $V_{dc}$ | | | | |
| 56 | ±20 | 2 | 9 | 22 | 5.21 | 100 | -38 | +12 | +15 | 800 | T1 | 0041- | 0129- | 0217- | 0305- |
| 56 | ±10 | 2 | 9 | 22 | 5.21 | 100 | -38 | +12 | +15 | 800 | T1 | 0042- | 0130- | 0218- | 0306- |
| 220 | ±20 | 3 | 16 | 42 | 2.53 | 36 | -60 | +13 | +16 | 1,200 | T2 | 0043- | 0131- | 0219- | 0307- |
| 220 | ±10 | 3 | 16 | 42 | 2.53 | 36 | -60 | +13 | +16 | 1,200 | T2 | 0044- | 0132- | 0220- | 0308- |
| 470 | ±20 | 8 | 32 | 64 | 1.81 | 25 | -65 | +20 | +25 | 1,500 | T3 | 0045- | 0133- | 0221- | 0309- |
| 470 | ±10 | 8 | 32 | 64 | 1.81 | 25 | -65 | +20 | +25 | 1,500 | T3 | 0046- | 0134- | 0222- | 0310- |
| 560 | ±20 | 9 | 36 | 55 | 1.30 | 20 | -65 | +25 | +30 | 2,000 | T4 | 0047- | 0135- | 0223- | 0311- |
| 560 | ±10 | 9 | 36 | 55 | 1.30 | 20 | -65 | +25 | +30 | 2,000 | T4 | 0048- | 0136- | 0224- | 0312- |
| 50 $V_{dc}$ at +85°C 1/ | | | | | | | 30 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 57.5 $V_{dc}$ | | | | |
| 33 | ±20 | 2 | 9 | 12.3 | 4.95 | 135 | -29 | +10 | +12 | 700 | T1 | 0049- | 0137- | 0225- | 0313- |
| 33 | ±10 | 2 | 9 | 12.3 | 4.95 | 135 | -29 | +10 | +12 | 700 | T1 | 0050- | 0138- | 0226- | 0314- |
| 120 | ±20 | 4 | 24 | 22.5 | 2.49 | 49 | -42 | +12 | +15 | 1,200 | T2 | 0051- | 0139- | 0227- | 0315- |
| 120 | ±10 | 4 | 24 | 22.5 | 2.49 | 49 | -42 | +12 | +15 | 1,200 | T2 | 0052- | 0140- | 0228- | 0316- |
| 270 | ±20 | 8 | 32 | 37 | 1.82 | 29 | -46 | +20 | +25 | 1,450 | T3 | 0053- | 0141- | 0229- | 0317- |
| 270 | ±10 | 8 | 32 | 37 | 1.82 | 29 | -46 | +20 | +25 | 1,450 | T3 | 0054- | 0142- | 0230- | 0318- |
| 330 | ±20 | 9 | 36 | 38 | 1.53 | 22 | -46 | +25 | +30 | 1,900 | T4 | 0055- | 0143- | 0231- | 0319- |
| 330 | ±10 | 9 | 36 | 38 | 1.53 | 22 | -46 | +25 | +30 | 1,900 | T4 | 0056- | 0144- | 0232- | 0320- |
| 60 $V_{dc}$ at +85°C 1/ | | | | | | | 40 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 69.0 $V_{dc}$ | | | | |
| 27 | ±20 | 3 | 12 | 10.2 | 5.01 | 144 | -24 | +10 | +12 | 700 | T1 | 0057- | 0145- | 0233- | 0321- |
| 27 | ±10 | 3 | 12 | 10.2 | 5.01 | 144 | -24 | +10 | +12 | 700 | T1 | 0058- | 0146- | 0234- | 0322- |
| 100 | ±20 | 4 | 20 | 19 | 2.52 | 54 | -36 | +12 | +15 | 1,100 | T2 | 0059- | 0147- | 0235- | 0323- |
| 100 | ±10 | 4 | 20 | 19 | 2.52 | 54 | -36 | +12 | +15 | 1,100 | T2 | 0060- | 0148- | 0236- | 0324- |
| 220 | ±20 | 8 | 32 | 30 | 1.81 | 29 | -40 | +16 | +20 | 1,400 | T3 | 0061- | 0149- | 0237- | 0325- |
| 220 | ±10 | 8 | 32 | 30 | 1.81 | 29 | -40 | +16 | +20 | 1,400 | T3 | 0062- | 0150- | 0238- | 0326- |
| 270 | ±20 | 9 | 36 | 27 | 1.33 | 23 | -45 | +20 | +25 | 1,850 | T4 | 0063- | 0151- | 0239- | 0327- |
| 270 | ±10 | 9 | 36 | 27 | 1.33 | 23 | -45 | +20 | +25 | 1,850 | T4 | 0064- | 0152- | 0240- | 0328- |
| 75 $V_{dc}$ at +85°C 1/ | | | | | | | 50 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 86.2 $V_{dc}$ | | | | |
| 22 | ±20 | 3 | 12 | 8.5 | 5.13 | 157 | -19 | +10 | +12 | 600 | T1 | 0065- | 0153- | 0241- | 0329- |
| 22 | ±10 | 3 | 12 | 8.5 | 5.13 | 157 | -19 | +10 | +12 | 600 | T1 | 0066- | 0154- | 0242- | 0330- |
| 82 | ±20 | 4 | 24 | 15.2 | 2.46 | 63 | -30 | +12 | +15 | 1,000 | T2 | 0067- | 0155- | 0243- | 0331- |
| 82 | ±10 | 4 | 24 | 15.2 | 2.46 | 63 | -30 | +12 | +15 | 1,000 | T2 | 0068- | 0156- | 0244- | 0332- |
| 180 | ±20 | 9 | 36 | 24.4 | 2.23 | 30 | -35 | +16 | +20 | 1,300 | T3 | 0069- | 0157- | 0245- | 0333- |
| 180 | ±10 | 9 | 36 | 24.4 | 2.23 | 30 | -35 | +16 | +20 | 1,300 | T3 | 0070- | 0158- | 0246- | 0334- |
| 220 | ±20 | 10 | 40 | 37.0 | 1.80 | 24 | -40 | +20 | +25 | 1,800 | T4 | 0071- | 0159- | 0247- | 0335- |
| 220 | ±10 | 10 | 40 | 37.0 | 1.80 | 24 | -40 | +20 | +25 | 1,800 | T4 | 0072- | 0160- | 0248- | 0336- |
| 100 $V_{dc}$ at +85°C 1/ | | | | | | | 65 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 115.0 $V_{dc}$ | | | | |
| 10 | ±20 | 3 | 12 | 4.5 | 5.97 | 200 | -17 | +10 | +12 | 800 | T1 | 0073- | 0161- | 0249- | 0337- |
| 10 | ±10 | 3 | 12 | 4.5 | 5.97 | 200 | -17 | +10 | +12 | 800 | T1 | 0074- | 0162- | 0250- | 0338- |
| 39 | ±20 | 5 | 24 | 10.4 | 3.54 | 80 | -20 | +12 | +15 | 1,300 | T2 | 0075- | 0163- | 0251- | 0339- |
| 39 | ±10 | 5 | 24 | 10.4 | 3.54 | 80 | -20 | +12 | +15 | 1,300 | T2 | 0076- | 0164- | 0252- | 0340- |
| 68 | ±20 | 10 | 40 | 11.3 | 2.21 | 40 | -30 | +14 | +16 | 1,600 | T3 | 0077- | 0165- | 0253- | 0341- |
| 68 | ±10 | 10 | 40 | 11.3 | 2.21 | 40 | -30 | +14 | +16 | 1,600 | T3 | 0078- | 0166- | 0254- | 0342- |
| 120 | ±20 | 12 | 48 | 25 | 2.76 | 30 | -35 | +15 | +17 | 2,000 | T4 | 0079- | 0167- | 0255- | 0343- |
| 120 | ±10 | 12 | 48 | 25 | 2.76 | 30 | -35 | +15 | +17 | 2,000 | T4 | 0080- | 0168- | 0256- | 0344- |
| 125 $V_{dc}$ at +85°C 1/ | | | | | | | 85 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 144.0 $V_{dc}$ | | | | |
| 6.8 | ±20 | 3 | 12 | 6.0 | 11.71 | 300 | -14 | +10 | +12 | 700 | T1 | 0081- | 0169- | 0257- | 0345- |
| 6.8 | ±10 | 3 | 12 | 6.0 | 11.71 | 300 | -14 | +10 | +12 | 700 | T1 | 0082- | 0170- | 0258- | 0346- |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

| Cap. | Cap. tolerance | DC leakage (max) | | Dissipation factor (max) | ESR at +25°C (max) 2/ | Impedance (max) | Capacitance change at | | | Max +85°C 40 kHz ripple current 3/ | Case size | PIN M39006/25- 4/ | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | +25°C | +85°C +125°C | | | | -55°C | +85°C | +125°C | | | Failure rate level (%/1,000 hrs) | | | |
| µF | ±% | µA | µA | % | Ohms | Ohms | % | % | % | mA rms | | M(1.0) | P(0.1) | R(0.01) | S(0.001) |
| 125 $V_{dc}$ at +85°C 1/ | | | | | | 85 $V_{dc}$ at +125°C 1/ | | | | Surge (+85°C) 144.0 $V_{dc}$ -Continued. | | | | | |
| 27 | ±20 | 5 | 24 | 7.2 | 3.54 | 90 | -18 | +12 | +15 | 1,200 | T2 | 0083- | 0171- | 0259- | 0347- |
| 27 | ±10 | 5 | 24 | 7.2 | 3.54 | 90 | -18 | +12 | +15 | 1,200 | T2 | 0084- | 0172- | 0260- | 0348- |
| 47 | ±20 | 10 | 40 | 7.9 | 2.23 | 50 | -26 | +14 | +16 | 1,500 | T3 | 0085- | 0173- | 0261- | 0349- |
| 47 | ±10 | 10 | 40 | 7.9 | 2.23 | 50 | -26 | +14 | +16 | 1,500 | T3 | 0086- | 0174- | 0262- | -0350- |
| 82 | ±20 | 12 | 48 | 17.4 | 2.82 | 32 | -30 | +15 | +17 | 1,900 | T4 | 0087- | 0175- | 0263- | 0351- |
| 82 | ±10 | 12 | 48 | 17.4 | 2.82 | 32 | -30 | +15 | +17 | 1,900 | T4 | 0088- | 0176- | 0264- | 0352- |

1/ Reverse voltage rating at +85°C is 3 V dc and at +125°C is 2 V dc.
2/ Maximum ESR is calculated by the following equation:

$$ESR_{(max)} = \frac{DF}{2\pi f C}$$

Where: $DF$ = Maximum dissipation factor from table I;
$f$ = 120 Hz;
$C$ = Nominal capacitance.

3/ For ripple current limits at various temperatures, voltages, and frequencies, see table II.
4/ Dash number shall include the letter “H” to indicate the optional vibration and shock requirements (i.e., 53.79 g’s random vibration,80 g’s sinusoidal vibration, and 500 g’s shock) or the “-“ will be deleted. The acquiring activity may substitute an “H” designated part in place of a non “H” designated part at their option.

TABLE II. Ripple current multipliers versus frequency, temperature, and applied peak voltage. 1/ 2/ 3/ 4/ 5/

| Frequency of applied ripple current | | 120 Hz | | | | 800 Hz | | | | 1 kHz | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Ambient still air temperature in °C | | ≤+55 | +85 | +105 | +125 | ≤+55 | +85 | +105 | +125 | ≤+55 | +85 | +105 | +125 |
| % of +85°C rated peak voltage | 100% | .60 | .39 | - | - | .71 | .43 | - | - | .72 | .45 | - | - |
| | 90% | .60 | .46 | - | - | .71 | .55 | - | - | .72 | .55 | - | - |
| | 80% | .60 | .52 | .35 | - | .71 | .62 | .42 | - | .72 | .62 | .42 | - |
| | 70% | .60 | .58 | .44 | - | .71 | .69 | .52 | - | .72 | .70 | .52 | - |
| | 66-2/3% | .60 | .60 | .46 | .27 | .71 | .71 | .55 | .32 | .72 | .72 | .55 | .32 |
| Frequency of applied ripple current | | 10 kHz | | | | 40 kHz | | | | 100 kHz | | | |
| Ambient still air temperature in °C | | ≤+55 | +85 | +105 | +125 | ≤+55 | +85 | +105 | +125 | ≤+55 | +85 | +105 | +125 |
| % of +85°C rated peak voltage | 100% | .88 | .55 | - | - | 1.0 | .63 | - | - | 1.1 | .69 | - | - |
| | 90% | .88 | .67 | - | - | 1.0 | .77 | - | - | 1.1 | .85 | - | - |
| | 80% | .88 | .76 | .52 | - | 1.0 | .87 | .59 | - | 1.1 | .96 | .65 | - |
| | 70% | .88 | .85 | .64 | - | 1.0 | .97 | .73 | - | 1.1 | 1.07 | .80 | - |
| | 66-2/3% | .88 | .88 | .68 | .40 | 1.0 | 1.0 | .77 | .45 | 1.1 | 1.1 | .85 | .50 |

1/ At +125°C, the rated voltage of the capacitors decreases to 66.67 percent of the +85°C rated voltage.
2/ The peak of the applied ac ripple voltage plus the applied dc voltage must not exceed the dc voltage rating of the capacitor either forward or reverse.
3/ The ripple current listed in table I represents a rating calculated by using a maximum internal temperature rise (ΔT) at +50°C at 40 kHz at +85°C ambient temperature, with a maximum peak rated voltage of 66.67 percent of the +85°C peak voltage rating.
4/ The maximum allowable internal temperature rise (ΔT) decreases linearly to a calculated 10°C rise at +125°C ambient.
5/ The internal temperature rise is directly proportional to the ESR of the capacitor, and ESR increases with decreasing frequency.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-39006, this document references the following:

| | | |
|---|---|---|
| MIL-PRF-39006/21 | MIL-STD-202-108 | MIL-STD-202-214 |
| MIL-PRF-39006/22 | MIL-STD-202-112 | MIL-STD-202-301 |
| MIL-PRF-39006/31 | MIL-STD-202-204 | MIL-STD-202-302 |
| MIL-STD-202-101 | MIL-STD-202-208 | MIL-STD-202-305 |
| MIL-STD-202-105 | MIL-STD-202-210 | MIL-STD-810 |
| MIL-STD-202-106 | MIL-STD-202-211 | MIL-STD-1276 |
| MIL-STD-202-107 | MIL-STD-202-213 | |

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2023-015)

Review activities:
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:18Z
Check the source to verify that this is the current version before use.