INCH-POUND
MIL-PRF-39006/30A
AMENDMENT 1
2 April 2003

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM
(POLARIZED, SINTERED SLUG), 85°C (VOLTAGE DERATED TO 125°C),
ESTABLISHED RELIABILITY, STYLE CLR90

This amendment forms a part of MIL-PRF-39006/30A, dated 17 April 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 9

Footnote 4, add the following sentence after deleted.: The acquiring activity may substitute an "H" designated part in place of a non "H" designated part at their option. Also in footnote 4 change 51 g's to 53.79 g's

PAGE 11

Thermal shock: After Number of cycles: delete "300 for qualification and group C; 30 for group B." and replace with "In accordance with MIL-PRF-39006, the following shall apply."

PAGE 14

Resistance to soldering heat: change from condition "G" to condition "C".

After Marking: and after Example: but before Voltage groups insert the following: "Polarity: Series of plus (+) symbols encircling positive end (see figure 1)."

After voltage groups add the following: "Substitution of H designated parts for non H designated parts: The acquiring activity may substitute an H designated part in place of a non H designated part at their option."

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5910-2207-03)

Review activities:
Navy - AS, MC, OS
Air Force – 19

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.