
MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM (POLARIZED, SINTERED SLUG) (EXTENDED RANGE), 85°C (VOLTAGE DERATED TO 125°C), ESTABLISHED RELIABILITY, STYLE CLR91

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the capacitors described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-39006.



CIRCUIT DIAGRAM

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses.
3. Metric equivalents are given for general information only.
4. The weld shall not be enclosed in the end seal.

FIGURE 1. Style CLR91 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

Dimensions				
	Basic case		Insulated case	
Case size	L 1/ +.031 (0.79) -.016 (0.41)	B ±.016 (0.41)	D max	E ±.250 (6.35)
T1	.453(11.51)	.188 (4.78)	.219 (5.56)	1.500(38.10)
T2	.641(16.28)	.281 (7.14)	.312 (7.92)	2.250(57.15)
T3	.766(19.46)	.375 (9.52)	.406(10.31)	2.250(57.15)
T4	1.062(26.97)	.375 (9.52)	.406(10.31)	2.250(57.15)

1/ Length of basic case sleeving shall be as specified in MIL-C-39006.

FIGURE 1. Style CLR91 capacitors - Continued.

QUALIFICATION:

A manufacturer shall be considered qualified to this specification sheet by similarity if the manufacturer is qualified to style CLR81 capacitors in MIL-C-39006/25 and if the design and construction of the capacitors in this specification sheet is the same as the design and construction of the capacitors covered by MIL-C-39006/25.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Case type: Tantalum, tubular, insulated.

Seal type: Hermetic (glass-to-tantalum anode).

Terminals: Axial-wire lead: Cathode and anode (type N32, N51, or N52 of MIL-STD-1276).

Rated temperature: -55°C to +85°C, voltage derated to +125°C (see figure 2).




FIGURE 2. Voltage derating with temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

Rated voltage: See table I.

Capacitance (Cap) (nom): See table I.

Cap tolerance: ±10 percent or ±20 percent (see table I).

FR level: M, P, R, and S (see table I).

DC leakage (DCL) (max) (at +25°C): See table I.

Cap (nominal): Method 305 of MIL-STD-202.

Dissipation factor (DF) (max): See table I.

Seal: Method 112 of MIL-STD-202, conditions A or D, and C.

Shock (specified pulse): Method 213 of MIL-STD-202, condition I (100 g's) or condition D (500 g's), as applicable.

Vibration, high frequency: Method 204 of MIL-STD-202, condition D (20 g's), or condition H (80 g's), as applicable.

Random vibration (when applicable): Method 214 of MIL-STD-202, test condition II-K (51 g's).

Thermal shock: Method 107 of MIL-STD-202, condition A (with step 3 at +125°C).

Number of cycles: 300 for qualification and group C; 30 for group B.

DCL: 200 percent (max) of 25°C value of table I for qualification and group C.

DCL: 125 percent (max) of +25°C value of table I for group B.

ΔCap: Within ±5 percent of initial measurement.

DF: 115 percent (max) of initial requirement.

Salt spray (corrosion): Method 101 of MIL-STD-202, condition B (48 hours).

Solderability: Method 208 of MIL-STD-202.

Terminal strength:

Pull: Method 211 of MIL-STD-202, condition A.

Wire-lead bend: In accordance with MIL-C-39006.

Surge voltage: See table I.

Moisture resistance: Method 106 of MIL-STD-202.

DCL: 125 percent (max) of 25°C value of table I.

ΔCap: Within ±8 percent of initial measurement.

DF: 115 percent (max) of initial requirement.

Dielectric withstanding voltage (DWV): Method 301 of MIL-STD-202. 2,000 V dc, minimum.

Insulation resistance (IR): Method 302 of MIL-STD-202, condition B. 100 megohms, minimum.

Low temperature (storage): Method 502 of MIL-STD-810.

DCL: See table I.

ΔCap: Within ±5 percent of initial measurement.

DF: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

1/ Rated voltage (+85°C)	Cap.	Cap. tolerance	DC leakage (max)		Dissipation factor (max)	2/ ESR at +25°C (max)	1/ Derated voltage (+125°C)	Surge voltage (+85°C)	Impedance (max)	Capacitance change at			3/ Max 85°C 40 kHz ripple current	Case size	PIN M39006/31- 4/			
			+25°C	+85°C, +125°C						-55°C	+85°C	+125°C			Failure rate level (%/1,000 hr.)			
															M(1.0)	P(0.1)	R(0.01)	S(0.001)
V dc	µF	%	µA	µA	%	ohms	V dc	V dc	ohms	%	%	%	mA rms					
6	220	±20	2	9	25	1.51	4	6.9	36	-64	+13	+16	1000	T1	0001-	0089-	0177-	0265-
6	220	±10	2	9	25	1.51	4	6.9	36	-64	+13	+16	1000	T1	0002-	0090-	0178-	0266-
6	820	±20	3	14	77.5	1.26	4	6.9	18	-88	+16	+20	1500	T2	0003-	0091-	0179-	0267-
6	820	±10	3	14	77.5	1.26	4	6.9	18	-88	+16	+20	1500	T2	0004-	0092-	0180-	0268-
6	1500	±20	5	28	86	0.76	4	6.9	18	-90	+20	+25	1900	T3	0005-	0093-	0181-	0269-
6	1500	±10	5	28	86	0.76	4	6.9	18	-90	+20	+25	1900	T3	0006-	0094-	0182-	0270-
6	2200	±20	6	24	85	0.52	4	6.9	13	-90	+25	+30	2300	T4	0007-	0095-	0183-	0271-
6	2200	±10	6	24	85	0.52	4	6.9	13	-90	+25	+30	2300	T4	0008-	0096-	0184-	0272-
8	180	±20	2	9	20.5	1.51	5	9.2	45	-60	+13	+16	1000	T1	0009-	0097-	0185-	0273-
8	180	±10	2	9	20.5	1.51	5	9.2	45	-60	+13	+16	1000	T1	0010-	0098-	0186-	0274-
8	680	±20	3	14	65	1.27	5	9.2	22	-83	+16	+20	1500	T2	0011-	0099-	0187-	0275-
8	680	±10	3	14	65	1.27	5	9.2	22	-83	+16	+20	1500	T2	0012-	0100-	0188-	0276-
8	1500	±20	5	28	85	0.75	5	9.2	18	-90	+20	+25	1900	T3	0013-	0101-	0189-	0277-
8	1500	±10	5	28	85	0.75	5	9.2	18	-90	+20	+25	1900	T3	0014-	0102-	0190-	0278-
8	1800	±20	7	25	69	0.51	5	9.2	14	-90	+25	+30	2300	T4	0015-	0103-	0191-	0279-
8	1800	±10	7	25	69	0.51	5	9.2	14	-90	+25	+30	2300	T4	0016-	0104-	0192-	0280-
10	150	±20	2	9	17	1.51	7	11.5	54	-55	+13	+16	900	T1	0017-	0105-	0193-	0281-
10	150	±10	2	9	17	1.51	7	11.5	54	-55	+13	+16	900	T1	0018-	0106-	0194-	0282-
10	560	±20	3	16	53	1.26	7	11.5	27	-77	+16	+20	1450	T2	0019-	0107-	0195-	0283-
10	560	±10	3	16	53	1.26	7	11.5	27	-77	+16	+20	1450	T2	0020-	0108-	0196-	0284-
10	1200	±20	5	28	68.5	0.76	7	11.5	18	-88	+20	+25	1850	T3	0021-	0109-	0197-	0285-
10	1200	±10	5	28	68.5	0.76	7	11.5	18	-88	+20	+25	1850	T3	0022-	0110-	0198-	0286-
10	1500	±20	7	25	57	0.51	7	11.5	15	-88	+25	+30	2300	T4	0023-	0111-	0199-	0287-
10	1500	±10	7	25	57	0.51	7	11.5	15	-88	+25	+30	2300	T4	0024-	0112-	0200-	0288-
15	100	±20	2	9	15	1.99	10	17.2	72	-44	+13	+16	900	T1	0025-	0113-	0201-	0289-
15	100	±10	2	9	15	1.99	10	17.2	72	-44	+13	+16	900	T1	0026-	0114-	0202-	0290-
15	390	±20	3	16	37	1.26	10	17.2	31	-66	+16	+20	1450	T2	0027-	0115-	0203-	0291-
15	390	±10	3	16	37	1.26	10	17.2	31	-66	+16	+20	1450	T2	0028-	0116-	0204-	0292-
15	820	±20	6	24	55.5	0.90	10	17.2	22	-77	+20	+25	1800	T3	0029-	0117-	0205-	0293-
15	820	±10	6	24	55.5	0.90	10	17.2	22	-77	+20	+25	1800	T3	0030-	0118-	0206-	0294-
15	1080	±20	8	32	46	0.61	10	17.2	17	-77	+25	+30	2300	T4	0031-	0119-	0207-	0295-
15	1080	±10	8	32	46	0.61	10	17.2	17	-77	+25	+30	2300	T4	0032-	0120-	0208-	0296-
25	68	±20	2	9	11	2.15	15	28.8	90	-48	+12	+15	850	T1	0033-	0121-	0209-	0297-
25	68	±10	2	9	11	2.15	15	28.8	90	-48	+12	+15	850	T1	0034-	0122-	0210-	0298-
25	270	±20	3	16	27.5	1.35	15	28.8	33	-62	+13	+16	1400	T2	0035-	0123-	0211-	0299-
25	270	±10	3	16	27.5	1.35	15	28.8	33	-62	+13	+16	1400	T2	0036-	0124-	0212-	0300-
25	560	±20	7	28	38	0.90	15	28.8	24	-72	+20	+25	1750	T3	0037-	0125-	0213-	0301-
25	560	±10	7	28	38	0.90	15	28.8	24	-72	+20	+25	1750	T3	0038-	0126-	0214-	0302-
25	680	±20	8	32	31.5	0.62	15	28.8	19	-72	+25	+30	2100	T4	0039-	0127-	0215-	0303-
25	680	±10	8	32	31.5	0.62	15	28.8	19	-72	+25	+30	2100	T4	0040-	0128-	0216-	0304-

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-02-21T16:20Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

1/ Rated voltage (+85°C)	Cap.	Cap. tolerance	DC leakage (max) +25°C	DC leakage (max) +85°C, +125°C	Dissipation factor (max)	2/ Eq'l at +25°C (max)	1/ Derated voltage (+125°C)	Surge voltage (+85°C)	Impedance (max)	Capacitance change at -55°C	Capacitance change at +85°C	Capacitance change at +125°C	1/ Max 85°C 40 kHz ripple current	Case size	PIN M39006/31- 4/ Failure rate level (%/1,000 hr.) M(1.0)	P(0.1)	R(0.01)	S(0.001)
See footnotes on next page.																		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

1/ Reverse voltage rating at 85°C is 3 V dc, and at 125°C is 2 V dc.
2/ Maximum ESR is calculated by the following equation:

$$ESR\ (max) = \frac{DF}{2\pi fC}, \text{ where:}$$

DF = Maximum dissipation factor from table I;
f = 120 Hz;
C = Nominal capacitance.

3/ For ripple current limits at various temperatures, voltages, and frequencies, see table II.
4/ Dash number shall include the letter "H" to indicate the optional vibration and shock requirements (i.e., 51 g's random vibration, 80 g's sinusoidal vibration, and 500 g's shock) or "-" will be deleted.

Stability at low and high temperatures:

Step 1 (+25°C):

DCL: See table I.

ΔCap: Within tolerance of table I value.

DF: See table I.

Step 2 (-55°C):

Impedance: See table I.

ΔCap: See table I.

Step 3 (+25°C):

DCL: See table I.

ΔCap: Within ±5 percent of step 1 value.

DF: See table I.

Step 4 (+85°C):

DCL: See table I.

ΔCap: See table I.

DF: See table I.

Step 5 (+125°C):

DCL: See table I.

ΔCap: See table I.

DF: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

TABLE II. Ripple current multipliers versus frequency, temperature, and applied peak voltage. 1/ 2/ 3/ 4/ 5/

Frequency of applied ripple current		120 Hz				600 Hz				1 kHz				10 kHz				40 kHz				100 kHz			
		Temp °C				Temp °C				Temp °C				Temp °C				Temp °C				Temp °C			
Ambient still air		≤55°	85°	105°	125°	≤55°	85°	105°	125°	≤55°	85°	105°	125°	≤55°	85°	105°	125°	≤55°	85°	105°	125°	≤55°	85°	105°	125°
% of 85°C rated peak voltage	100%	.60	.39	---	---	.71	.43	---	---	.72	.45	---	---	.88	.55	---	---	1.0	.63	---	---	1.1	.69	---	---
	90%	.60	.46	---	---	.71	.55	---	---	.72	.55	---	---	.88	.67	---	---	1.0	.77	---	---	1.1	.85	---	---
	80%	.60	.52	.35	---	.71	.62	.42	---	.72	.62	.42	---	.88	.76	.52	---	1.0	.87	.59	---	1.1	.96	.65	---
	70%	.60	.58	.44	---	.71	.69	.52	---	.72	.70	.52	---	.88	.85	.64	---	1.0	.97	.73	---	1.1	1.07	.80	---
	66 2/3%	.60	.60	.46	.27	.71	.71	.55	.32	.72	.72	.55	.32	.88	.88	.68	.40	1.0	1.0	.77	.45	1.1	1.1	.85	.50

1/ At 125°C the rated voltage of the capacitors decreases to 66 2/3 percent of the 85°C rated voltage.
2/ The peak of the applied ac ripple voltage plus the applied dc voltage must not exceed the dc voltage rating of the capacitor, either forward or reverse.
3/ The ripple current listed in table I represents a rating calculated by using a maximum internal temperature rise (ΔT) of 50°C at 40 kHz and at 85°C ambient temperature, with a maximum peak rated voltage of 66 2/3 percent of the 85°C peak voltage rating.
4/ The maximum allowable internal temperature rise (ΔT) decreases linearly to a calculated 10°C rise at 125°C ambient.
5/ The internal temperature rise is directly proportional to the ESR of the capacitor, and ESR increases with decreasing frequency.

Source: https://assist.dla.mil -- Downloaded: 2026-02-21T16:20Z
Check the source to verify that this is the current version before use.

Step 6 (+25°C):

DCL: See table I.

ΔCap: Within ±5 percent of step 1 value.

DF: See table I.

Reverse voltage: As specified in MIL-C-39006.

DCL: See table I.

ΔCap: Within tolerance of table I value.

DF: See table I.

Life at 85°C: Method 108 of MIL-STD-202.

2,000 hours (qualification):

DCL: See table I.

ΔCap: Within ±10 percent of initial measurement.

DF: See table I.

10,000 hours (group B) and extended life:

DCL (85°C): 125 percent (max) of table I value.

DCL (25°C): See table I.

ΔCap: Within +10, -20 percent of initial measurement.

DF: 200 percent (max) of table I value.

DWV: 2,000 V dc, minimum.

IR: 100 megohms, minimum.

AC ripple at 85°C (qualification and group C):

Test ripple current: See table I.

Test voltage: 66.67 percent of rated voltage (see table I).

DCL: See table I.

ΔCap: Within ±10 percent of initial measurement.

DF: See table I.

Life at 125°C: Method 108 of MIL-STD-202.

DCL: See table I.

ΔCap: Within ±10 percent of initial measurement.

DF: See table I.

DWV: 2,000 V dc, minimum.

IR: 100 megohms, minimum.

2,000 hours (group C):

DCL (125°C): 125 percent (max) of table I value.

DCL (25°C): See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.

ΔCap: Within +10 percent, -20 percent of initial measurement.

DF: 200 percent (max) of table I value.

DWV: 2,000 V dc, minimum.

IR: 100 megohms, minimum.

Barometric pressure: Method 105 of MIL-STD-202, condition E (150,000 feet) (45,720.1 m).

Test voltage: Rated voltage.

Resistance to soldering heat: Method 210 of MIL-STD-202, condition G.

DCL: See table I.

ΔCap: Within ±5 percent of initial measurement.

DF: See table I.

Marking: In accordance with MIL-C-39006, with the following exception: The manufacturer may mark the T1 case size "H" designated capacitors as follows:

EXAMPLE: ~~M39006/~~
31H0001
JAN TH
12345
9615A

Voltage groups (85°C rated voltage):

I.....6 V through 15 V

II.....25 V through 75 V

III.....100 V and 125 V

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR
~~Navy~~ - AS, ~~MC~~, ~~OS~~
Air Force -17, 19, 99

Preparing activity:
DLA - ES

(Project 5910-1882)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:20Z
Check the source to verify that this is the current version before use.