MIL-A-52019B(ME)
22 September 1981
SUPERSEDING
MIL-A-52019A(ME)
22 May 1968

MILITARY SPECIFICATION

ADAPTER ASSEMBLY, GLIDE ANGLE LIGHT TO STAKE OR CONE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an adapter assembly for airport and heliport glide angle lights.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

HH-L-361	- Linings; Brake (Automotive-Use).
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple Wall.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U.S. Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government document, drawings, and publications. The following other Government documents drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13205E3550	- Electric Lighting Equipment Sets Airport and Heliport, Adapter Assembly Glide Angle Light.

(Copies of specifications, standards, and drawings required by contractors in connection with specific, acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specifications to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposed shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B26 - Aluminum-Alloy Sand Castings, Specification for
B209 - Aluminum-Alloy Sheet and Plate, Specification for
B211 - Aluminum-Alloy Bar, Rod, and Wire, Specification for
B221 - Aluminum-Alloy Extruded Bar, Rod, Wire, Shape, and Tube, Specification for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of conflict between the test of this specification and the reference cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The mounting adapter shall be constructed in accordance with Top Assembly TA13205E3550, and as specified herein. The adapter shall rotate freely through 360 degrees, and all adjusting screws and bolts shall turn freely by hand throughout their range of adjustment. Thumb screws and knurled bolts shall securely lock the moving parts of the adapter, and the adapter shall securely mount on a 1-1/4 by 1-1/4 by 1/4-inch standard aluminum angle when adjustment screws are tightened by hand.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the mounting adapter. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The contractor shall furnish one mounting adapter for examination and testing within the time frame specified (see 6.2) to prove, prior to starting production, that his production methods will produce mounting adapters that comply with the requirements of this specification (see 6.3). Examination and tests shall be those specified herein.

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Material not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.3.1 Aluminum alloy. Aluminum alloy shall conform to the following specifications unless otherwise shown on the drawings:

Form	Specifications
Castings, sand	ASTM B26, alloy 443.0, temper F
Sheets and plates	ASTM B209, alloy 6061, temper T6
Bars, rods, and shapes	ASTM B211, alloy 6061, temper T6; or ANSI/ASTM B221, alloy 6061, temper T6

3.3.2 Friction disc material. Friction disc material shall conform to HH-L-361, type II, composition B, class M.

3.4 Identification marking. The adapter shall be identified in accordance with MIL-STD-130.

3.5 Treatment and painting. The portions of the adapter normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. All parts and components of the mounting adapter including castings, stampings, machined surfaces, and welds shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, weld splatter, or any other defects that could impair its operation or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The mounting adapter shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, inspection level S-3.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The mounting adapters shall be examined for the following defects:

Major

101. Nonconformance with any attribute designated for inspection by the drawings.
102. Adapter does not rotate freely through 360 degrees.
103. Any adjusting screw or bolt does not turn freely by hand throughout its range of adjustment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

104. When clamped on a 1-1/4- by 1-1/4- by 1/4-inch standard aluminum angle and adjustment screws are tightened by hand, relative motion between the adapter and the angle can be felt by hand.
105. Thumb screws and knurled bolts do not securely lock moving parts of adapter.
106. Treatment and painting not as specified.
107. Workmanship not as specified.

Minor

201. Identification marking missing, incomplete, or not legible.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

Major

108. Materials, methods, or containers not as specified for level A or B. Each incorrect material, method, or container shall constitute one defect.
109. Box closure and sealing not in accordance with the specified method for level A.
110. Quantities packed together exceed specified quantities for level A or B.
111. Marking missing, illegible, incorrect, or incomplete for level A, level B or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each adapter assembly shall be preserved in accordance with MIL-P-116, method III using a close fitting box conforming to PPP-B-636, W6c, style optional. Box closure and sealing shall be as specified for method V in the appendix to the box specification.

5.1.2 Commercial. Adapter assemblies shall be preserved in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

5.2.1 Level A. Adapter assemblies, preserved as specified in 5.1, shall be packed together in close-fitting boxes conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed 200 pounds. Box closure and strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. Adapter assemblies, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-636, V3c, style optional, or PPP-B-640, class 2, grade A, style optional. The gross weight or size shall not exceed the limitations of the box specification. Box closure and sealing shall be in accordance with the appendix to the applicable box specifications.

5.2.3 Commercial. Adapter assemblies, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The adapters are intended for use in mounting a glide angle approach light to a stake or cone.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2).
(c) When the government will conduct any or all of the preproduction model examination and tests. When the Government will conduct some but not all of the preproduction examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and test shall be conducted by the contractor (see 4.1).
(d) Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - GS

Project: 6210-A538

☆U.S. GOVERNMENT PRINTING OFFICE: 1981 – 703-023/7374

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-52019B(ME) Adapter Assembly, Glide Angle Light to Stake or Cone

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.