MIL-C-50409(MU)
Amendment 2
14 December 1972
SUPERSEDING
MIL-C-50409(MU)
Amendment 1
9 June 1971

MILITARY SPECIFICATION

COMPONENTS, METAL, FOR FIBER
CONTAINER M105

This Amendment forms a part of Military Specification MIL-C-50409MU dated 11 April 1969.

Make the following changes to Specification MIL-C-50409MU, dated 11 April 1969.

Title: Delete "M105"

Section 1

*Paragraph 1.1:

After "Packing stop support" add "or washer".

*Section 2, Specification, Military: Delete "MIL-I-45607-Inspection...of" and substitute "MIL-C-45662-Calibration System Requirements".

Section 2, Drawings: Add "9258063-WASHER" and "9276019-WASHER"

*Section 2, Publication, Army: Delete "ET-9243286-Equipment Tabulation"

*Section 3, Paragraph 3.2: After "9243287" Add "and 9258063 and 9276019"

*Section 4

*Paragraph 4.2.1:

Delete the second sentence in its entirety and substitute the following:

"The first article sample shall consist of:

a. Thirty five each packing stop supports and packing stops and washer dwg. 9276019 and three treated 8 inch test

FSC: 8 [illegible]

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

bars from each heat treater of the packing stop prepared in accordance with FED-STD-151 method 211.1 from the same material as will be used in production.

or;

b. Thirty five washers, dwg. 9258063

as applicable in accordance with the terms of the contract, which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract".

*Section 4, paragraph 4.3.2.1: Add "or Washer" and after 9243286: Add "or 9276019" Major Category: Delete "none defined" and substitute, "AQL 0.40 percent". Add the following Major defect, "101. Straightness...Gage 01010".

Section 4, paragraph 4.3.2.2, Major category: Delete "None defined" and substitute "AQL 0.40 percent". Add the following Major defect, "101. Straightness...Gage 02010". Add the following minor defect: "207. Corner radius max...Gage 02011".

Section 4: Add the following paragraph:

"4.3.2.3 Washer (see dwg. 9258063)

Categories	Defects	Method Of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Straightness	Gage	03001
Minor:	AQL 2.5 percent		
201.	Outside diameter	Gage	03002
202.	Inside diameter	Gage	03003
203.	Thickness	Gage	03004
204.	Finish	Visual	03005
205.	Evidence of poor workmanship	Visual	03006"

*Section 4, paragraph 4.3.3.1: Add "or Washer" and after 9243286: Add "or 9276019"

Section 4, paragraph 4.3.3.3: Add after Supports "or Washers" and after 9243286: Add "or 9276019".

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:24Z
Check the source to verify that this is the current version before use.

Section 4: Add

"4.3.3.7 Dimensional control of stamped parts.-With the approval of the Contracting Officer, paragraphs 4.3.3.7.1 and 4.3.3.7.2 may be used as an alternate plan of examination for minor defects 201 and 202 of paragraph 4.3.2.1 and minor defects 201, 202 and 203 and 207 of paragraph 4.3.2.2 and Minor defects 201 and 202 of paragraph 4.3.2.3.

4.3.3.7.1 The first hundred (100) units of product, from each production tool and each reworked production tool, shall be screened for the applicable defects to qualify the tool. If any defects are found during qualification, the tool producing the defective parts shall be removed from production but may be eligible for later qualification after rework by the contractor. After qualification a sample of ten (10) parts shall be taken from the last portion of each three thousand (3,000) units of product as a tool control check. If no defects are found, the three thousand units shall be deemed acceptable with regard to the defects specified in paragraph 4.3.3.7. If any defects are found, the tool producing them shall be removed from production. Further, that portion of production since the last qualification inspection shall be rejected.

4.3.3.7.2 The term "tool" shall be defined as any punch or cavity producing a dimension or control associated with the applicable characteristic."

*Section 4: Add

"4.3.4 The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and 4.3.3 see 6.3.

4.3.4.1 Inspection Equipment Capability and Accuracy.-All inspection equipment and facilities shall be of adequate quality and quantity to perform properly and accurately all the required inspections, measurements and tests. The inspection equipment shall be maintained in satisfactory condition for the continued proper performance of these functions and shall be calibrated in accordance with the provisions of MIL-C-45662.

4.3.4.2 Government Rights to Documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements may be used by DOD activities for design,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed."

Section 6

*Paragraph 6.1:

Delete "b. Data Cards-...in MIL-STD-1169".

*Section 6: "Delete 6.3" Add

"6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types-Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs, if available, are designated by drawing numbers (on the Equipment Lists referenced on the Equipment Tabulation) or (on the Equipment Lists referenced on the Equipment Tabulation) or (under the "Method of Inspection" headings in Section 4). Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which established the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is catalored and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalor listings or other means

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:24Z
Check the source to verify that this is the currentversion before use.

which provide sufficient information to permit identification and evaluation by the Government any may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number, paragraph number and defect number if such number has been assigned shall be referrenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of designs for approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt."

*Asterisk indicated changes in addition to or differing from those of Amendment 1.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 8140-A-068

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.