MIL-F-52653A(ME)
26 August 1975
SUPERSEDING
MIL-F-52653(ME)
27 June 1969

MILITARY SPECIFICATION

FIRE FIGHTING EQUIPMENT SET:

TRUCK MOUNTED; BRUSH, CLASS 530-SERIES;

PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements for preservation, packaging, packing, and marking of a Fire Fighting Equipment Set: Truck Mounted; Brush, Class 530-Series; (SC 4210-97-CL-E04).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

U-A-500	- Ammonia, Aromatic (Inhalants).
QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-C-650	- Crates, Wood, Open and Covered.
PPP-P-40	- Packaging and Packing of Hand tools.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-P-775	- Packaging of Hose, Hose Assemblies; Rubber, Plastic, Fabric, or Metal (Including Tubing); and Fittings, Nozzles, and Strainers.
MIL-T-11407	- Truck, Firefighting: Pumper, Tactical-Type; Midship-Mounted-Pump, 750 Gallon-Per-Minute (Class 530-C).
MIL-H-20206	- Heating Torches, Fuel Oil Burning, Portable.

STANDARDS

Federal

FED. STD. No. 356	- Commercial Packaging of Supplies and Equipment.

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Material shall be as specified herein and in the applicable specifications and standards. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.2 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove, prior to starting production packaging and packing, that the applied preservation, packaging, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3 Preservation and packaging. Preservation and packaging shall be Level A, B, or C, as specified (see 6.2).

3.3.1 Level A - maximum military protection.

3.3.1.1 Preservatives. Preservatives specified herein shall conform to the applicable specification listed in, and shall be applied in accordance with, MIL-P-116.

3.3.1.2 Methods. Methods of preservation, indicated by symbols herein, shall conform to the corresponding symbols in MIL-P-116.

3.3.1.3 Unprotected surfaces. Unpainted exterior metal surfaces of components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative.

3.3.1.4 Axes, bush hooks, crowbar, cutter, mattocks, rakes, hand shovels, handles, and spanner wrenches. Each item shall be preserved and packaged in accordance with PPP-P-40, Level A.

3.3.1.5 Hoses, nozzles, playpipes, reducers, strainer, nozzle tips, couplings, and siamese connection valves. Each item shall be preserved and packaged in accordance with MIL-P-775, Level A.

3.3.1.6 Fire extinguisher. Each extinguisher shall be packaged in a box conforming to PPP-B-636, W5c. The contents shall be cushioned and secured to prevent damage by free movement within the box. The boxes shall be sealed with tape as specified in Method V of the Appendix to the box specification.

3.3.1.7 Heating torch. The heating torch shall be preserved and packaged in accordance with MIL-H-20206, Level A.

3.3.1.8 Pails. Pails shall be nested together and packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be sealed with tape as specified in 3.3.1.6.

3.3.1.9 Ammonia inhalant solution. The ammonia inhalant solution shall be unit packaged in accordance with U-A-500, Level A. One unit package shall be placed in each first aid kit.

3.3.1.10 Scissors. Each pair of scissors shall be preserved in accordance with Method IA-8. One pair of scissors shall be placed in each first aid kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3.1.11 First aid kit case. Each first aid kit case, with its components, scissors and ammonia inhalant solution placed therein, shall be packaged in a close-fitting box conforming to PPP-B-636, W5c. The boxes shall be sealed as specified in 3.3.1.6.

3.3.1.12 Rope. The rope shall be coiled to the minimum diameter coil, and the coil packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be waterproof sealed with tape as specified in 3.3.1.6.

3.3.1.13 Lantern. Each lantern contained in a vendor's carton or in a box conforming to PPP-B-566, Variety Plain, type and style optional, shall be preserved in accordance with Method IC-2.

3.3.1.14 Gaskets. Gaskets of like description shall be preserved together in accordance with Method IC-2. The container shall be the supplier's commercial carton or a close-fitting box conforming to PPP-B-566, Variety Plain, type and style optional.

3.3.1.15 Snake bite kit. Each kit shall be preserved in accordance with Method IC-1. Four preserved kits shall be placed in a box conforming to PPP-B-566, Variety Plain, type and style optional.

3.3.1.16 Truck. The truck, when furnished, shall be preserved in accordance with MIL-T-11407, Level A.

3.3.1.17 Consolidated packaging. The preserved and packaged components of the set shall be consolidated packaged together in close-fitting boxes conforming to PPP-B-601, Class Domestic, Grade B. When a truck chassis is furnished, the size and configuration of the boxes shall be determined by the available space for placing and securing of the boxes on the fire truck.

3.3.2 Level B - minimum military protection. Components of the set shall be preserved and packaged as specified for Level A, except that boxes used for consolidated packaging shall, as an alternate, conform to PPP-B-636, V3c or equivalent. Fiberboard boxes shall be closed in accordance with Method V of the appendix to the box specification. The truck, when furnished, shall be preserved and packaged in accordance with MIL-T-11407, Level B.

3.3.3 Commercial. The components of the set shall be preserved and packaged to afford protection against corrosion, deterioration and damage from the supplier to the initial destination in accordance with FED. STD. No. 356. The truck, when furnished, shall be preserved and packaged in accordance with MIL-T-11407, Level C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.4 Packing. Packing shall be Level A, B, or C, as specified (see 6.2).

3.4.1 Level A - maximum military protection. When a truck is furnished, the components of the set, preserved and packaged as specified in 3.3, shall be positioned and secured to the truck in any available space that will not increase cubage, cause damage to the truck or components, or in any way interfere with lifting, steering or towing of the truck. Securing of the consolidated packages to the truck shall be with strapping or by bolting, when practical. The truck, with the consolidated containers attached, shall be shipped unboxed (mobile). When a truck is not furnished, the set components, preserved and packaged as specified in 3.3, shall be packed in a crate conforming to PPP-C-650, Type V, Style A, Class 1. Blocking, bracing and anchoring of contents and closure and strapping of the crate shall be in accordance with the appendix to the crate specification, except that strapping shall conform to QQ-S-781, Class 1, Type I, II, or IV as applicable, size as applicable, and unless otherwise specified herein, shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

3.4.2 Level B - minimum military protection. Packing shall be as specified for Level A, except that strapping shall be either Finish A or B and crates shall be Style B, Class 1, Open.

3.4.3 Commercial. The components of the set, preserved and packaged as specified in 3.3, shall be packed in containers that will assure carrier acceptance and safe delivery from the supplier to the initial destination at the lowest ratings of the carrier in accordance with FED. STD. No. 356. When a truck is furnished, the containers shall be secured in any available space on the truck in a manner not to increase cubage or interfere when the truck is lifted with slings, or interfere with steering or towing of the truck. The truck shall be shipped unboxed (mobile).

3.5 Marking.

3.5.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

3.5.2 Commercial. Marking for commercial packaging and packing shall be in accordance with FED. STD. No. 356.

3.6 Workmanship. Workmanship shall be such as to provide maximum protection to the set components, by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage to the components during handling, shipment and storage, and shall be in accordance with the highest grade possible for this type of work.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects listed in 4.5.1. Presence of one or more defects shall be cause for rejection of the preproduction pack.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking, prior to placing the packages into consolidated containers.
(b) The second stage shall include inspection of closure and marking of consolidated containers, and the arrangement and blocking and bracing of consolidated containers in the shipping container.
(c) The third stage shall include inspection of the closed, strapped, and marked shipping containers prepared for shipment, and the securing of the consolidated containers to the truck when a truck is furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

4.4.2 Unit of product. For the purpose of inspection, all packages or packs prepared for any applicable inspection stage that will comprise a complete pack shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination.

Table I. Classification of Defects

No.	Defect	Level		
		A	B	C
101.	Materials, methods and containers not as specified. Each incorrect material, method and container shall constitute one defect (3.1, 3.3, 3.4).	X	X	X
102.	Unpainted exterior surfaces of components not coated with preservative as specified (3.3.1.3, 3.3.2).	X	X	-
103.	Tools not preserved and packaged in accordance with the referenced document as specified (3.3.1.4, 3.3.2).	X	X	-
104.	Hoses and fittings not preserved and packaged in accordance with the referenced document as specified (3.3.1.5, 3.3.2).	X	X	-
105.	Fire extinguishers not packaged as specified (3.3.1.6, 3.3.2).	X	X	-
106.	Heating torch not preserved and packaged in accordance with the referenced document as specified (3.3.1.7, 3.3.2).	X	X	-
107.	Pails not nested together or not packaged as specified (3.3.1.8, 3.3.2).	X	X	-
108.	Ammonia inhalant solution not packaged in accordance with referenced document (3.3.1.9, 3.3.2).	X	X	-
109.	Scissors not preserved as specified (3.3.1.10, 3.3.2).	X	X	-
110.	Components of the first aid kit, scissors, and ammonia inhalant solution not placed in the first aid kit case or the case not packaged as specified (3.3.1.11, 3.3.2).	X	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

No.	Defect	Level		
		A	B	C
111.	Rope not packaged as specified (3.3.1.12, 3.3.2).	X	X	-
112.	Lantern not preserved and packaged as specified (3.3.1.13, 3.3.2).	X	X	-
113.	Gaskets not preserved as specified (3.3.1.14, 3.3.2).	X	X	-
114.	Snake bite kit not preserved and packaged as specified (3.3.1.15, 3.3.2).	X	X	-
115.	Truck not preserved in accordance with referenced document (3.3.1.16, 3.3.2, 3.3.3).	X	X	X
116.	Fiberboard boxes not closed as specified (3.3.1.6, 3.3.1.8, 3.3.1.11, 3.3.1.12, 3.3.2).	X	X	-
117.	Consolidated packaging not as specified (3.3.1.17, 3.3.2).	X	X	-
118.	Boxes not secured to truck as specified when a truck is furnished (3.4.1, 3.4.2, 3.4.3).	X	X	X
119.	Strapping used for securing packages to the truck or base of the crate not finished as specified (3.4.1).	X	-	-
120.	Marking illegible, incomplete or incorrect (3.5).	X	X	X

5. PREPARATION FOR DELIVERY
(This section not applicable to this specification.)

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packaging, packing, and marking of a Fire Fighting Equipment Set: Truck Mounted; Brush, Class 530-Series (NSN 4210-00-393-0349).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4). Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it has been determined that the set components will be held in covered storage for an indefinite period from date of initial packaging.
(d) When strapping shall be Finish A (see 3.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 4210-A072

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. *DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product* are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-F-52653A(ME) Fire Fighting Equipment Set: Truck Mounted; Brush, Class 530-Series; Packaging Of

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Center
ATTN: AMXFB-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.