MIL-P-48194 (MU)
2 October 1972
SUPERSEDING
See 6.3

MILITARY SPECIFICATION

PROPELLANT CHARGE NUCLEAR COMPONENT

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of propellant charge used on 8 inch 422 Projectile.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

JAN-P-323-Propellant, Cannon, M2 and M5
MIL-P-116-Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	- Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8786584	- Spacer
8787135	- Propellant Charge Nuclear Component
8787136	- Propellant Case
8795941	- Carton, Packing, Ammunition for Propellant Charge, Nuclear Component

FSC 1145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The charge shall comply with all requirements specified on the drawing (dwg) 8787135, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Propellant. The propellant shall be limited to propellant from lot PA-E-6124 unless prior approval in writing is obtained from the contracting officer.

3.4 Air pressure. The propellant case assembly less cover shall withstand an internal air pressure of three (3) pounds per square inch gauge for fifteen (15) seconds without leaking.

3.5 Workmanship.

3.5.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.5.3 Burrs. Parts shall be free from burrs.

3.5.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.5.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contractor requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8787135) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or test	Dest	Non Dest	Parts	Sub Assy	Assy
1. Classification of Characteristics (see 4.3.2.1)		x	x	x	x
2. Pressure test (see 4.3.2.1)		x			x

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.


4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:17Z
Check the source to verify that this is the currentversion before use.

inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.



Source: https://assist.dla.mil -- Downloaded: 20260-22T19:17Z
Check the source to verify that this is the current version before use.

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131			

4.3.2.1 Classification of characteristics (see 3.2). Critical major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Propellant case prior to painting and soldering igniter well bottom in place or igniter well case assembly (see dwg 8787136) covering a detail of dwg 8787135.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major: None defined.

Minor:

201. Thickness of well bottom.....Gage
202. Diameter of well flange, (min.).....Gage
203. Thickness of igniter well sidewall.....Gage
204. Length of closed end section .....Gage
205. Total length of igniter well.....Gage
206. Igniter well seam overlap, (max.).....Gage
207. Soldering of igniter well joints adequate .....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Propellant case prior to coating (see dwg 8787136) covering a detail of dwg 8787135.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major: None defined.

Minor:

201.	Inside diameter of case body, (min.)	Gage
202.	Inside diameter of igniter well	Gage
203.	Total length including extended flange, (max.)	Gage
204.	Depth from extended flange end to inside forward end of case	Gage
205.	Depth from forward end to igniter well bottom (min.)	Gage
206.	Length of overlap at closed end outside diameter (min.)	Gage
207.	Thickness of case body sidewall	Gage
208.	No excessive solder present above forward end surface	Visual
209.	Workmanship (see 3.5)	Visual/Manual

4.3.2.1.3 Spacer (see dwg. 8786584) covering a detail of dwg 8787135.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major: None defined.

Minor:

201.	Concentricity of inner diameter with outside diameter	Gage
202.	Inside diameter, min	Gage
203.	Outside diameter, max	Gage
204.	Total length	Gage
205.	Protective finish present	Visual
206.	Stamping correct and legible	Visual
207.	Channel along outside diameter present	Visual
208.	Workmanship (see 3.5)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Propellant Case prior to inserting of propellant and assembling case cover (see dwg 8787135).

Categories	Characteristics	Method of Inspection
Critical:		
	1. Weight of propellant correct	Balance
Major: None defined.		
Minor:		
	201. Inner disc adequately secured to case	Visual/Manual
	202. Case liner adequately secured to case	Visual/Manual
	203. Spacer adequately secured to case	Visual/Manual
	204. Front disc adequately secured to propellant case cover	Visual/Manual

4.3.2.1.5 Propellant Case (see dwg 8787135).

Categories	Characteristics	Method of Inspection
Critical:		
	1. Propellant present	Balance
Major:		
	101. No dent or damage to the extent that the shape has been visibly altered	Visual
Minor:		
	201. Outside diameter of double seam overlap, (max).	Gage
	202. Total length, (max.)	Gage
	203. Coating adequate including bare spot	Visual
	204. Color of coating proper	Visual
	205. Marking correct, complete and identifiable	Visual
	206. Workmanship (see 3.5)	Visual/Manual

4.3.2.1.6 Carton, packing, ammunition for propellant charge, nuclear component (see dwg 8795941) and section 5.

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
101.	Contents tight in package	Manual
102.	Carton properly sealed	Visual
103.	Carton corners blunted	Visual/Manual
104.	Air exhausted from bag	Manual
105.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual
106.	Proper heat seal	Visual/Manual
107.	Materials (3.1)	Visual
Minor:		
201.	Workmanship (see 3.5)	Visual/Manual

4.3.3 Testing. All tests shall be performed.

Test	Test Classification
a. Air pressure	Major

This test is not considered destructive and samples so tested shall be returned to the lot.

4.3.3.1 Pressure test (see 3.4). Each propellant case shall be tested in accordance with 4.4.1. If any item fails to comply with 3.4, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Air pressure (see 3.4). The propellant case shall be held in a fixture to close the open end and introduce an internal pressure of three (3) p.s.i. gauge. An indicating device shall be in the line to indicate any pressure drop in the case after the pressure source is shut off.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The propellant case shall be packaged in accordance with dwg 8795941 using the specified moisture barrier.

5.1.2 Level C. The propellant case shall be packaged in accordance with dwg 8795941 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The propellant case shall be packed in accordance with dwg 8795941.

5.3 Marking. Marking shall be as specified in accordance with dwg 8795941.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1050, Rev 1 dated 19 February 1962.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1145-A 008

☆ U. S. GOVERNMENT PRINTING OFFICE: 1972-714-540/3156

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.