MIL-S-52001B(ME)
22 October 1971
SUPERSEDING
MIL-S-52001A(MO)
28 January 1966

MILITARY SPECIFICATION

STAKES: ANCHOR AND GUY, ELECTRIC LIGHTING SET,

AIRPORT AND HELIPORT

1. SCOPE

1.1 This specification covers angle and tee stakes for use in airport and heliport electrical lighting sets.

1.2 Classification. Stakes shall be of the following types, as specified:

Type I - Angle shape anchor stake, aluminum.
Type II - Tee shape guy stake, galvanized steel.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.

Military

MIL-T-704 - Treatment and Painting of Materiel.

FSC 6210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U. S. Military Property.

DRAWINGS

ME

DL13205E3542	- Stake, Guy.
DL13205E3543	- Stake, Anchor.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids, or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Description. The type I anchor stake and the type II guy stake shall be as shown on DL13205E3543 and DL13205E3542 respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) Prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified herein and on the drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.3 Identification marking. The stakes shall be identified in accordance with MIL-STD-130.

3.4 Treatment and painting (type I only). The type I stakes shall be cleaned, treated and painted in accordance with MIL-T-704, type A. Color shall be 34087.

3.5 Workmanship. The stakes shall be free from defects or imperfections that might affect their serviceability or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5)

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, inspection level S-4.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined in accordance with 4.4.1. AQL shall be 1.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

4.4 Inspection procedure.

4.4.1 Examination. The stakes shall be examined for the following defects:

101. Nonconformance to any dimension or requirement shown on the drawings.
102. Stake bent or deformed.
103. Treatment and painting not as specified such as incomplete preparation before painting, scale, lumps, runs, craze, thin or bare spots, color of dry film not as specified or streaked and uneven (type I only).
104. Marking not as specified.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, inspection level S-2.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

105. Materials or containers not as specified for levels A and B. Each incorrect material or container shall constitute one defect.
106. Boxes not reinforced as specified for levels A and B.
107. Strapping not zinc coated for level A.
108. Marking illegible, incomplete, incorrect, or missing.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C, as specified.

5.1.1 Level A. The stakes of like description shall be packed in quantities not to exceed the weight limitation of close-fitting boxes conforming to PPP-B-621, class 2, style 2, for type 3 load. The ends of the box shall be reinforced by the addition of boards covering the entire inner face of each end. The reinforcing boards shall be the same thickness as the end boards and shall be placed with grain direction at right angles to that of the end boards and shall be nailed to them with the nails clinched. The sides, top, and bottom of the box shall be nailed to the reinforcing boards in addition to the nailing required by the box specification. The boxes shall be closed and strapped in accordance with the appendix to the box specification. Strapping shall be zinc coated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. The stakes shall be packed as specified in 5.1.1 for level A except boxes shall be class 1 and strapping will not be required to be zinc coated.

5.1.3 Level C. The stakes shall be packed to assure carrier acceptance and safe delivery to destination at lowest rating in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.2 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The stakes are intended to be driven into the ground and used for securing various components of airport and heliport electric lighting equipment.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Level of packing required (see 5.1).

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 6210-A416

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-S-52001B(ME) Stakes: Anchor and Guy, Electric Lighting Set, Airport and Heliport

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:04Z
Check the source to verify that this is the current version before use.