INCH-POUND

MIL-S-63433D (AR)
AMENDMENT 2
10 April 1990
SUPERSEDING
AMENDMENT 1
7 August 1989

MILITARY SPECIFICATION

SIMULATOR, ARTILLERY FLASH, M21
PERFORMANCE SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-S-63433D (AR), dated 20 January 1989, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.11: Add to list of Military Standards:

"MIL-STD-1234 Pyrotechnics, Sampling, Inspection and Testing".

PAGE 4

* 3.2.4.5, Electrostatic discharge: Change to "Electrostatic discharge - composition".

PAGE 5

* 3.2.5.1: Revise as follows:

DOD Hazard Classification. - Delete "1.3" and substitute "1.4".

DOT Explosive Label - Delete "Class B" and substitute "Class C".

DOT Marking - Delete "SPECIAL FIREWORKS" and substitute "SIGNAL FLARES".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:51Z
Check the source to verify that this is the current version before use.

PAGE 6

* 3.3.6, Line 3: Delete "applicable gunfire devices" and substitute "socket contacts of the connector block (see 6.5.3)."

PAGE 9

* 3.5.2: Five foot drop: Delete "4.5.8.12" and substitute "4.5.8.4".

PAGE 10

3.5.12: Delete in its entirety and substitute the following:

"3.5.12 Heat soak at 160°F. (First Article Test Only) The packaged simulators (in barrier bag) shall meet the functioning requirements of 3.4.1 after being subjected to a temperature of 71.1 ± 3°C, (160°F ± 5°F) for a minimum period of 5 weeks. Prior to functioning, the simulator assembly resistance shall not exceed 2.0 ohms maximum."

3.5.13: Delete in its entirety and substitute the following:

"3.5.13 Temperature-humidity. (First Article Test Only). The packaged simulators (in barrier bag) shall meet the functioning requirements of 3.4.1 after exposure to temperature-humidity cycling as specified in 4.5.8.10. Prior to functioning, the simulator assembly resistance shall not exceed 2.0 ohms maximum."

PAGE 13

* Table I: Add under "Paragraph ref./Insp. method" column: "4.4.3.1" to "Charge composition" and "4.4.3.1" to "Paper or paper products". Delete "4.5.4.4" and "4.5.4.5"; and substitute "4.5.14" and "4.5.15".

PAGE 14

* Table I, Temperature - humidity: Delete "3.5.12" and "4.5.8.9"and substitute"3.5.13" and "4.5.8.10".

* Table I, Temperature cycling: Delete "Temperature cycling, 3.5.13, 4.5.8.10/4.5.4" and substitute "Heat soak at 160°F, 3.5.12, 4.5.8.9/4.5.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

* 4.4.2.1: Add under "Paragraph ref/Insp method" column: "4.4.3.1" to "Charge Composition" and "4.4.3.1" to "Paper products".

PAGE 20

* 4.5.2, Line 2: Delete "approved gunfire device" and substitute "firing tubes of a Hoffmann Device".

PAGE 21

4.5.4, Functioning: Line one, change "6" to "12".

* 4.5.4, Line 4: Delete "an approved gunfire device" and substitute "a Hoffmann Device".

* 4.5.4.1, Line 3: Delete "suspended" and substitute "fired using a Hoffmann Device, mounted horizontally,"

PAGE 22

4.5.8.2, Cold temperature: Line three, change "6" to read "12".

4.5.8.3, Hot temperature: Line three, change "6" to read "12".

PAGE 23

4.5.8.9: Delete in its entirety and substitute the following:

"4.5.8.9 Heat soak at 160°F. (First Article Test Only) The packaged simulator assemblies shall be conditioned for a period of five(5) weeks minimum at the specified temperature. After removal from the conditioning chamber and allowed to return to ambient temperature, resistance measurement shall be made using a Fluke 8024B, 8050A Multimeter, or equivalent meter, approved for use with electro-explosive devices.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:51Z
Check the source to verify that this is the current version before use.

SAFETY NOTE: All resistance measurements shall be conducted from behind a barricade and shorting caps shall be in place at all times except during resistance measurement and when functioning items.

The simulator resistance shall not exceed the applicable requirement after conditioning. Only those simulators passing the resistance requirement shall be placed in the firing device and functioned (ref. 4.5.4). Any simulator failing to meet the applicable requirements shall be classed defective (Destructive test)".

4.5.8.10 : Delete in its entirety and substitute the following:

"4.5.8.10 Temperature humidity. (First Article Test Only) The packaged simulators shall be subjected to a 28-day temperature-humidity test in accordance with MIL-STD-331, Test 105.1, para. 5.2, Single Chamber cycling Method. After removal from the conditioning chamber and allowed to return to ambient temperature, resistance measurements shall be made and the simulators functioned as specified in 4.5.8.9 above. Any simulators failing to meet the applicable requirements shall be classed defective. (Destructive test)."

PAGE 27

* 4.5.15: Change to "4.5.16"

Add new paragraph: "4.5.15 Electrostatic discharge. The simulator, bare, packaged and in the Hoffmann Device shall be tested in accordance with Test 126 of MIL-STD-331. Observations shall be made for compliance with the applicable requirements. (Non-destructive test)"

PAGE 28

* 6.4: Under "Paragraph no". column: Delete "4.5.15" and substitute "4.5.16". Delete "6.2.2" and substitute "6.2.1". Add "6.3" in "DI-R-1714" line.

PAGE 29

* 6.5.3: Delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

"6.5.3 Interface devices: Hoffmann Device (Simulator, Tank Gunfire Device 17-61) for use in chamber withdrawal, functioning, electromagnetic radiation and electrostatic discharge tests. Request from Contracting Officer, Armament Munitions and Chemical Command, Rock Island, IL 61299.

Connector Block with Socket Contacts - 8602D03016 (part of EC Corp Device 17-157) for assurance that simulator electric plug fits all firing devices power outlets. Request from ARDEC, ATTN: SMCAR-AEE-P, Picatinny Arsenal, NJ 07806-5000. (This part is manufactured by the EC Corporation, 10511 Hardin Valley Road, Knoxville, TN 37932)".

NOTE: the margins of this amendment are marked with asterisks or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project: 1370-A311)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.