MILITARY SPECIFICATION

CLOTHS, CLEANING, FOR AIRCRAFT FUEL TANKS

1. SCOPE AND CLASSIFICATION

1.1 Scope. This Specification covers the requirements for two types of wiping cloths for critical cleaning requirements preparatory to painting and sealing in aircraft fuel tanks.

1.2 Classification. The cloths shall be of the following types as specified.

Type I - Cheesecloth, bleached

Type II - Gauze pads

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this purchase description to the extent specified herein.

Specifications

Federal

CCC-C-440 Cloth, Cheesecloth, Cotton, Bleached and Unbleached

DDD-S-1298 Sponge, Surgical

Military

MIL-C-38736 Cleaning Compound, Solvent, for use in Integral Fuel Tanks

Standards

MIL-STD-129 Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:27Z
Check the source to verify that this is the current version before use.

3.1 Material. The cleaning cloths shall be based on the following materials for the respective types.

3.1.1 Type I - This type shall be cotton cheesecloth, bleached, with a warp and fill count of 28 by 24 yarns per inch, which meets Federal Specification CCC-C-440, Type II, Class 2.

3.1.2 Type II - This type shall be unsterilized gauze pads, 4 by 4 inch size by 8 ply which meets Federal Specification DD-S-1298, Type I, Class A.

3.2 Physical Requirements. The maximum amount of extractables in the fabric shall be zero percent by weight of the fabric when tested as specified in 4.5.

3.3 Reclaimed materials. Recycled and recovered raw materials should be used to the maximum extent possible in lieu of virgin raw materials provided they do not jeopardize the intended use and fully comply with all specification and contract requirements. This requirement applies to the raw materials from which the end item cloth is manufactured and shall not be interpreted to allow the acquisition of used or rebuilt products.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the applicable paragraphs of this specification.

4.3 Quality Conformance Inspection. The quality conformance inspection of the cloth shall be in accordance with the basic material specifications for the respective types, CCC-C-440, Type II, Class 2 for Type I and DDD-S-1298, Type I, Class A for Type II. In addition, the cloths shall be tested for solvent extraction described herein.

4.4 Quality Conformance Inspection Sampling. For the solvent extraction test, each 100 yards of Type I and each 4000 pads of Type II shall be sampled to provide three specimens weighing 9 to 10 grams.

4.5 Test Method. Three specimens weighing 9 to 10 grams from each sampling shall be tested as follows. Overedge each specimen to prevent raveling during test. Weigh the specimen for original sample weight. Place specimen in dessicator for 72 hours. Remove specimen from dessicator and weigh within one minute in grams to four decimal places. Call this weight Wo. Place specimen in 1000 ml of cleaning solvent, MIL-C-38736, in a 2000 ml covered beaker with specimen supported one-half inch from the bottom. Agitate liquid with a magnetic stirrer on slow for 30 minutes. Remove specimen, wring dry, and air dry for 10 minutes. Place specimen in dessicator for 24 hours. Remove specimen from dessicator and weigh within one minute in grams to four

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:27Z
Check the source to verify that this is the current version before use.

decimal places. Call this weight W_1. Calculate the percent extractable using this formula:

$$\% \text{ Extractable} = \frac{\text{Wt. before extraction, Wo} - \text{Wt. after extraction, } W_1}{\text{Wt. before extraction, } W_1}$$

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be according to the options of the basic material specifications, CCC-C-440 for Type I and DDD-S-1298 for Type II, as specified.

5.2 Packing. Packing shall be according to the options of the basic material specifications, CCC-C-440 for Type I and DDD-S-1298 for Type II, as specified.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129. The marking shall include this Specification number and title.

6. NOTES

6.1 Intended Use. The cloths are intended for critical cleaning requirements in aircraft fuel tanks prior to application of coatings and sealants or repair of coatings and sealants.

6.2 Ordering Data. The procurement documents should specify the following:

a. Title, number and date of this Specification.

b. Type required (see 1.2).

c. Quantity

d. Packaging and packing level, suppliers commercial practice unless otherwise specified.

Custodian:
Air Force - 99

Preparing Activity
Air Force - 99

Project 7920-F247

☆U.S. GOVERNMENT PRINTING OFFICE: 1978—603-002/5161

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:27Z
Check the source to verify that this is the current version before use.