
FED. SUP CLASS
5935



Design standard for use with MIL-C-28748/9

Ⓑ Entire standard revised

APPROVED 20 Dec 1965 REVISED Ⓐ 20 May 1970 Ⓑ 8 July 1976

User activities: Army ME, AV, WC
Navy MC
Air Force

Reviewer activities: Army MI, MU, AT
Navy AS, SH, OS
Air Force 11, 80
DSA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A Navy - EC Other Cust AF - 85 Army - EL	International interest:	TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR, POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 158 (SIZE 16 CRIMP REMOVABLE) PIN CONTACTS	MILITARY STANDARD MS 18165
Procurement Specification MIL-C-28748		SUPERSEDES:	SHEET 1 OF 3

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-2004-15

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.

TYPE
SEE TABLE I




TABLE I		
TYPE	A	B
1	90°	135°
2	85°	137° 30'

TABLE II		
MS PART NUMBER	POLARIZATION *	JACKSCREW
MS 18165-1N	N (TYPE 1)	SUPPLIED WITH CONNECTOR
MS 18165-1V	V (TYPE 1)	
MS 18165-1W	W (TYPE 1)	
MS 18165-1X	X (TYPE 2)	
MS 18165-1Y	Y (TYPE 2)	
MS 18165-1Z	Z (TYPE 2)	
MS 18165-2N	N (TYPE 1)	NOT SUPPLIED WITH CONNECTOR POLARIZING BOSS THREADED INTERNALLY .250-28 UNF-2B
MS 18165-2V	V (TYPE 1)	
MS 18165-2W	W (TYPE 1)	
MS 18165-2X	X (TYPE 2)	
MS 18165-2Y	Y (TYPE 2)	
MS 18165-2Z	Z (TYPE 2)	

TABLE III		
MS PART NUMBER	POLARIZATION *	GUIDE PIN
MS 18165-3N	N (TYPE 1)	SUPPLIED WITH CONNECTOR
MS 18165-3V	V (TYPE 1)	
MS 18165-3W	W (TYPE 1)	
MS 18165-3X	X (TYPE 2)	
MS 18165-3Y	Y (TYPE 2)	
MS 18165-3Z	Z (TYPE 2)	
MS 18165-4N	N (TYPE 1)	NOT SUPPLIED WITH CONNECTOR POLARIZING BOSS WITH .254 ± .002 I.D. TO ACCEPT GUIDE PIN
MS 18165-4V	V (TYPE 1)	
MS 18165-4W	W (TYPE 1)	
MS 18165-4X	X (TYPE 2)	
MS 18165-4Y	Y (TYPE 2)	
MS 18165-4Z	Z (TYPE 2)	

* LARGE OPENING IN POLARIZATION BOSS MUST BE ADJACENT TO POLARIZATION LETTER ON CONNECTOR BODY.

User activities: Army ME, AV, WC
Navy MC
Air Force

Reviewer activities: Army MI, MU, AT
Navy AS, SH, OS
Air Force 11, 80
DSA - ES

APPROVED 20 Dec 1965 REVISED (B) For changes see sheets 1, 2 and 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use will be made from this document.

P.A Navy - EC
Other Cust
AF - 85
Army - EL

International interest:

Procurement Specification
MIL-C-28748

SUPERSEDES:

TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR, POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 158 (SIZE 16 CRIMP REMOVABLE) PIN CONTACTS

MILITARY STANDARD

MS 18165

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-2004-15

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.

INCHES	MM	INCHES	MM
.001	.03	.520	13.21
.002	.05	.525	13.34
.005	.13	.550	13.97
.006	.15	.579	14.71
.010	.25	.600	15.24
.060	1.52	.650	16.51
.075	1.91	.675	17.15
.130	3.30	.750	19.05
.149	3.78	.780	19.81
.150	3.81	.810	20.57
.156	3.96	.825	20.96
.218	5.54	.900	22.86
.225	5.72	.930	23.62
.246	6.25	.975	24.77
.250	6.35	1.180	29.97
.260	6.60	1.250	31.75
.287	7.29	1.438	36.53
.300	7.62	1.760	44.70
.375	9.53	1.860	47.24
.390	9.91	2.156	54.76
.437	11.10	2.500	63.50
.450	11.43	2.875	73.03

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.015 (.38 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. Tolerance between any two adjacent contact centers shall be ±.004 (.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ±.006 (.15 mm).
5. Contact hole details shall be in accordance with MIL-C-28748.
6. For mating connector see MS18166 (socket body).
7. Dimensions symmetrical about centerlines.
8. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
9. Reference documents shall be of the issue in effect on date of invitation for bid.
10. Insert material shall be in accordance with MIL-C-28748.
11. Flatness, squareness and parallelism shall be within dimensional tolerances.
12. Center polarizing hardware may be rotated by removing retaining ring and spacer or removing cap (left hand thread) at rear of insert.
13. Maximum insertion and withdrawal force (connector assembly) shall be 148 pounds.
14. Maximum torque required at jackscrew to properly engage or disengage connector shall be 10 inch pounds.
15. Jackscrew wrench size 5/32 hex.

User activities: Army. ME, AV, WC
Navy MC
Air Force

Reviewer activities: Army MI, MU, AT
Navy AS, SH, OS
Air Force 11, 80
DSA - ES

APPROVED 20 Dec 1965 REVISED (B) For changes see sheets 1, 2 and 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A Navy - EC Other Cust AF - 85 Army - EL	International interest	TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR, POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 158 (SIZE 16 CRIMP REMOVABLE) PIN CONTACTS	MILITARY STANDARD MS 18165
Procurement Specification MIL-C-28748		SUPERSEDES:	SHEET 3 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.