
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

User activity: Air Force - 11

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

FED. SUP CLASS
5930



Ⓓ Denotes changes

APPROVED 19 April 1965 REVISED Ⓐ 20 April 1967 Ⓑ 16 Sep 1967 Ⓒ 14 May 1974 Ⓓ 28 Sep 1987

P A Air Force - 85 Other Cust Army - ER Navy - AS	Inactivated for new design	TITLE SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED	MILITARY STANDARD MS27406
Procurement Specification MIL-S-3950		SUPERSEDES	PAGE 1 OF 3

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5930-1358-07
AMSC N/A

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:23Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.005	0.13	.37	9.4
.008	0.20	.38	9.7
.012	0.30	.432	10.97
.020	0.51	.47	11.9
.03	0.8	.69	17.5
.060	1.52	1.10	27.9
.076	1.93	1.340	34.04
.130	3.30	1.370	34.80
.240	6.10	1.660	42.16
.25	6.4		

NOTES:
1. Dimensions are inches.
(D) 2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.020 (0.51 mm) for two place decimals and ±.005 (0.13 mm) for three place decimals.
(D) 4. For hardware and terminal screw detail specifications, see appendix of MIL-S-3950.
5. All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever.
6. Maximum weight is 0.20 pound.
(D) 7. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
(D) 8. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

(D) For changes see page 2.

APPROVED 19 April 1965
REVISED (D)

User activity: Air Force - 11
Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

P.A Air Force - 85 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED	MILITARY STANDARD MS27406
Procurement Specification MIL-S-3950		SUPERSEDES	PAGE 2 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:23Z
Check the source to verify that this is the current version before use.

* U.S. GOVERNMENT PRINTING OFFICE: 1987-181-037/71436

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

Review activities: Army - AV, Navy - EC, Air Force - 99, DLA - ES

User activity: Air Force - 11

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Procurement Specification: MIL-S-3950

PA: Air Force - 85, Other Cust: Army - ER, Navy - AS

International interest:

SUPERSEDES

TITLE: SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED

MILITARY STANDARD

MS27406

FED. SUP CLASS 5930

PAGE 3 OF 3

Detail requirements:

MS part number	Circuit with toggle lever in			Current capacity (amperes) 28 volts dc			Current capacity (amperes) 115 volts, 60 and 400 hertz ac		
	Keying side	Center	Opposite keying side	Lamp-load circuit	Resistive circuit	Inductive circuit	Lamp-load circuit	Resistive circuit	Inductive circuit
MS27406-1	1-2 4-5 7-8 On 10-11	2-3 4-5 7-8 On 11-12	2-3 5-6 8-9 On 11-12	5	20	12	4	15	15
MS27406-2	1-2 Mom. 4-5 7-8 on 10-11	2-3 4-5 7-8 On 11-12	2-3 5-6 8-9 On 11-12						
MS27406-3	1-2 Mom. 4-5 7-8 on 10-11	2-3 4-5 7-8 On 11-12	2-3 Mom. 5-6 8-9 on 11-12	4	18	10	2	11	8

APPROVED 19 April 1965 REVISED (D) For changes see page 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:23Z
Check the source to verify that this is the current version before use.