



FED. SUP CLASS
6640


MS36352-1


MS36352-2


MS36352-3


MS36352-4

PART NUMBER	NOMINAL INNER CHAMBER DIMENSIONAL DATA, inches WIDTH	DEPTH	HEIGHT	NUMBER OF OUTER DOORS	NUMBER OF SHELVES
MS36352-4	8 1/2	5	7 3/4	1	4
MS36352-1	13	14	13	1	2
MS36352-2	25	19	19	1	2
MS36352-3	37	19	25	2	2

MATERIAL: Interior walls, exterior walls, water reservoir, and shelves, shall be of corrosion-resisting steel in accordance with Federal Standard No. 66 AISI 304.

Shelves of MS36352-4 shall be of aluminum.

B Insulation shall be noncombustible, nonhygroscopic, nonpowdering glass wool.

Heating elements shall be of a high electrical resistant alloy, such as nickel-chromium.

FINISH: Corrosion-resisting steel shall be ground to a No. 4 commercial finish.

All hardware shall be coated to resist corrosion.

DESIGN: Incubators shall be of the gravity convection type, capable of distributing and maintaining uniform heat without the use of a water jacket.

Shelves shall be removable, adjustable, and so constructed as to allow proper air circulation throughout the inner chamber.

Insulation shall be a minimum of three inches thick and shall completely envelop the inner chamber of MS36352-1, MS36352-2, MS36352-3. MS36352-4 shall be insulated.

Cabinet shall have openings for proper ventilation and shall have an opening in the top for accommodation of a graduated glass thermometer.

Instruments and controls include line cord, main switch, pilot light, and thermo-regulator.

Operating temperature range shall be from 30°C to 70°C for MS36352-1, MS36352-2, and MS36352-3 and from 21°C to plus 60°C for MS36352-4.

Wattage, voltage, current and frequency shall be sufficient for reaching any point within the OPERATING TEMPERATURE RANGE and maintaining this temperature within a tolerance of ± 1/2°C for extended periods.

Electrical components shall comply with the standards of Underwriters' Laboratories, Inc.

NOTES: 1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements as specified herein.

USER ACTIVITIES:
ARMY - MD
NAVY - AS, YD
AIR FORCE - 03
DoD - MB

REVIEWER ACTIVITIES:

APPROVED 10 JUN 1963 REVISED (A) 22 AUG 1969 (B) 25 FEB 1988

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P. A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		INCUBATOR, BACTERIOLOGICAL gravity convection	MS 36352
Other Cust MS			
PROCUREMENT SPECIFICATION See Notes 4,5,6 & 7	SUPERSEDES:		SHEET 1 OF 2

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NUMBER 6640-1471-2
REVISION

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

DATE

DRAWN BY
TYPED BY
CHECKED BY

NOTES TO PRINTER REDUCE BORDER TO 7.5 X 10 - 1/2 SHEET PRINT
BORDER LINE ONE INCH FROM LEFT EDGE OF 8 X 10 - 1/2 SHEET PRINT
BOTTOM BORDER LINE 3/8 INCH FROM BOTTOM EDGE OF 8 X 10 - 1/2 SHEET
SIGNATURE FORM NOT TO BE INCLUDED ON 8 X 10 - 1/2 SHEET

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:39Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
6640

B 2. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.

B 3. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this standard to the extent specified herein.

B 4. Procurement document for MS36352-4 is Military Specification, MIL-I-37078.

B 5. Procurement document for MS36352-1 is Federal Specification, GG-I-488/1.

B 6. Procurement document for MS36352-2 is Federal Specification, GG-I-488/2.

B 7. Procurement document for MS36352-3 is Federal Specification, GG-I-488/3.

B 8. FSCM: 94480

USER ACTIVITIES:

REVIEWER ACTIVITIES:

REVISED

APPROVED

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P. A. Other Cust	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
			MS 36352
PROCUREMENT SPECIFICATION: See Notes 4,5,6 & 7	SUPERSEDES:		SHEET 2 OF 2

DD FORM 1 MAY 73 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NUMBER 6640-1471-2
REVISION

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

NOTES TO PRINTER REDUCE BORDER TO 6 - 27/32 X 9 - 3/4 PRINT LEFT BORDER LINE ONE INCH FROM LEFT EDGE OF 8 X 10 - 1/2 SHEET PRINT BOTTOM BORDER LINE 3/8 INCH FROM BOTTOM EDGE OF 8 X 10 - 1/2 SHEET SIGNATURE FORM NOT TO BE INCLUDED ON 8 X 10 - 1/2 SHEET

	DATE
DRAWN BY	
TYPED BY	
CHECKED BY	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:09:07
Check the source to verify that this is the current version before use.