MIL-A-22397
INTERIM AMENDMENT - 1 (SHIPS)
12 June 1964

MILITARY SPECIFICATION

ADHESIVE, PHENOL AND RESORCINOL RESIN BASE

(FOR MARINE SERVICE USE)

(This interim amendment forms a part of Military Specification MIL-A-22397, 8 September 1960. It was developed by the Department of the Navy, Bureau of Ships, for immediate use pending the inclusion of its contents in a coordinated document.)

Page 1, section 2: Delete and substitite:

"2. APPLICABLE DOCUMENTS

"2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-C-96 - Cans, Metal, 28 Gage and Lighter.
PPP-D-729 - Drums: Metal, 55-Gallon (For Shipment of Non-corrosive Material).
PPP-D-705 - Drum: Metal Shipping, Steel (Over 12 and Under 55 Gallon).
PPP-P-704 - Pails: Shipping, Steel (1 Through 12 Gallon).

STANDARDS

FEDERAL

FED-STD-175 - Adhesives: Methods of Testing.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

FSC 8040

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:13Z
Check the source to verify that this is the current version before use.

"2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OFFICIAL CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York 16, N.Y.)"

Page 3, paragraph 3.10: Delete "and 6.4".

Page 3, paragraphs 3.10.1 and 3.10.2, line 4: Delete "a" and substitute "an original unopened and".

Page 3, first sentence: Delete and substitute "The number of copies of printed instructions shall be specified in the contract or order. Printed instructions shall cover at lease the following (see 6.2g):"

Page 3, paragraph 3.11, item (f): Delete and substitute:

"(f) Recommended adhesive spread in pounds per thousand square feet of assembled glue joint (see 3.5)."

Page 4, paragraph 4.1: Delete and substitute:

"4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 4, paragraph 4.3, last sentence: Delete and substitute "A batch shall be defined as that quantity of adhesive which has been manufactured by some unit chemical process and subjected for some physical mixing operation intended to make the final product substantially uniform."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:13Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 4.4.1: Delete and substitute:

"4.4.1 Sampling for examination of filled containers.- A random sample of filled containers shall be selected in accordance with MIL-STD-105 at inspection level I and an Acceptable Quality Level (AQL) of 2.5 percent defective to verify conformance to all requirements of this specification regarding fill, closure, labels, instructions, and other requirements not involving tests."

Page 5, paragraph 4.6.1.2: Delete.

Pages 5 and 6, paragraph 4.6.1.2.1: Delete.

Page 6, paragraph 4.6.4, fourth sentence through remainder of paragraph: Delete and substitute "In case of doubt as to whether the material is brushable, a Brookfield Synchrolectric Viscosimeter or an equivalent instrument shall be used to determine viscosity. If the viscosity exceeds 200 poises the material shall be considered no longer brushable."

Page 7, paragraph 4.6.6.1.2: Delete and substitute:

"4.6.6.1.2 Machining.- The laminations shall be accurately machined to a uniform thickness throughout by removal of approximately equal thicknesses from each face and the thickness variation of any lamination at the time of gluing shall not exceed 0.01 inch as determined through the use of an accurate thickness gage. Surfaces shall not be sanded after surfacing. The final surfaces for gluing shall be prepared not more than 24 hours before gluing is started."

Page 7, paragraph 4.6.6.1.4: Delete and substitute:

"4.6.6.1.4 Assembly.- Two beams shall be assembled at an ambient temperature of $23^{\circ} \pm 2^{\circ}C.$ ($73.4^{\circ} \pm 3.6^{\circ}F.$). Using a negligible open assembly period (close to zero minutes), fabricate one beam at the minimum closed assembly period recommended in the manufacturer's printed instruction, and one at the maximum recommended closed assembly period (see 3.6 for assembly period limitations)."

Page 7, paragraph 4.6.6.1.4.1: Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:13Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 4.6.6.1.6: Insert as first sentence "The two beams, assembeld as in 4.6.6.1.4, shall be cured at a glueline temperature of 65.6° ± 2°C. (150° ± 3.6°F.) for the period of time recommended in the manufacturer's instruction (see 3.7 for cure period limitations)."

Page 7, paragraph 4.6.6.1.6.1: Delete.

Page 8, paragraph 4.6.6.2.1, last line: Delete "0.010" and substitute "0.01".

Page 8, paragraph 4.6.6.2.3, line 1: Delete "blocks" and substitute "block".

Page 9, paragraph 4.6.7, line 2: After "stored" insert "in a sealed container".

Page 9, paragraph 4.8: Renumber as "4.7".

Page 9, paragraph 5.1.1.1: Delete "5.1.1.1 Level A" and substitute "5.1.1 Level A.- "

Page 9, paragraph 5.1.1.1, line 4: Delete "(see 6.2(e))" and substitute "(see 6.2(c))".

Page 9, paragraph 5.1.1.1.1, line 3: Delete "stripping" and substitute "striping".

Page 9, paragraph 5.1.1.1.2: Delete and substitute:

"5.1.1.1.2 Five-gallon pails.- The 5-gallon pail shall conform to type I of PPP-P-704. Color shall be as specified in the contract or order."

Page 9, paragraph 5.1.1.1.3: Delete and substitute:

"5.1.1.1.3 Thirty-gallon drums.- The 30-gallon drums shall conform to type I of PPP-D-705. Interior coating of drums shall not affect or be affected by the packaged product."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:13Z
Check the source to verify that this is the current version before use.

Page 10, paragraph 5.1.1.1.4, line 2: Delete "type III" and substitute "type II".

Page 10, paragraph 5.1.1.2, lines 6 and 7: Delete "stripping" and substitute "striping".

Page 10, paragraph 6.2, item (f), line 2: Delete "15" and substitute "30".

Page 10, paragraph 6.2, item (g): Delete and substitute:

"(g) The number of copies of use instructions required (see 3.11)."

Page 11, figure 1: Delete "A - STRAIGHT BEAM" and caption and substitute "Figure 1 - Cut-up plan-laminated test beams."

Preparing activity:
Navy - Ships
(Project 8040-N016Sh)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-433-694/3771

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:13Z
Check the source to verify that this is the current version before use.