MIL-C-22362D(AS)
16 JULY 1986
SUPERSEDING
MIL-C-22362C(AS)
9 April 1968

MILITARY SPECIFICATION

# CARTRIDGE, IMPULSE, MARK 18 MOD 0

This specification is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers the requirements for the manufacture and acceptance of the Mark 18 Mod 0 Impulse Cartridge (see 6.1).

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-D-21625 | Design and Evaluation of Cartridges for Cartridge Actuated Devices |
| MIL-P-116 | Preservation, Methods of |
| MIL-P-223 | Powder, Black |
| MIL-P-46610 | Primers, Percussion, Styphnate and Chlorate Types, for Small Arms Ammunition |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-453 | Inspection, Radiographic |
| MIL-STD-414 | Sampling Procedures and Tables for Inspection by Variables for Percent Defective |

Beneficial comments (recommendations, additions , deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Air Engineering Center, Systems Engineering and Standardization Department (SESD) Code 93, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 20260-19T12:10Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

DRAWINGS

Bureau of Naval Weapons

| | |
|---|---|
| DL 491833 | Cartridge, Impulse, MARK 18 MOD 0 |
| DL 486208 | Container, Inner, for Cartridges, Impulse |
| DL 486209 | Container, Outer, for Cartridges, Impulse |
| DL 491820 | Test Set, Ballistic, MARK 327 MOD 0, Aircraft Ejection Seat Catapult Cartridge |

Ordnance Corps of the Army

| | |
|---|---|
| C-7645339 | Primer, Caliber .50 |

PUBLICATIONS

Instruction 4030.17 Preservation, Packaging, Packing and Marking; Navy Policy for

Bureau of Naval Weapons

| | |
|---|---|
| OP 5 | Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the Government Inspector for use of the publication.) |
| WR-43 | Preparation of Quality Assurance Provisions |

**2.1.2 Other Government documents, drawings, and publications.** The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Code of Federal Regulations

| | |
|---|---|
| 49 CFR 100-199 | Transportation |

(Copies of specifications, standards, other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

**2.2 Order of Precedence.** In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 General.** The Mark 18 Mod 0 impulse cartridges covered by this specification shall be manufactured in accordance with DL 491833 and all documents listed thereon.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

3.2 **First article.** When specified in the contract or purchase order, a first article shall be subjected to first article inspection (see 4.4 and 6.5).

3.3 **Materials.** All materials used in the manufacture of the cartridges shall conform strictly with the specifications referred to on the respective drawings unless otherwise specified approval in writing covering a departure therefrom has been obtained from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 **Primary components.** For the purpose of this specification, the primers and the propellant are defined as primary components (see 4.5.1).

3.5 **Primer.** The primers shall be furnished from lots manufactured within 2 years or have been recertified within 12 months prior to cartridge lot completion. The primers (50M) shall be loaded with Remington Arms Primer Mixture 5061W, manufactured in accordance with Drawing C-7645339 and accepted in accordance with the applicable requirements of MIL-P-46610, Class 1 (see 4.6.1).

3.5.1 **Radiographic examination.** Primers shall be free of the following defects as verified by radiographic examination in accordance with 4.6.2.1: missing or abnormally thin charge; charge broken, cracked, or porous; cracked or off center anvil or other misplaced or deformed parts; anvil abnormally close to the cup dome; and all other observable defects in the assembly.

3.6 **Propellant and Ignition Charges.**

3.6.1 **Charges.** All propellant and ignition charges shall be as specified on Drawings 201577 and 736684, respectively, of DL 491833. Charges shall be determined by weight rather than by volume measurements.

3.6.2 **Black powder.** The moisture content of the black powder shall be determined as specified in MIL-P-223 and at the time of loading shall be within the limits specified therein for the applicable class of black powder being used (see 4.6.3).

3.6.3 **Smokeless powder, handling and loading.** Do not subject the smokeless powder to unnecessary handling or exposure to the atmosphere. The handling and loading of smokeless powder exposed to the atmosphere shall be performed only under conditions that do not permit the relative humidity to exceed 75 percent.

3.6.4 **Smokeless powder, condition.** The smokeless powder utilized shall exhibit no evidence of decomposition (see 4.6.4).

3.6.5 **Change of propellant lot.** Whenever a change occurs in the propellant lot, validity of the charge determination shall be verified by performing the test prescribed in 4.7.

3.7 **Cartridge inspection.**

3.7.1 **Visual inspection.** The cartridge shall be free of the visible defects noted in 4.6.5.

3.7.2 **Leakage.** There shall be no leakage of air in the completed cartridge (see 4.6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

3.7.3 **X-ray.** Each cartridge produced under a contract shall pass the X-ray examination of 4.6.2.2.

3.8 **Ballistic requirements.** Cartridges from each production lot, selected in accordance with 4.6.7, shall meet the requirements listed below when subjected to the test prescribed in 4.6.7.1.

3.8.1 **Velocity.** The lower limit of the ejection velocity shall be 44 feet per second (see 4.6.7.1.1).

3.8.2 **Chamber pressure.** The lower limit of maximum pressure shall be 800 psi (see 4.6.7.1.2).

3.8.3 **Maximum rate of increase of chamber pressure.** The upper limit for the maximum rate of increase of chamber pressure shall be 13,450 pounds per square inch per second (see 4.6.7.1.3).

3.8.4 **Misfire.** There shall be no misfires (see 4.6.7.2).

3.8.5 **Hangfire.** There shall be no hangfires (see 4.6.7.3).

3.9 **Workmanship.** Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 **Responsibility for compliance.** All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 **Classification of inspections.** The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 **Inspection conditions.** Unless otherwise specified (see 6.2), all inspections shall be performed as specified in the applicable test method of 4.6.

4.4 **First article inspection.** First article inspection shall be performed after award of contract and prior to production by a facility designated in the contract or order (see 6.2). A first article sample acceptable for environmental and function testing shall be considered as a sample which has met the requirements of 3.3 through 3.7.3 of this specification. First article inspection shall be performed on sample units which have



Source: https://assist.dla.mil -- Downloaded: 20261O-19T12:10Z
Check the source to verify that this is the currentversion before use.

been produced using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be from the intended sources of supply.

4.4.1 **Sample size.** The first article sample shall consist of 76 cartridges.

4.4.2 **Inspection routine.** Sixty-six cartridges shall be expended in the tests listed below and ten shall be retained for investigative purposes. The contractor shall deliver the cartridges to the activity designated by the contracting agency for test. The environmental tests to be performed on the first article sample and the number of cartridges required for each test are: 15 "g" shock (6), vibration (6), temperature and humidity cycling (18). Before exposure to the environmental tests described in MIL-D-21625, these cartridges shall be conditioned for a minimum of 6 hours at + 70° F ± 5° F together with 12 cartridges that received no previous environmental conditioning and fired in accordance with 4.6.7. In addition 24 cartridges shall be temperature conditioned for a minimum of 6 hours (12 at −65° F ± 5° F, 12 at + 160° F ± 5° F) and fired as prescribed in 4.6.7 to check temperature sensitivity. No cartridge firing shall produce results outside the limits set forth in 3.8.1 through 3.8.5 except for the following: For firings at − 65° F, the lower limit of maximum pressure shall be 490 psi, and the lower limit of ejection velocity shall be 35 feet per second. For firings at + 160° F, the upper limit for the maximum rate of increase of chamber pressure shall be 14,860 pounds per square inch per second. Any quantity production prior to notification by the contracting agency of first article sample acceptability shall be at the contractor's risk. The first article cartridges will not be applied as a part of the quantity specified for delivery by the contract.

4.4.3 **Failure.** Failure of any cartridge shall be cause for rejection of the first article sample.

4.5 **Quality conformance inspection.** Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of DL 491833 and the tests and examinations of table I.

TABLE I. Quality conformance tests and examinations.

| Item | Nature of test | Requirement | Test | Classification (WR-43) |
|---|---|---|---|---|
| Primary component | Single lot verification | 3.4 | 4.5.1 | (M101) |
| Primer | Age, type, loading and acceptance verification | 3.5 | 4.6.1 | (C1) |
| Primer | X-ray | 3.5.1 | 4.6.2.1 | (C3) |
| Propellant and ignition charges | Type and weight verification | 3.6.1 | - | (C3) |
| Black powder | Moisture content | 3.6.2 | 4.6.3 | (C4) |
| Smokeless powder | Condition | 3.6.4 | 4.6.4 | (C5) |
| Cartridge | Ballistics (change in propellant lot) | 3.6.5 | 4.7 | (C6) |
| Cartridge | Visual inspection | 3.7.1 | 4.6.5 | (M102) |
| Cartridge | Leakage | 3.7.2 | 4.6.6 | (C7) |
| Cartridge | X-ray | 3.7.3 | 4.6.2.2 | (C8) |
| Cartridge | Ballistic | 3.8 | 4.6.7 | (C9) |
| Cartridge | Packing and marking | Section 5 | — | (M103) |

4.5.1 **Production lot.** The suggested production lot size is 801 minimum and 1,300 maximum cartridges. Cartridges required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

shall be used in a production lot of cartridges. One primary component production lot may be used in more than one cartridge production lot. Cartridges selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

**4.5.2 Sampling.** Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-414. Unless otherwise specified in the contract, order, or requisition, all samples for test purposes shall be provided at the expense of the contractor.

**4.5.3 Classification of characteristics.** The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C), and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

**4.6 Tests.**

**4.6.1 Primer.** Verification shall be provided that the primers used were certified and accepted in accordance with the requirements of 3.4.

**4.6.2 Radiographic examination.**

**4.6.2.1 Primers.** Prior to assembly, all primers shall be radiographically examined in accordance with MIL-STD-453. Primers having any of the defects specified in 3.4 shall be rejected. The primers shall be mounted on boards or trays, preferably grooved, with the cup side perpendicular to the rays, for the most revealing exposure. Pressure sensitive tape may be used as an aid in positioning the primers. The X-ray negatives shall be identified by item nomenclature and lot number. Primers are to be left mounted to the boards or trays until after the X-rays have been reviewed and defects identified to facilitate removal of defects. After screening, the X-rays with defectives identified, shall be forwarded to the engineering agency designated by the procuring activity.

**4.6.2.2 Cartridges.** All cartridges shall be radiographically examined in accordance with MIL-STD-453. Cartridges having any observable imperfections in assembly shall be rejected. The cartridges shall be positioned on their sides for the most revealing exposure. All cartridges shall be identified with serial numbers prior to examination. The cartridge serial numbers shall be in consecutive order beginning with the number 001 in each production lot. The cartridges shall be arranged on trays or boards in consecutive numerical order, and each radiograph shall carry a permanent identification of the cartridges displayed thereon. The radiograph identification shall include the complete lot number, as stamped on the cartridges, and the span of serial numbers displayed. Discontinuities in serial numbers shall be identified on the X-ray. Defective cartridges found by the vendor shall be clearly identified on the X-ray and those defectives removed from the production lot. The serial numbers shall be pen or ink stamped on the cartridges with approximately 1/8-inch-high characters. The serial numbers shall be located apart from the other cartridge markings.

**4.6.3 Moisture content of black powder.** Conduct at least one test for each cartridge lot (or daily whichever requires the more frequent testing) and such additional tests as considered warranted by variations in conditions or process. Samples may be collected at the site of loading from the powder container, or taken from cartridges prior to sealing the black powder charge in the cartridge. Weight losses per booster charge shall be ascertained with an accuracy of 0.2 milligram. The presence of moisture in excess of the limitations of 3.5.2 shall cause suspension of loading until corrective measures have been taken.

**4.6.4 Smokeless powder, condition.** Smokeless powder shall be inspected in accordance with the applicable portions of paragraphs 1308-1318 and 1322 of OP 5. Evidence of decomposition shall be cause for rejection.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

4.6.5 **Visual inspection.** Examine all cartridges produced and reject for: dents, deep scratches, pinches O-ring gaskets, split or cracked lip in the crimped area, chipping or flaking of the anodized finish, sharp edges (particularly on the under side of the shoulder), or other defects which may conceivably prevent entry into the firing chamber or affect the stability or resistance to moisture.

4.6.6 **Leakage.** Each cartridge in the first article sample or production sample shall be leak tested in a dry gas or dry air leak tester. A cartridge which exhibits a leak rate in excess of $10^{-5}$ cc/sec gas or air at a pressure differential of 1.0 ± 0.1 atmosphere shall be considered defective. Cartridges of the first article sample which exhibit a leakage defect shall be rejected. If one or more cartridges of the production sample exhibits a leakage defect, then a 100 percent leak test of the lot being tested shall be required at no additional expense to the government. Cartridges which exhibit a leak rate in excess of that specified above shall be rejected.

4.6.7 **Ballistic tests.** The number of cartridges selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table A-2 of MIL-STD-414, Inspection Level IV at an AQL of 0.04. An additional ten cartridges shall be furnished with each test sample for investigative purposes. The cartridges shall be conditioned for a minimum of 6 hours at +70° F ± 5° F and fired in the MARK 327 MOD 0 ballistic test set, DL 491820, using a propelled load of 360 pounds. The firing chamber shall be thoroughly cleaned before each firing.

4.6.7.1 **Acceptance criteria.**

4.6.7.1.1 **Velocity.** The velocity of the propelled load shall be measured over the interval from 40 to 46 inches of travel from its initial position. Instrumentation used shall record the ejection velocity to within an accuracy of 1.0 percent. The lower specification limit (L) shall be specified in 3.8.1. The lot shall be accepted if the quantity $(\bar{X} - L)/S$ is greater than the appropriate value of K in Table B-1 of MIL-STD-414 at an AQL of 0.04.

4.6.7.1.2 **Maximum chamber pressure.** The lower specification limit (L) for maximum pressure shall be as specified in 3.8.2. Instrumentation used shall record the maximum chamber pressure to within an accuracy of 2.0 percent. The lot shall be accepted if the quantity $(\bar{X} - L)/S$ is greater than the appropriate K value in Table B-1 of MIL-STD-414, at an AQL of 0.04.

4.6.7.1.3 **Maximum rate of increase of chamber pressure.** The maximum rate of increase of chamber pressure shall be measured over the substantially linear portion of the pressure-time curve, over an interval of 0.02 second, neglecting small perturbations. The upper specification limit (U) for the maximum rate of increase of chamber pressure (DP/DT) shall be as specified in 3.8.3. The lot shall be accepted if the quantity $(U-\bar{X})/S$ is greater than the appropriate value of K in Table B-1 of MIL-STD-414 at an AQL of 0.04.

4.6.7.2 **Misfire.** The failure of any cartridge to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.6.7.3 **Hangfire.** One or more hangfires shall result in rejection of the lot represented. A hangfire is defined as a firing in which the elapsed time between actuation of the firing mechanism and first indication of pressure or case opening exceeds 0.05 second.

4.6.8 **Retest.** There shall be no retests.

4.6.8.1 **Test failure.** If test failure is attributable to an assignable cause, excluding the test cartridges, original test results should be discarded and the test reconducted with a new sample of cartridges.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

4.7 **Change in propellant lot.** Whenever a change in propellant lot occurs, validity of the charge determination shall be verified by firing 36 cartridges temperatures conditioned for a minimum of 6 hours (12 at −65° F ± 5° F, 12 at +70° F ± 5° F and 12 at +160° F ± 5° F). Acceptability of firings at the various temperatures shall be as provided in 4.4.2.

## 5. PACKAGING.

5.1 **Preservation and packaging.** For definitions of packaging levels see 6.3.

5.1.1 **Level A.** Level A packaging shall be used in packaging of all production lots for service use. One cartridge shall be packaged in an inner container in accordance with Drawing 1665585 of DL 486208.

5.1.2 **Level B.** Not applicable.

5.1.3 **Level C.** When directed by the procuring activity, those cartridges which are intended for expenditure in first article sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with 49 CFR 171-178.

5.2 **Packing.** For definitions of packing levels, see 6.3.

5.2.1 **Level A.** Level A packing shall be used for packing of all production lots for service use. Twelve inner containers as described in 5.1.1 shall be packed in accordance with Drawing 1800305 of DL 486209.

5.2.2 **Level B.** Not applicable.

5.2.3 **Level C.** When directed by the procuring activity, cartridges intended for expenditure in first article sample testing and for production lot acceptance tests and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with 49 CFR 171-178.

5.3 **Markings.**

5.3.1 **Special markings.** Marking of exterior containers shall be in accordance with 49 CFR 171-178.

5.3.2 **Normal markings.** In addition to markings required by contract or order, and as required by DL 486208 and DL 486209, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

## 6. NOTES

6.1 **Intended Use.** The MARK 18 MOD 0 impulse cartridge was designed for use in the explosive actuated cylinder installed in the escape door emergency system of the A-3 aircraft.

6.2 **Ordering information.** Acquisition documents should specify the following:

a. Title, number and date of this specification

b. Whether first article inspection is required and if so, specify the test activity

c. Production lot size and test activity (see 4.5.1)



Source: https://assist.dla.mil -- Downloaded: 202610-19T12:10Z
Check the source to verify that this is the current version before use.

6.3 **Definitions.** The definitions of Levels A and C packaging and packing are given below.

6.3.1 **Level A packaging.** The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.3.1.1 **Level C packaging.** The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commerical practice when such meets the requirements of this level.

6.3.2 **Level A packing.** The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.3.2.1 **Level C packing.** The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirements of this level.

6.4 **Advisory leak test.** Indian Head leak tests cartridges in accordance with "Cartridge Leak Test Procedures at the Naval Ordnance Station, Indian Head, MD."

6.5 **First article.** When a first article inspection is required, the item should be a first article sample. The first article should consist of 76 cartridges. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.6 Subject term (key word) listing.

Cartridge
Charges
Black Powder
Smokeless Powder
Propellant Lot
Primers

Preparing activity:
Navy - AS

(Project 1377- N825



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS**: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE*: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
(SESD), Code 93
Lakehurst, NJ 08733

**OFFICIAL BUSINESS**
**PENALTY FOR PRIVATE USE $300**

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
(SESD). Code 93
Lakehurst, NJ 08733

Source: https://assist.dla.mil -- Downloaded: 202610-19T12:10Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-22362D | Cartridge, Impulse, Mark 18 Mod 0 |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:10Z
Check the source to verify that this is the current version before use.