MILITARY SPECIFICATION SHEET

INTERCOMMUNICATION SETS AN/AIC-14 AND AN/AIC-14A

PASSIVE INTERPHONE CONTROL PANEL

C-2643/AIC-14

Inactive for new design after 10 August 1984
For new design use MIL-I-22352/17 or MIL-I-22352/18.

This specification sheet is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the unit described herein shall consist of this document and the latest issue of specification MIL-I-22352.

1. SCOPE

This specification sheet provides performance and physical characteristics for the passive Interphone Control panel C-2643/AIC-14, hereinafter referred to as C-2643.

1.2 Military Part Number. The military part number shall be M22352/26-1

2. APPLICABLE DOCUMENTS

Refer to 2.3 of MIL-I-22352 for a listing of applicable documents. The requirements specified herein shall have precedence over all referenced documents. The contract and is attachments shall have precedence over any specification or reference document.

3. REQUIREMENTS

3.1 Item Definition. The passive interphone control panel shall provide the operator with the capability to activate interconnections with on-board receivers and transmitters. The operator using the C-2644 shall have the capability to interact with the associated radio transmitters and receivers and to have access to both interphone signals. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.

operator shall have the capability of selecting from the OFF mode, a receive mode from four associated receivers, or keying and connecting of transmit audio to one selected transmitter of the two available.

3.1.1 Item Diagram. Passive Control Panel C-2644 shall provide the functions represented schematically in accordance with the diagram of Figure 1.

3.1.2 Interface definition. The passive Interphone Control panel input and output signals will normally exhibit the characteristics presented in Table I.

TABLE I. Interface signal list.

Signal Name	Characteristics
Inputs:	
Receiver No. 1 (RCVR NO. 1)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 15 Vac. No dc component normally present.
Receiver No. 2 through Receiver No. 4 (RCVR NO. X)	Same as Receiver No. 1
Interphone No. 1 and Interphone No. 2 (INTPH NO. X)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 1 Vac. No dc component normally present.
Transmit Audio (XMIT AUDIO)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 1 Vac.
Transmit Key (XMIT KEY)	Relay logic having two states: 1) Open and 2) Short to ground
Panel Lights (LIGHTS)	0 to + 28Vdc or 0 to 6V., 400 Hz

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.

TABLE I. Interface signal list - continued.

Signal Name	Characteristics
Outputs:	
Interphone (INTPH)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 1 Vac. No dc component normally present.
Selected Receiver (SEL RCVR)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 1 Vac. No dc component normally present.
Transmit Audio No. 1 and No. 2 (XMIT AUDIO NO. X)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 1 Vac. No dc component normally present
Transmit Key No. 1 and No. 2 (XMIT KEY NO. X)	Relay logic: 1) lamp supply voltage 2) short to ground
Emergency Receiver No. 1, No. 2 and No. 3 (EMER RCVR NO. X)	Voice range audio (300 to 6,000 Hz) signal ranging in amplitude from 0 to 15 Vac. No dc component normally present.
Grounds:	
Power (PWR GND)	Power return. See 3.4.4.2 of MIL-I-22352.
System (SYS GND)	Signal return. See 3.4.4.3 of MIL-I-22352.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T12:08Z
Check the source to verify that this is the current version before use.

3.1.3 Controls. The passive Interphone Control panel shall provide the controls listed in Table II.

TABLE II. C-2644/AIC-14 controls list.

Title	Function
TRANS SEL	The C-2643 shall provide two two-position toggle switches for the selection of two transmitters for keying and connection of the transmit audio. One transmitter is associated with each of the two switches.
PCVR SEL	The C-2643 shall provide five two-position toggle switches with the following functions: OFF - In the down position the associated receiver output is disabled. ON - In the up position the system shall present the audio signals from the associated receiver.

3.1.4 Panel Lamps. The passive Interphone Control panel shall provide the two (edge lighted) panel lamps to illuminate the front panel.

3.2 Characteristics.

3.2.1 Performance Characteristics.

3.2.1.1 Input Characteristics.

3.2.1.1.1 Receiver No. 1 through No. 4 (RCVR NO. X). The signals incoming from radio receivers shall be identified and assigned as a function of the aircraft in which the system is installed. The RCVR input characteristics shall be as follows:

3.2.1.1.1.1 Signal Frequency. The RCVR NO. X inputs shall accept drive signals which range from 300 to 6,000 Hz.

3.2.1.1.1.2 Signal Amplitude. The RCVR NO. X inputs shall accept drive signals which range in amplitude from 0 to 15 Vac.

3.2.1.1.1.3 Input Impedance. The RCVR NO. X inputs shall each present a 10,000 ohm ±10 percent impedance to the incoming signals when the ON (up) position is selected on the RCVR SEL switch otherwise open.

3.2.1.1.1.4 Isolation. The isolation between RCVR NO. X signals shall be at least 68 dB for signals ranging from 300 to 6,000 Hz.

Source: https://assist.dla.mil -- Downloaded: 202610-19T12:08Z
Check the source to verify that this is the current version before use.

3.2.1.1.2 Interphone No. 1 and Interphone No. 2 (INTPH NO. X). The INTPH NO. 1 through INTPH NO. 5 input characteristics shall be as follows:

3.2.1.1.2.1 Signal Frequency. The INTPH NO. X input shall accept drive signals which range from 300 to 6,000 Hz.

3.2.1.1.2.2 Signal Amplitude. The INTPH inputs shall accept drive signals which range in amplitude from 0 to 10 Vac.

3.2.1.1.2.3 Input Impedance. The INTPH inputs shall each present a 62,000 ohm ±10 percent impedance to the incoming signals.

3.2.1.1.2.4 Isolation. The isolation between RCVR signals shall be at least 68 dB for signal ranging from 300 to 6,000 Hz.

3.2.1.1.3 Transmit Audio (XMIT AUDIO). The XMIT AUDIO signal shall be applied to the TRANS SEL switches. The XMIT AUDIO input shall exhibit the following characteristics:

3.2.1.1.3.1 Signal Frequency. The XMIT AUDIO input shall accept drive signals which range from 300 to 6,000 Hz.

3.2.1.1.3.2 Signal Amplitude. The XMIT AUDIO input shall accept drive signals which range in amplitude from 0 to 10 VAC.

3.2.1.1.4 Transmit Key (XMIT KEY). The XMIT KEY input shall accept a relay drive logic signal having two states: 1) open and 2) short to ground. The XMIT KEY signal shall be used to product the XMIT KEY NO. 1 and NO. 2 output on the line associated with the transmitter selected by the TRANS SEL switches.

3.2.1.1.5 Panel Lights (LIGHTS). The C-2643 shall be capable of accepting power ranging up to +28Vdc or 6 Vac to illuminate the two front panel lamps. The panel lamps used shall be selected accordingly from Table III.

TABLE III. Front panel bulbs.

Nomenclature	Power
MS25237A-327 MS25237A-328	+28 Vdc 6 Vac

Source: https://assist.dla.mil -- Downloaded: 20260-19T12:08Z
Check the source to verify that this is the current version before use.

3.2.1.2 Output Characteristics. All signals which are passed through this unit from input to output by being routed only through connectors, wire, printed wiring, switches, and relays shall not experience insertion loss in excess of 0.5 dB. The C-2643 passive Interphone Control Panel shall have the following output characteristics.

3.2.1.2.1 Interphone (INTPH). The INTPH output shall be the sum of INTPH NO. 1 and NO. 2 signals each reduced by 40.4 ± 1dB in amplitude from the individual input value(s) and summed when terminated in 600 ohms. The contribution to the total by each input shall be equal ± 10 percent.

3.2.1.2.2 Selected Receiver (SEL RCVR). The SEL RCVR output shall be the sum of the operator selected RCVR NO. 1 through RCVR NO. 4 inputs adjusted (reduced) in amplitude by the RAD VOL control. Each RCVR input shall contribute equally ±10 percent to the total output.

3.2.1.2.3 Transmit Audio No. 1 through Transmit Audio No. 2 (XMIT AUDIO NO. X). The XMIT AUDIO NO. X output line shall be taken from the XMIT AUDIO input. The specific active line to present the output shall be determined by operator selection of the associated TRANS SEL switch to the ON position.

3.2.1.2.4 Transmit Key No. 1 and Transmit Key No. 2 (XMIT KEY NO. X). The XMIT KEY NO. X output shall be a relay drive logic signal having two states: 1) open and 2) short to ground. The output shall be a short to ground when the associated TRANS SEL switch is selected to ON position and the XMIT KEY input is a ground. KEY NO. 2 output signal shall exhibit equivalent.

3.2.1.2.5 Emergency Receiver No. 1, Emergency Receiver No. 2 and Emergency Receiver No. 3 (EMER RCVR No. X). The EMER RCVR NO. X output shall be connected to the RCVR NO. X input through the associated RCVR SEL switch within the C-2643. Therefore, the output characteristics shall be identical to the input.

3.2.2 Physical characteristics.

3.2.2.1 Dimensions. The C-2643 shall consist of a single panel-mounted assembly having the dimensions of Figure 2. All outside dimensions shall be within 0.03 inches of the nominal value shown.

3.2.2.2 Weight. The C-2643 shall weigh no more than 2.0 pounds.

3.3 Design and Construction. The design and construction of the passive Interphone Control panel C-2643 shall be in accordance with the requirements of 3.3 of MIL-I-22352.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.

3.3.1 Front panel lighting. The front panel lamps shall be installed using mounting hardware having red filters in accordance with MIL-L-25467 to enhance night vision. The panel lamps shall be mounted in accordance with the outline drawing Figure 2. The lamp drive circuitry shall be capable of accommodating power ranging up to 28 Vdc or 6 V, 400 Hz ac.

4. QUALITY ASSURANCE PROVISIONS

See MIL-I-22352.

4.1 Responsibility for tests and inspections. See MIL-I-22352.

4.2 Test plan. A detailed test plan will be submitted by the contractor for approval by the acquiring activity which details the tests to be performed in order to verify compliance with the performance characteristics specified in 3.2.1. The test plan will consider all of the inspections delineated in 4.2 of MIL-I-22352.

4.3 Test procedures. Detailed test procedures will be submitted by the contractor for approval by the acquiring activity which will satisfy the requirements of the test plan of 4.2.

Preparing Activity
Navy - AS
(Project No. -5832-N027

Source: https://assist.dla.mil -- Downloaded: 20260-19T12:08Z
Check the source to verify that this is the current version before use.





FIGURE 1. C-2643 functional diagram.

Source: https://assist.dla.mil -- Downloaded: 202610-19T12:08Z
Check the source to verify that this is the current version before use.



NOTE:
ALL DIMENSIONS ARE IN INCHES.
TOLERANCES ON DIMENSIONS ARE ± 0.03 INCHES UNLESS OTHERWISE SPECIFIED.

FIGURE 2. C-2643 outline drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Department
(ESSD), Code 93
Lakehurst, NJ 08733

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Dept.
(ESSD), Code 93
Lakehurst, NJ 08733

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-22352/26	INTERCOMMUNICATION SETS AN/AIC-14 AND AN/AIC-14A PASSIVE INTERPHONE CONTROL PANEL C-2643/AIC-14

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:08Z
Check the source to verify that this is the current version before use.