INCH-POUND

MIL-DTL-39024/2D
3 February 2003
SUPERSEDING
MIL-C-39024/2C
14 August 1991

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, TEST POINT TYPE, PANEL TYPE; SINGLE TEST POINT (THREADED), HIGH VOLTAGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-39024.



Inches	mm	Inches	mm
.016	0.41	.100	2.54
.026	0.66	.120	3.05
.030	0.76	.130	3.30
.050	1.27	.195	4.95
.055	1.40	.250	6.35
.062	1.57	.281	7.14
.070	1.78	.312	7.92
.085	2.16	.41	10.4
		1.000	25.40

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .010 (0.25 mm) for three place decimals and ± .03 (0.8 mm) for two place decimals.
4. Parts supplied unassembled.
5. Hex nut .338 (8.59 mm) ± .006 (0.15 mm) across flats x .09 (2.3 mm) ± .03 (0.8 mm) thick.

FIGURE 1. Configuration and dimensions.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.

TABLE I. Design and identification data.

Dash number	Terminal style	Insulation	
		Color	Number in accordance with FED-STD-595
-01	Turret	White	17875
-02	"	Red	11105
-03	"	Black	17038
-04	"	Brown	10075
-05	"	Green	14110
-06	"	Orange	12246
-07	"	Blue	15123
-08	"	Yellow	13655
-09	"	Gray	16187
-10	"	Purple	27144
-11	Eyelet	White	17875
-12	"	Red	11105
-13	"	Black	17038
-14	"	Brown	10075
-15	"	Green	14110
-16	"	Orange	12246
-17	"	Blue	15123
-18	"	Yellow	13655
-19	"	Gray	16187
-20	"	Purple	27144

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Terminals: Shall be capable of being wired with two type E, AWG 20 wires in accordance with NEMA-HP3. Configuration shall be specified on figure 1 and table I.

Operating temperature: -65°C to +200°C.

Test probe: .080 ± .001 inch in diameter and .438 inch (min) length.

Contact current rating: 5 amperes (max).

Contact resistance: A test probe in accordance MIL-DTL-39024 shall be fully inserted in the connector. With a current of 5 amperes, potential drop shall be measured between the connector terminal and the extreme end of the solder cup on the test probe. Measured values shall be 20 millivolts (max).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage (at sea level):

Measurements shall be made between current carrying parts and ground as specified in MIL-DTL-39024.

Test voltage: 5,000 volts rms, 60 hertz.

Insertion and withdrawal forces:

Insertion force: 4.5 pounds (max).
Withdrawal force: 0.4 pound (min).

Thermal shock: Shall be in accordance with method 107 of MIL-STD-202, condition C.

Identification marking:

Part or Identifying Number (PIN): M39024/2-(dash number from table I).

Operating conditions:

Operating voltage, when applied between ground and current carrying parts, is 3,700 volts rms, 60 hertz at sea level; and 1,000 volts rms, 60 hertz at 50,000 feet.

Maximum thickness of panel on which these connectors may be used is .094 inch.

Qualification: Not applicable.

Quality conformance inspection. Quality conformance inspection: Group A and B tests of MIL-DTL-39024 shall be applicable.

Note: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
DLA - CC

(Project 5935-4438-002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.