INCH-POUND


MIL-DTL-39024/3C
22 September 2018
SUPERSEDING
MIL-C-39024/3B
14 August 1991

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, TEST POINT TYPE, PRINTED WIRING, SINGLE TEST POINT (RIGHT ANGLE, 2-LEG MOUNTING), LOW VOLTAGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-39024.



Inches	mm	Inches	mm
.001	0.3	.130	3.30
.005	0.13	.190	4.83
.010	0.25	.400	10.16
.016	0.41	.437	11.10
.040	1.02	.531	13.49
.052	1.32	.600	15.24
.080	2.03		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Terminal contour is optional provided that mounting hole and mounting center requirements are met.

FIGURE 1. Configuration and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions and color code.

Dash number	Dimensions 1/		Color
	A (max)	B	
-01	.230 (5.84)	.130 (3.30) ± .015 (0.38)	White
-02	"	"	Red
-03	"	"	Black
-04	"	"	Brown
-05	"	"	Green
-06	"	"	Orange
-07	"	"	Blue
-08	"	"	Yellow
-09	"	"	Gray
-10	"	"	Purple
-11	.467 (11.86)	.375 (9.53)	White
-12	"	"	Red
-13	"	"	Black
-14	"	"	Brown
-15	"	"	Green
-16	"	"	Orange
-17	"	"	Blue
-18	"	"	Yellow
-19	"	"	Gray
-20	"	"	Purple

1/ Metric equivalents are in parentheses.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Test probe tip – Connector jack shall accept a .080 ± .001 inch diameter and .438 inch (min) length, test probe tip.

Insulation resistance: For test circuit, see figure 2 in MIL-DTL-39024.

Dielectric withstanding voltage (at sea level): A test voltage of 2,500 volts rms, 60 hertz shall be applied. (For test circuit, see figure 2 in MIL-DTL-39024).

Insertion and withdrawal forces:

Insertion force: 4.5 pounds (max).

Withdrawal force: 0.5 pound (min)

Identification marking:

Part or Identifying Number (PIN): M39024/3-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.

OPERATING NOTES:

1. Operating voltage at sea level is 1,800 volts rms, 60 hertz, and at 50,000 feet is 500 volts rms, 60 hertz.
2. Maximum thickness of printed wiring board is .125 inch.

QUALIFICATION: Not applicable.

Quality conformance inspection: Groups A and B tests of MIL-DTL-39024 shall be applicable.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. This document references MIL-DTL-39024.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force - 85
DLA -CC

Preparing activity:
DLA-CC

(Project 5935-2018-122)

Review activities:
Army – AR, CR4, MI
Navy – AS, CG, MC, OS
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:23Z
Check the source to verify that this is the current version before use.