INCH-POUND
MIL-PRF-39023/7C
w/Amendment 3
11 September 2020
SUPERSEDING
MIL-PRF-39023/7C
w/Amendment 2
1 December 2015

PERFORMANCE SPECIFICATION SHEET

RESISTOR, VARIABLE, NONWIREWOUND, PRECISION, STYLE RQ160

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39023.

1. SCOPE

1.1 Scope. This specification covers the requirements for style RQ160, variable, nonwirewound, precision resistors.

1.2 Classification.

1.2.1 Part or Identifying Number (PIN). The PIN is in the following form:

Single-section (cup) resistors

RQ160AA12AB103

RQ160	-	Style
A	-	Resistance temperature characteristic, maximum ambient temperature and taps (1.2.2)
A	-	Shaft length (1.2.3)
1	-	Moisture resistance (1.2.4)
2	-	Life characteristic (1.2.5)
A	-	Function conformity tolerance characteristic (1.2.6)
B	-	Output smoothness characteristic (1.2.7)
103	-	Resistance (1.2.8)

1.2.2 Resistance temperature characteristic, maximum ambient temperature and taps. The resistance temperature characteristic, maximum ambient temperature and taps applicable to this specification are symbols A and B.

1.2.3 Shaft length. The shaft length applicable to this specification are symbols A to F, inclusive.

1.2.4 Moisture resistance. The moisture resistance applicable to this specification are symbols 1 and 2.

1.2.5 Life Characteristic. The life characteristics applicable to this specification are 1 to 4, inclusive.

Comments, suggestions, or questions on this document should be addressed to: DLA Land and Maritime, ATTN: VAT, Post Office Box 3990, Columbus, Ohio 43218-3990 or by email resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/

AMSC N/A

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:20Z
Check the source to verify that this is the current version before use.

1.2.6 Function conformity tolerance characteristic. The function conformity tolerance characteristic applicable to this specification are symbols A to E, inclusive.

1.2.7 Output smoothness characteristic. The output smoothness characteristic applicable to this specification are symbols A to E, inclusive.

1.2.8 Resistance. The nominal total resistance values and maximum end voltage applicable to this specification will be in accordance with table I.

TABLE I. Nominal total resistance values and maximum end voltage.

Nominal total resistance values	Maximum end voltage (percent of total applied voltage)	Nominal total resistance values	Maximum end voltage (percent of total applied voltage)
Ohms	Percent	Ohms	Percent
1,000	1.4	50,000	
2,000	1.3	0.10 Megohm	
5,000	1.3	0.20 Megohm	1.3
10,000	1.3	0.50 Megohm	
20,000	1.3	1.00 Megohm	

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-39023 - Resistor, Variable, Nonwirewound, Precision, General Specification for.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the event of a conflict between the text of this document and the references cited herein (except for related specifications), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.


3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-39023.

3.2 Interface and physical dimensions. The resistors shall meet the interface and physical dimension specified in figure 1.

3.3 Minimum total resistance. The minimum total resistance value shall be 1,000 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:20Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
0.0005	0.01	0.015	0.38	0.063	1.60	1.094	27.79	1.468	37.29	2.50	63.50
0.0006	0.02	0.031	0.79	0.073	1.85	1.3125	33.34	1.625	41.28		
0.005	0.13	0.047	1.19	0.093	2.36	1.313	33.35	2.00	50.80		
0.010	0.25	0.062	1.57	0.250	6.35	1.437	36.50	2.025	57.15		

NOTE: Dimensions are in inches. Metric equivalents are given for general information only.

Style	Turns	Maximum continuous working voltage (volts)	Power rating (watts) 1/	Maximum starting and running torque (ounce-inch)				Stop-torque (pound-inch)
				Single cup		Per each additional cup		
				Starting	Running	Starting	Running	
RQ160	10	500	3.5	1.5	1.0	1.5	1.0	8

1/ When 2 single units are ganged, the first cup shall be rated at 75 percent of single unit wattage rating and second cup shall be rated at 60 percent of rated wattage

FIGURE 1. Style RQ160

3.4 Maximum total resistance. The maximum total resistance value shall be 3.0 megohm.

3.5 Mechanical travel. The mechanical travel shall be 3600 degrees + 100 degrees, - 0 degrees continuous.

3.6 Theoretical electrical travel. The theoretical electrical travel shall be 3600 degrees.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:20Z
Check the source to verify that this is the current version before use.

3.7 Ganged cups. There shall be no more than 2 cups ganged.

3.8 Phasing. The phasing shall be for simultaneous conformity.

3.9 Weight. The maximum weight shall be 5.0 ounces and each additional cup shall be 4.0 ounces.

3.10 Function conformity. The type of conformity shall be independent linearity.

3.11 Pure tin. The use of pure tin, as an underplate or final finish, is prohibited both internally and externally. Tin content of resistor components and solder shall not exceed 97 percent, by mass. Tin shall be alloyed with a minimum of 3 percent lead, by mass (see 6.4).

4. VERIFICATION

4.1 Sampling and inspection. Sampling for delivery shall be in accordance with MIL-PRF-39023.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the military system commands Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-39023 will be applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification, and the complete PIN (see 1.2).
b. Unless otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.
c. Packaging requirements (see 5.1).

6.3 PIN. This specification requires a PIN that describes technology and appropriate references to associated documents (see 1.2 and 3.1).

6.4 Tin whisker growth. The use of alloys with tin content greater than 97 percent, by mass, may exhibit tin whisker growth problems after manufacture. Tin whiskers may occur anytime from a day to years after manufacture and can develop under typical operating conditions, on products that use such materials. Conformal coatings applied over top of a whisker-prone surface will not prevent the formation of tin whiskers. Alloys of 3 percent lead, by mass, have shown to inhibit the growth of tin whiskers. For additional information on this matter, refer to ASTM-B545 (Standard Specification for Electrodeposited Coatings of Tin).

6.5 Amendment notations. The margins of this specification are marked with vertical lines to indicate modification generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities
Army - AR, AT, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19

(Project 5905-2020-053)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:20Z
Check the source to verify that this is the current version before use.