MIL-C-39012/43A
AMENDMENT 2
1 November 1979
SUPERSEDING
AMENDMENT 1
21 May 1976

MILITARY SPECIFICATION SHEET

CONNECTORS, COAXIAL, RADIO FREQUENCY
SERIES SC (UNCABLED - RECEPTACLE, FEMALE, JAM NUT MOUNTED,
REAR MOUNTED, CLASS 2)

This amendment forms a part of Military Specification Sheet MIL-C-39012/43A, dated 19 April 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1: Delete ".260 MAX PANEL" and substitute ".045 MIN / .260 MAX PANEL"; delete "3/4-32NS-2A" and substitute ".750-32NS-2A (SEE NOTE 5)".

* FIGURE 1, NOTES: Add the following:
"5. Full threads to within .063 (1.60 mm) of shoulder; 1 1/2 max uneven threads to shoulder.
6. There shall be a solder barrier in the socket between the pin entry and the solder pocket to prevent solder wicking."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AM, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3075-10)

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:57Z
Check the source to verify that this is the current version before use.