INCH-POUND

MIL-PRF-39012/39G
AMENDMENT 1
24 April 1996

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY
(SERIES SC (CABLED), PIN CONTACT, RIGHT ANGLE, CLASS 2)

This amendment forms a part of MIL-PRF-39012/39G, dated 26 September 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete and substitute the following title as follows;

"CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY
(SERIES SC (CABLED), PIN CONTACT, RIGHT ANGLE, CLASS 2)"

Figure 1, General configuration, add the following new note 9 as follows;

"9. Three holes .027 (0.69 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on the coupling nut optional."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - ES

(Project 5935-4054-06)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:56Z
Check the source to verify that this is the current version before use.