
MILITARY SPECIFICATION SHEET

CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY,

(SERIES SMA (CABLED) - PLUG, PIN CONTACT, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-39012.




MARKING IMPLEMENTATION DATE, CATEGORY B, SEE TABLE VII

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. For dimension A, see table I and V.
4. Dimension .400 (10.16 mm) is the largest overall diameter of the connector.
5. Width across flats are to accommodate wrench, nominal size of .3125 (7.937 mm) minimum in accordance with FED-STD-H28, appendix 10, wrench openings.
6. Dimension A defines the overall length of connector when assembled to the cable.
7. All undimensioned pictorial configurations are for reference purposes only.
8. Series SMA, pin contact interface in accordance with MIL-STD-348.
9. Metric equivalents are in parentheses.

FIGURE 1. General configuration.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.



Insulator dimensions for category D only

Inches	mm
.001	0.03
.005	0.13
.008	0.20
.021	0.53
.042	1.07
.140	3.56

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Chamfer is optional, if chamfer is used put chamfer on a 30° maximum.
4. Three holes .016 (0.41 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on coupling nut optional.

FIGURE 2. Category D captivation detail.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference and dimensions.

Dash number	Applicable cable #	Dimensions	Inches-millimeters maximum 1/8/6/
Category A - Field serviceable (no special tools required) 3/ 9/			
3006 3106 7/ 4006 4106 7/	M17/93-RG178 M17/169-00001ø	A	1.030(26.16)
3007 3107 7/ 4007 4107 7/	M17/119-RG174 M17/173-00001ø M17/113-RG316 M17/172-00001ø		
3008 3108 7/ 4008 4108 7/	M17/54-RG122 M17/157-00001ø		
3009 3109 7/ 4009 4109 7/	M17/28-RG058 M17/60-RG142@ M17/84-RG223* M17/155-00001ø M17/158-00001ø M17/167-00001ø		
3010 3110 7/ 4010 4110 7/	M17/111-RG303*@ M17/170-00001ø		
3030 3130 7/ 4030 4130 7/	M17/152-00001		
Category C - Field replaceable (MIL-C-22520 crimp tool) 2/3/			
3025 3125 7/ 4025 4125 7/	M17/93-RG178∞ M17/169-00001∞ø	A	1.250(31.75)
3026 3126 7/ 4026 4126 7/	M17/119-RG174Σ M17/173-00001Σø M17/113-RG316Σ M17/172-00001Σø		
3027 3127 7/ 4027 4127 7/	M17/54-RG122*& M17/157-00001ø&		
3028 3128 7/ 4028 4128 7/	M17/60-RG142@~ M17/158-00001~ø M17/167-00001~ø M17/84-RG223*~		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.


TABLE I. Dash numbers, cross reference and dimensions - Continued.

Dash number	Applicable cable #	Dimensions	Inches-millimeters maximum 1/8/6/
Category C - Field replaceable (MIL-C-22520 crimp tool) 2/3/			
3029	M17/155-00001~ø		
3129 7/	M17/28-RG058*~		
4029	M17/111-RG303~	A	1.250(31.75)
4129 7/	M17/170-00001~ø		
Category D - Field replaceable - Defined piece parts 2/4/5/3/			
3502	M17/60-RG142@		
3602 7/	M17/158-00001ø	A	1.250(31.75)
4502	M17/128-RG400		
4602 7/	M17/175-00001ø		

1/ Millimeters are in parentheses.
2/ These connectors are assembled, using the applicable crimp tool, to the specified cables stripped as shown on figure 4.
3/ These connectors have captivated center contacts.
4/ Complete connector assembly shall consist of a body, center contact, ferrule, and assembly instructions.
5/ Not for use in army equipment.
6/ Coupling nuts shall be corrosion resistant steel with a passivated finish per MIL-F-14072.
(applies only to "-3XXX" series connectors).
7/ No safety wire holes.
8/ For logistics purposes, only connectors with safety wire holes will be stocked.
9/ All corrosion resistant steel bodied connectors which are designed to be assembled to the cable outer conductor using solder shall be gold plated per MIL-G-45204, Type II, Class I,

The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in note @.
@ Cable to be used for the +200°C temperature cycling tests.
Connectors mate with connectors of the same material; i.e., M39012/59-3001 mates with M39012/55-3001, and M39012/59-4001 mates with M39012/55-4001.
∞ Preferred die M22520/5-33 closure B, alternate die M22520/5-03 closure B.
Σ Preferred die M22520/5-35 closure B, alternate die M22520/5-03 closure A.
& Preferred die M22520/5-41 closure B, alternate die M22520/5-05 closure B, or -09 closure A.
~ Preferred die M22520/5-19 closure B, alternate die M22520/5-05 closure A or -11, -57, closure A.
ø Caution is directed to the application of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.



CENTER CONTACT

CRIMP FERRULE

Dash no.	Contact no. 2/	A ±.001	Basic crimp tool 1/	Crimp die or positioner	Crimp tensile min	Color band □	Color band ○
3502 4502	55-10	.041	M22520/1-01	Solder or M22520/1-15	6 lbs	Red	Silver

Dash no.	Ferrule no. 2/	A +.001	B ±.001	Basic crimp tool 1/	Crimp die or positioner M22520/5-
3502 4502	55-50	.250	.220	M22520/5-01	M22520/5- 05, 11, 57 Closure A or 19 Closure B


Inches	mm	Inches	mm
.001	0.03	.050	1.27
.002	0.05	.062	1.57
.003	0.08	.100	2.54
.005	0.13	.133	3.38
.010	0.25	.153	3.89
.015	0.38	.193	4.90
.024	0.61	.220	5.59
.025	0.64	.250	6.35
.038	0.97	.421	10.69
.041	1.04	.500	12.70

1/ Class 2 tool may be used by OEM (see MIL-C-22520).
2/ Contact numbers and ferrule numbers are for identification only.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Crimp tensile test shall be in accordance with MIL-C-39029.
4. Copyright notice: All information disclosed in these specification sheets which is or may be copyrighted is reproduced herein with the express permission of the copyright owner.
5. .003 (0.08 mm) maximum break.

FIGURE 3. Contact and ferrule dimensions for category D only - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.



Inches	mm
.130	3.30
.150	3.81
.271	6.88
.291	7.39
.380	9.65
.400	10.16
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 4. Cable stripping dimensions for field replaceable connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 12,400 MHz.

Voltage rating: The voltage rating shall be in accordance with table II.

TABLE II. Voltage rating.

Cables	Voltage max (at sea level)	Voltage max (70,000 ft)
	Vrms	Vrms
M17/93-RG178, M17/169-00001	170	45
M17/54-RG122, M17/157-00001 M17/119-RG174, M17/173-00001 M17/94-RG179, M17/113-RG316, M17/172-00001 M17/152-00001	250	65
M17/28-RG58, M17/155-00001 M17/60-RG142, M17/158-00001 M17/84-RG223, M17/167-00001 M17/111-RG303, M17/170-00001 M17/128-RG400, M17/175-00001	335	85

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: 2 inch-pounds, maximum.

Coupling proof torque: 15 inch-pounds, minimum.

Inspection conditions: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Mating characteristics: Reference MIL-STD-348 and figure 2 for dimensions.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 302 of MIL-STD-202, test condition B.

5,000 megohms, minimum.

Center contact retention: 6 pounds, minimum axial force. Applicable to captivated-center-contact connectors only.

Radial torque: Not applicable.

Corrosion (salt spray): Method 101 of MIL-STD-202, test condition B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

Voltage standing wave ratio (VSWR):

Cables	VSWR
M17/93-RG178	1.20+0.025 (F) GHz
M17/54-RG122 M17/119-RG174 M17/94-RG179 M17/113-RG316, M17/152-00001	1.15+0.02 (F) GHz
M17/28-RG058 M17/60-RG142 M17/84-RG223 M17/111-RG303 M17/128-RG400	1.15+0.01 (F) GHz

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.025+.002 F (F in GHz).

Item 16: VSWR shall be less than 1.025+.002 F (F in GHz).

Second step of VSWR checkout procedure: VSWR shall be less than 1.080+.005 F (F in GHz).

Group B inspection: Use step 5, long cable method.

Qualification and group C inspection: Use step 5, long cable method.

Connector durability: Insertion and withdrawal force: 500 cycles, minimum at 12 cycles per minute, maximum.

The connector shall meet the mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact:	3.0	4.0
Outer contact:	2.0	Not applicable
Braid to body:	0.5 1/	Not applicable

Dielectric withstanding voltage at sea level:

Method 301 of MIL-STD-202.

Cables	Vrms
M17/93-RG178, M17/169-00001	500
M17/54-RG122, M17/157-00001 M17/119-RG174, M17/173-00001 M17/94-RG179 M17/113-RG316, M17/172-00001, M17/152-00001	750
M17/28-RG058, M17/155-00001 M17/60-RG142, M17/158-00001 M17/84-RG223, M17/167-00001 M17/111-RG303, M17/170-00001 M17/128-RG400, M17/175-00001	1,000

1/ Five milliohms are permissible on all passivated steel bodied connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

Vibration, high frequency: Method 204 of MIL-STD-202, test condition D. No discontinuity permitted.

Shock: Method 213 of MIL-STD-202, test condition I. No discontinuity permitted.

Thermal shock: Method 107 of MIL-STD-202, test condition B, except test high temperature shall be +85°C.

High temperature shall be +200°C for connectors using +200°C cables (see tables I and V).

Moisture resistance: Method 106 of MIL-STD-202.

No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Altitude: 70,000 feet.

Cables	Volts (min)
M17/93-RG178, M17/169-00001	125
M17/54-RG122, M17/157-00001 M17/119-RG174, M17/173-00001 M17/94-RG179 M17/113-RG316, M17/172-00001, M17/152-00001	190
M17/28-RG058, M17/155-00001 M17/60-RG142, M17/158-00001 M17/84-RG223, M17/167-00001 M17/111-RG303, M17/170-00001 M17/128-RG400, M17/175-00001	250

RF high potential withstanding voltage:

Frequency: 5 to 7.5 MHz

Leakage current: Not applicable.

Cables	Volts (min)
M17/93-RG178, M17/169-00001	335
M17/54-RG122, M17/157-00001 M17/119-RG174, M17/173-00001 M17/94-RG179 M17/113-RG316, M17/172-00001, M17/152-00001	500
M17/28-RG058, M17/155-00001 M17/60-RG142, M17/158-00001 M17/84-RG223, M17/167-00001 M17/111-RG303, M17/170-00001 M17/128-RG400, M17/175-00001	670

Cable retention force: The cable retention force shall be in accordance with table III.

TABLE III. Cable retention force.

Cable dielectric outer diameter	Pounds (min)	
	Single braid	Double braid
Inches (max)		
.036	10	N/A
.067	20	N/A
.110	30	N/A
.122	40	45

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

Coupling mechanism retention force: 60 pounds, minimum.

RF leakage: -60 dB minimum tested at a frequency between 2 and 3 GHz.

RF insertion loss: dB maximum = .06 $\times\sqrt{\text{freq GHz}}$. Test frequency at 6.0 GHz.

Part number: M39012/55- (dash number from table I or "B" number from table V).

TABLE IV. Group qualifications and retention testing.

Group	Submission and qualification of any of the following connectors 1/ 2/	Qualifies the following connectors
I	M39012/55-†009	M39012/55-†006 M39012/55-†007 M39012/55-†008 M39012/55-†009 M39012/55-†010 M39012/55-†030
II	M39012/55B†015	M39012/55B†011 M39012/55B†012 M39012/55B†013 M39012/55B†014 M39012/55B†015 M39012/55B†016 M39012/55B†017
III	M39012/55B†022	M39012/55B†018 M39012/55B†019 M39012/55B†020 M39012/55B†021 M39012/55B†022 M39012/55B†023 M39012/55B†024
IV	M39012/55-†028	M39012/55-†025 M39012/55-†026 M39012/55-†027 M39012/55-†028 M39012/55-†029
V	M39012/55-†502	M39012/55-†502

1/ Individual connectors other than listed are self qualifying only.
2/ Qualification of connectors qualifies connectors of the same material only.
3/ Connectors qualified with safety wire holes automatically qualifies connectors without safety wire holes.
† Denotes material.

NOTES:

1. For qualification retention, where more than one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right hand column. The part does not necessarily have to be the part initially qualified.

2. If a connector manufacturer produces a connector which meets all the requirements for two or more connector part numbers (within the same series), the manufacturer may receive qualification approval for two or more connector part numbers by qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate part number. For group qualification, the connectors must be of similar design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

TABLE V. Category B - Nonfield replaceable (special tools may be required).

Not for Air Force or Navy use. For OEM use only.

M39012/55B †	Applicable cable M17/ #	Dimensions	Inches (millimeters) maximum 1/2/5/6/
3011 7/ 3111 4/ 7/ 4011 7/ 4111 4/ 7/	M17/93-RG178 M17/169-00001ø		
3012 7/ 3112 4/ 7/ 4012 7/ 4112 4/ 7/	M17/119-RG174 M17/113-RG316 M17/173-00001ø M17/172-00001ø		
3013 7/ 3113 4/ 7/ 4013 7/ 4113 4/ 7/	M17/54-RG122* M17/157-00001ø	A	1.250(31.75)
3014 7/ 3114 4/ 7/ 4014 7/ 4114 4/ 7/	M17/28-RG058* M17/155-00001ø		
3015 7/ 3115 4/ 7/ 4015 7/ 4115 4/ 7/	M17/60-RG142*@ M17/158-00001ø		
3016 7/ 3116 4/ 7/ 4016 7/ 4116 4/ 7/	M17/84-RG223* M17/167-00001ø		
3017 7/ 3117 4/ 7/ 4017 7/ 4117 4/ 7/	M17/111-RG303* M17/170-00001ø		
3018 3/ 3118 4/ 3/ 4018 3/ 4118 4/ 3/	M17/93-RG178 M17/169-00001ø		
3019 3/ 3119 4/ 3/ 4019 3/ 4119 4/ 3/	M17/119-RG174 M17/173-00001ø M17/113-RG316 M17/172-00001ø		
3020 3/ 3120 4/3/ 4020 3/ 4120 4/3/	M17/54-RG122* M17/157-00001ø	A	1.375(34.93)
3021 3/ 3121 4/3/ 4021 3/ 4121 4/3/	M17/28-RG058* M17/155-00001ø		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

TABLE V. Category B - Nonfield replaceable (special tools may be required) - Continued.

Not for Air Force or Navy use. For OEM use only.

M39012/55B†	Applicable cable M17/ #	Dimensions	Inches (millimeters) maximum 1/2/5/6/
3022 3/	M17/60-RG142*@		
3122 4/3/	M17/158-00001ø		
4022 3/			
4122 4/3/			
3023 3/	M17/84-RG223*		
3123 4/3/	M17/167-00001ø	A	1.375 (34.93)
4023 3/			
4123 4/3/			
3024 3/	M17/111-RG303		
3124 4/3/	M17/170-00001ø		
4024 3/			
4124 4/3/			

1/ Millimeters are in parentheses.
2/ Coupling nuts shall be corrosion resistant steel with a passivated finish per MIL-F-14072. Existing qualified parts may be supplied until 25 July 1986. (applies only to "-3XXX" series connectors).
3/ These connectors have captivated center contacts.
4/ No safety wire holes.
5/ For logistics purposes, only connectors with safety wire holes will be stocked.
6/ All corrosion resistant steel bodied connectors which are designed to be assembled to the cable outer conductor using solder shall be gold plated per MIL-G-45204, Type II, Class I, existing qualified parts may be supplied until 25 July 1986.
7/ Inactive for new design.
The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in note @.
@ Cable to be used for the +200°C temperature cycling tests.
† Connectors mate with connectors of the same material; i.e., M39012/59-3001 mates with M39012/55-3001, and M39012/59-4001 mates with M39012/55-4001.
ø Caution is directed to the application of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

TABLE VI. Maintenance replacements for category B.

Category B dash number*	Category C dash number	Category A dash number	Category D dash number
B†011	025	006	---
B†012	026	007	---
B†013	027	008	---
B†014	029	009	---
B†015	028	009	502
B†016	028	009	---
B†017	029	010	---
B†018	025	006	---
B†019	026	007	---
B†020	027	008	---
B†021	029	009	---
B†022	028	009	502
B†023	028	009	---
B†024	029	010	---

*Category B connectors are for original installation only. They will not be stocked or procured by the Government.

The material of the item shall be the same material as the item being replaced. Example: 55B3011 (corrosion resistant steel) replaces 55-3025.

TABLE VII. Cross reference of part numbers.

M39012/55B 1/	M39012/55-
†011	†011
†111	†111
†012	†012
†112	†112
†013	†013
†113	†113
†014	†014
†114	†114
†015	†015
†115	†115
†016	†016
†116	†116
†017	†017
†117	†117
†018	†018
†118	†118
†019	†019
†119	†119
†020	†020
†120	†120
†021	†021
†121	†121
†022	†022
†122	†122
†023	†023
†123	†123
†024	†024
†124	†124

1/ The new "B" part numbers will be required marking 6 months after the date of this specification. The previous part numbers may be used in the interim.

† The material of the item shall be the same material as the item being replaced. Example: 55B3011 (corrosion resistant steel) replaces 55-3025.

Source: https://assist.dla.mil --Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11; 17, 99
DLA - ES

User activities:
Army - AM, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3518-17)

Source: https://assist.dla.mil Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.