PERFORMANCE SPECIFICATION

CONNECTORS, PLUGS, ELECTRICAL, COAXIAL, RADIO FREQUENCY
(SERIES SMA (CABLED) - PLUG, PIN CONTACT, CLASS 2)

This amendment forms a part of performance specification MIL-PRF-39012/55F, dated 27 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3 and 4

Delete and substitute the new table I as shown below:

"TABLE I. Dash numbers, cross reference and dimensions.

Dash number 1/ 2/ 3/	# Applicable cable group from MIL-PRF-39012, appendix B.	Dimensions	Inches(millimeters) maximum 4/
Category A - Field serviceable (no special tools required) 5/			
3006 3106 7/ 4006 4106 7/	CABLE GROUP I M17/93-RG178 10/ 17/	A	1.030 (26.16)
3007 3107 7/ 4007 4107 7/	CABLE GROUP II M17/113-RG316 10/ 17/		
3008 3108 7/ 4008 4108 7/	CABLE GROUP IV M17/54-RG122 10/ 17/		
3009 3109 7/ 4009 4109 7/	CABLE GROUP VI M17/60-RG142 11/ M17/128-RG400 17/ M17/84-RG223 10/		
3010 12/ 3110 7/ 12/ 4010 12/ 4110 7/ 12/	CABLE GROUP VI M17/111-RG303 10/ 17/		
3030 3130 7/ 4030 4130 7/	CABLE GROUP III M17/152-00001 10/ 17/		

DISTRIBUTION IS UNLIMITED. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference and dimensions. (continued)

Dash number 1/ 2/ 3/	# Applicable cable group from MIL-PRF-39012, appendix B.	Dimensions	Inches (millimeters) maximum 4/
Category C - Field serviceable (MIL-C-22520-01 crimp tool) 6/			
3025 3125 7/ 4025 4125 7/	CABLE GROUP I M17/93-RG178 10/ 13/ 17/	A	1.250 (31.75)
3026 3126 7/ 4026 4126 7/	CABLE GROUP IIa M17/113-RG316 10/ 14/ 17/		
3027 3127 7/ 4027 4127 7/	CABLE GROUP IV M17/54-RG122 10/ 15/ 17/		
3028 3128 7/ 4028 4128 7/	CABLE GROUP VIb M17/60-RG142 11/ M17/128-RG400 16/ 17/ M17/84-RG223 10/		
3029 3129 7/ 4029 4129 7/	CABLE GROUP VIa M17/111-RG303 16/ 17/ M17/28-RG058 10/		
Category D - Field replaceable - Defined piece parts 6/ 8/ 9 /			
3502 3602 7/ 4502 4602 7/	CABLE GROUP VIb M17/60-RG142 10/ 11/ M17/128-RG400 17/	A	1.250 (31.75)

1/ These connectors have captivated center contacts.
2/ For logistics purposes, only connectors with safety wire holes will be stocked.
3/ Coupling nuts shall be corrosion resistant steel with a passivated finish in accordance with MIL-F-14072 (applies only to "-3XXX series connectors).
4/ Millimeters are in parentheses.
5/ All corrosion resistant steel bodied connectors which are designed to be assembled to the cable outer conductor using solder shall be gold plated in accordance with MIL-G-45204, type II, class I.
6/ These connectors are assembled, using the applicable crimp tool, to the specified cables stripped as shown on figure 4.
7/ No safety wire holes.
8/ Complete connector assembly shall consist of a body, center contact, ferrule and assembly instructions.
9/ Not for use in Army equipment.
10/ Cable to be used when performing tests except as in note 11/.
11/ Cable to be used for the +200 degree C temperature cycling test. Connectors mate with connectors of the same material; i.e., "3XXX" series dash numbers mate only with other "3XXX" series connectors and "4XXX" series connectors with other "4XXX" series connectors.
12/ These parts are inactive for new design, new designs should procure to dash numbers -*009 and *109. These dash numbers use the same cable group. (VI).
13/ Preferred die M22520/5-33 closure B, alternate die M22520/5-03 closure B.
14/ Preferred die M22520/5-35 closure B, alternate die M22520/5-03 closure A.
15/ Preferred die M22520/5-41 closure B, alternate die M22520/5-05 closure B, or -09 closure A.
16/ Preferred die M22520/5-19 closure B, alternate die M22520/5-05 closure A, or -11, 57, closure A.
17/ Preferred cable.
The latest version of each cable shall be applicable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

PAGE 5

Delete and substitute the new table II as follows:

"Table II. Voltage rating.

Cables	Voltage max. (at sea level)	Voltage max. (70,000 ft.)
Cable group I	V rms 170	V rms 45
Cable group II, IIa, III, IV	250	65
Cable group VI, VIa, VIb	335	85

"

PAGE 8

Requirements, Voltage standing wave ratio, delete and substitute the following;

"Cable group	VSWR
I	1.20 + 0.025 (F) GHz
II, IIa, III, IV	1.15 + 0.02 (F) GHz
VI, VIa, VIb	1.15 + 0.01 (F) GHz"

PAGE 9

Dielectric withstanding voltage, delete and substitute the following;

"Cable group	V rms
I	500
II, IIa, III, IV	750
VI, VIa, VIb	1,000"

PAGE 10

Corona level, delete and substitute the following;

"Cable group	Volts min.
I	125
II, IIa, III, IV	190
VI, VIa, VIb	250"

RF high potential withstanding voltage, delete and substitute the following;

"Cable group	Volts min.
I	335
II, IIa, III, IV	500
VI, VIa, VIb	670"

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 11, 17, 99

Preparing activity:
DLA - ES

(Project 5935-4012-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:58Z
Check the source to verify that this is the current version before use.