PERFORMANCE SPECIFICATION

CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY
(SERIES SMA (CABLED) - SOCKET CONTACT, FLANGE MOUNTED, CLASS 2)

This amendment forms a part of performance specification MIL-PRF-39012/58F, dated 27 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3 and 4

Delete and substitute the new table I as shown below:

"TABLE I. Dash numbers, cross reference and dimensions.

Dash number 1/	# Applicable cable group from MIL-PRF-39012, appendix B.	Dimensions	Inches (millimeters) maximum 2/
Category A - Field serviceable (no special tools required) 3/			
3006 4006	CABLE GROUP I M17/93-RG178 7/ 14/	A	.960 (24.38)
3007 4007	CABLE GROUP II M17/113-RG316 7/ 14/		
3008 4008	CABLE GROUP IV M17/54-RG122 7/ 14/		
3009 4009	CABLE GROUP VI M17/60-RG142 8/ M17/128-RG400 14/ M17/84-RG223 7/		
3010 9/ 4010 9/	CABLE GROUP VI M17/111-RG303 7/ 14/		
3030 4030	CABLE GROUP III M17/152-00001 7/ 14/		

DISTRIBUTION IS UNLIMITED. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:59Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference and dimensions. (continued)

Dash number 1/	# Applicable cable group from MIL-PRF-39012, appendix B.	Dimensions	Inches (millimeters) maximum 2/
Category C - Field serviceable (MIL-C-22520-01 crimp tool) 4/			
3025 4025	CABLE GROUP I M17/93-RG178 7/ 10/ 14/	A	1.125 (28.58)
3026 4026	CABLE GROUP IIa M17/113-RG316 7/ 11/ 14/		
3027 4027	CABLE GROUP IV M17/54-RG122 7/ 12/ 14/		
3028 4028	CABLE GROUP VIb M17/60-RG142 8/ M17/128-RG400 13/ 14/ M17/84-RG223 7/		
3029 4029	CABLE GROUP VIa M17/111-RG303 13/ 14/ M17/28-RG058 7/		
Category D - Field replaceable - Defined piece parts 4/ 5/ 6/			
3502 4502	CABLE GROUP VIb M17/60-RG142 7/ 8/ M17/128-RG400 14/	A	1.125 (28.58)

1/ These connectors have captivated center contacts.
2/ Millimeters are in parentheses.
3/ All corrosion resistant steel bodied connectors which are designed to be assembled to the cable outer conductor using solder shall be gold plated in accordance with MIL-G-45204, type II, class I.
4/ These connectors are assembled, using the applicable crimp tool, to the specified cables stripped as shown on figure 4.
5/ Complete connector assembly shall consist of a body, center contact, ferrule and assembly instructions.
6/ Not for use in Army equipment.
7/ Cable to be used when performing tests except as in note 8/.
8/ Cable to be used for the +200 degree C temperature cycling test. Connectors mate with connectors of the same material; i.e., "3XXX" series dash numbers mate only with other "3XXX" series connectors and "4XXX" series connectors with other "4XXX" series connectors.
9/ These parts are inactive for new design, new designs should procure to dash numbers -*009 and *109. These dash numbers use the same cable group. (VI).
10/ Preferred die M22520/5-33 closure B, alternate die M22520/5-03 closure B.
11/ Preferred die M22520/5-35 closure B, alternate die M22520/5-03 closure A.
12/ Preferred die M22520/5-41 closure B, alternate die M22520/5-05 closure B, or -09 closure A.
13/ Preferred die M22520/5-19 closure B, alternate die M22520/5-05 closure A, or -11, 57, closure A.
14/ Preferred cable.
The latest version of each cable shall be applicable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:59Z
Check the source to verify that this is the current version before use.

PAGE 7

Delete and substitute the new table II as follows:

"Table II. Voltage rating.

Cables	Voltage max. (at sea level)	Voltage max. (70,000 ft.)
Cable group I	V rms 170	V rms 45
Cable group II, IIa, III, IV	250	65
Cable group VI, VIa, VIb	335	85

"

PAGE 8

Requirements, Voltage standing wave ratio, delete and substitute the following;

"Cable group	VSWR
I	1.20 + 0.025 (F) GHz
II, IIa, III, IV	1.15 + 0.02 (F) GHz
VI, VIa, VIb	1.15 + 0.01 (F) GHz"

PAGE 9

Dielectric withstanding voltage, delete and substitute the following;

"Cable group	V rms
I	500
II, IIa, III, IV	750
VI, VIa, VIb	1,000"

PAGE 10

Corona level, delete and substitute the following;

"Cable group	Volts min.
I	125
II, IIa, III, IV	190
VI, VIa, VIb	250"

RF high potential withstanding voltage, delete and substitute the following;

"Cable group	Volts min.
I	335
II, IIa, III, IV	500
VI, VIa, VIb	670"

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:59Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 11, 17, 99

Preparing activity:
DLA - ES

(Project 5935-4012-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:59Z
Check the source to verify that this is the current version before use.