INCH-POUND


MIL-PRF-39012/61D
w/AMENDMENT 3
17 November 2023
SUPERSEDING
MIL-PRF-39012/61D
w/AMENDMENT 2
27 June 2021

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (UNCABLED, SOCKET CONTACT, JAM NUT MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.




REAR MOUNT (M39012/61-3001 AND M39012/61-4001)

FIGURE 1. General configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:01Z
Check the source to verify that this is the current version before use.



FRONT MOUNT (M39012/61-3002 AND M39012/61-4002)

NOTES:

1. Dimensions are in inches.
2. Dimension .505 inch is the largest overall diameter of the connector.
3. All undimensioned pictorial configurations are for reference purposes only.
4. There shall be a solid barrier in the socket between the pin entry and the solder pocket to prevent solder wicking.
5. Solder pockets shall be gold plated in accordance with MIL-DTL-45204, type II, grade C, class1.
6. Series SMA, socket contact interface shall be in accordance with MIL-STD-348.

FIGURE 1. General configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:01Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.
Frequency range: Not rated.
Voltage rating: 335 volts rms maximum at sea level, 85 volts rms maximum at 70,000 feet.
Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.
Force to engage and disengage:
Longitudinal force: Not applicable.
Torque: 2 inch-pounds, maximum.
Coupling proof torque: Not applicable.

Inspection conditions: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Mating characteristics: See MIL-STD-348 and figure 2 for dimensions.
Contacts with spring members:
Center contact (female):
Oversize test pin: .0375 +.0001/-.0000 inch.
Test pin finish: 16 microinches.
Insertion depth: .030/.045 inch.
Number of insertions: 3.
Insertion force test:
Steel test pin diameter: .0370 +.0001/-.0000 inch.
Insertion depth: .050/.075 inch.
Test pin finish: 16 microinches.
Insertion force: 2 pounds, maximum.
Withdrawal force test:
Steel test pin diameter: .0355 +.0000/-.00001 inch.
Insertion depth: .050/.075 inch.
Test pin finish: 16 microinches.
Withdrawal force: 1 ounce, minimum.




FIGURE 2. Test pin data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:01Z
Check the source to verify that this is the current version before use.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Connectors shall be mounted in mounting hole shown on figure 1 with mating end capped. Test applicable to mounting seal only.

Air pressure: 30 psi.
Duration: 30 seconds minimum, 2 minutes maximum.

Insulation resistance: In accordance with EIA - 364-21, 5,000 megohms minimum.
Center contact retention:
Axial force: 6.0 pounds minimum.
Radial torque: 4 inch-ounces minimum.

Solderability: In accordance with MIL-STD-202-208 (for quality conformance inspection, the test shall be performed in group B following the insulation resistance test.)

Resistance to test probe damage: Not applicable.
Corrosion (salt spray): In accordance with EIA - 364-26, test condition B.
Voltage standing wave ratio (VSWR): Not applicable.

Connector durability: In accordance with EIA - 364-09, 500 cycles minimum at 12 cycles per minute maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact:	3.0	4.0
Outer contact:	2.0	Not applicable

Dielectric withstanding voltage at sea level: In accordance with EIA- 364-20,1,000 volts rms, minimum.
Vibration, high frequency: In accordance with EIA - 364-28, test condition IV.
Shock: In accordance with EIA - 364-27, condition G.
Thermal shock: In accordance with test procedure EIA - 364-32, Method A, condition VI, test duration A (5 cycles).

Humidity: In accordance with EIA - 364-31. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:
Voltage: 250 volts minimum.
Altitude: 70,000 feet.

RF high potential withstanding voltage:
Voltage and frequency: 670 volts rms at 5 MHz.
Leakage current: Not applicable.

Cable retention force: Not applicable.
Coupling mechanism retention force: Not applicable.
RF leakage: Not applicable.
RF insertion loss: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:01Z
Check the source to verify that this is the current version before use.

Group qualification: See table I.

TABLE I. Group qualification and retention testing.

Group	PINs 1/ 2/
I	M39012/60-3001 M39012/60-3002 M39012/61-3001 M39012/61-3002
II	M39012/60-4001 M39012/60-4002 M39012/61-4001 M39012/61-4002

1/ Submission and qualification of any connector in a group qualifies any and all connectors of the entire group.

2/ For qualification retention, data may be supplied on any part in a group to retain qualification for that entire group.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-39012, this document references the following documents:

MIL-STD-202-208	EIA - 364-09	EIA - 364-27
MIL-STD-348	EIA - 364-20	EIA - 364-28
MIL-DTL-45204	EIA - 364-21	EIA - 364-31
	EIA - 364-26	EIA - 364-32

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2023-089)

Review activities:
Army - AM, AT, CR4
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:01Z
Check the source to verify that this is the current version before use.