MILITARY SPECIFICATION

CATSUP, TOMATO, DEHYDRATED, FOR MEAL, READY-TO-EAT

This specification is approved for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This document covers dehydrated tomato catsup in flexible envelopes for use as a component of the meal, ready-to-eat, individual.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein:

STANDARDS

FEDERAL

FED-STD-101 - Preservation, Packaging and Packing Materials: Test Procedures

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

MUNSELL COLOR COMPANY, INC.

Munsell Color Discs

(Munsell Color Discs may be obtained from the Munsell Color Company, Inc., Baltimore, MD 21233.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Freight Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION

Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, 251 Kearney Street, #410, San Francisco, CA 94108.)

(Technical society and technical association documents are generally available fo reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.2).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free fro foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Tomato powder. Tomato powder shall show no evidence of heat damage, shall be practically free from skins and seeds (may contain skins and seeds in a quantity which no more than slightly affects the appearance of the product), and shall be such particle size that 95 percent of the material shall pass through a U.S. Standard No. 20 sieve (0.033-inch openings). It shall be free flowing, contain not more than 4.0 percent moisture, and not more than 450 parts per million (ppm) of sulfur dioxide. It shall rehydrate within 3 minutes without undue agglomeration when 4.5 ounces of powder are added to 12 fluid ounces of cold water (approximately 40°F). The rehydrated product shall possess a color which contains as much or more red than that produced by spinning the specified Munsell Color Discs in the following combinations: 59 percent of the area of red (5R 2.6/13 - glossy finish), 24-1/2 percent of the area of yellow (2.5 YR 5/12 - glossy finish) and 16-1/2 percent of either black (N1 - glossy finish) or grey (N4 - mat finish), or any combination of the two. Color comparisions shall be performed as directed in 4.6.3. (NOTE: If tomato flakes are used which are of larger granulation than above, they may be mixed with the sugar components and ground in a Fitz mill (or similar suitable machine) to reduce the particle size to the required limit. Care must be taken to avoid overheating and agglomeration of the product).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

3.2.2 Sugar. Sugar shall be white, refined, granulated cane or beet sugar, or a combination of both.

3.2.3 Salt. Salt shall be non-iodized, white, refined, sodium chloride with or without anticaking agents.

3.2.4 Spices, ground. Spices shall be uniformly ground, be typical of their varieties, and shall have color, taste, and pungency typical of the product.

3.2.5 Garlic powder. Garlic powder shall meet the requirements for fancy grade garlic powder of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic Products.

3.2.6 Citric acid. Citric acid shall conform to the Food Chemicals Codex.

3.2.7 Onion powder. Onion powder shall meet the requirements for fancy grade onion powder of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic Products.

3.2.8 Starch, pregelatinized. Starch shall be a pregelatinized type.

3.2.9 Sodium diacetate. Sodium diacetate is the bound compound of sodium acetate and acetic acid and shall conform to the Food Chemicals Codex.

3.2.10 Anticaking agent. Anticaking agent shall be silicon dioxide. (Syloid No. 244 has been found effective in assuring desired anticaking properties).

3.3 Preparation and processing.

3.3.1 Tomato catsup mix preparation. The tomato catsup mix shall be prepared according to the following formula:

Ingredients	Percent (based on total weight)
Tomato powder	44.00
Sugar	39.00
Salt	8.40
Onion powder	3.91
Anticaking agent	2.00
Starch, pregelatinized	1.00
Citric, acid	1.00
Sodium diacetate	0.50
Cinnamon, ground	0.05
Cloves, ground	0.05
Garlic powder	0.03
Red pepper, ground	0.03
Allspice, ground	0.03

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

NOTE: The ingredients, other than the tomato powder or the tomato powder and sugar mixture, shall be screened and mixed before incorporating the tomato powder or the tomato powder and sugar mixture.

* 3.3.2 Pouch filling. Each pouch shall be filled with catsup such as to conform to the following requirements:

a. Average net weight shall be 7.0 grams minimum.
b. No individual pouch shall contain less than 6.7 grams of catsup mix.

3.4 Finished product. The finished product shall be uniformly blended, free from rancid, musty, and other undesirable flavors or odors, and shall be free flowing. Desiccation of the dry mix with calcium oxide desiccant is required before final packaging.

3.4.1 Moisture content. The moisture content of the finished packaged product shall not exceed 2.0 percent.

3.4.2 Palatability. The product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.5 Plant qualification. The product shall be prepared, processed and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsiblity to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

* 4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shallbe cause for rejection of the first article

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Tomato powder examination. The tomato powder shall be examined for the defects listed in table I. The lot size shall be expressed in units of one primary container. The sample unit shall be 1 pound of tomato powder taken from a primary container. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Tomato powder defects 1/

Category	Defect
Major	
151	Heat damage
152	More than a trace of extraneous vegatable matter or skin and seeds
153	Less than 95 percent passes through a U.S. Standard No. 20 sieve (see 4.6.4)
154	Not free flowing
155	Does not rehydrate without undue agglomeration within 3 minutes after 4.5 ounces of the powder are added to 12 fluid ounces of cold water (approximately 40°F)

1/ The presence of any foreign material (e.g., glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

4.5.1.2 Other ingredients examination. Conformance of ingredients to identity and condition requirements shall be determined by examinatio of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any non-conformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

4.5.1.3 Component testing. The tomato powder and envelopes shall be tested as indicated in table II. Results shall apply to the lot average. Nonconformance to test requirement shall indicate an unacceptable component and use of such shall be cause for rejection of the involved end item.

TABLE II. Component tests

Component	Sample unit	Lot size expressed in	Inspection level	Characteristic	Results reported	Test ref and rqmt para
Tomato powder	1/	Primary containers	S-2	Moisture	Nearest 0.1 percent	3.2.1 4.6.1
				Sulfur dioxide	Nearest ppm	3.2.1 4.6.2
1				Color	Pass or fail	3.2.1 4.6.3
Envelope	1-yard strip from a roll or equivalent in envelopes	Envelopes	S-1	Basis weight of paper 2/	Nearest lb/ream	4.6.5 5.1
				Thickness of 2/:		
				Polyethylene	Nearest 0.0001 inch	5.1
				Aluminum foil	Nearest 0.00001 inch	5.1

1/ The sample shall be a 1-pound composite derived from the number of primary containers indicated by the inspection level.

2/ In lieu of performing tests for basis weight of paper and thickness, conformance to requirements may be ascertained by examination of labels, invoices, or other valid documents.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to preparation and processing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or other valid documents shall be cause for rejection of the involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

4.5.3 Net weight inspection. The net weight of the filled and sealed envelopes shall be determined by weighing each sample unit on a suitable scale tared with an average weight of representative empty envelopes. Any individual net weight of less than 6.7 grams shall be scored as a minor defect. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5. The results shall be reported to the nearest 0.1 gram. In addition, the lot shall be rejected if the sample average net weight is less than 7.0 grams.

* 4.5.4 Envelope external examination. The filled and sealed envelopes shall be examined for the defects listed in table III. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

TABLE III. Envelope external defects 1/

Category		Defect
Major	Minor	
151		Any opening in the envelope; e.g., tear, hole, open seam, or sifter 2/
152		Not type, color, or size (length, width, or thickness) specified
153		Crushed or misshaped, resulting in two or more creases in product area of the envelope
154		Foreign odor
155		Nomenclature or instructions missing, incorrect or illegible
156		Any seal width less than 1/8 inch
	201	Not clean
	202	Labeling information other than nomenclature missing, incorrect, or illegible
	203	Labeling method not as specified

1/ Any evidence of insect or rodent infestation shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

2/ A sifter is an envelope which loses any amount of dehydrated tomato catsup when shaken vigorously.

* 4.5.5 Envelope leakage, delamination and seal separation testing. The filled an sealed envelopes shall be tested by placing them in a dry desiccator, or similar apparatus, and subjecting them to a vacuum of 26 inches of mercury (atmospheric pressure is 29.9 inches of mercury) for 30 seconds. Any envelope that does not swell to a tightly distended form having at least one distorted edge while under th vacuum shall be counted as a major defect. After leakage testing, the envelopes shall be visually inspected for evidence of delamination and for seal separation. Any delamination or any seal separation of more than 1/16 inch from the product edg of any seal shall be counted as a major defect. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspectio level shall be I, except that the sample size shall be not less than 200 sample units. The AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.5.6 Product examination. The product shall be examined for the defects listed i table IV. The lot size shall be expressed in envelopes. The sample unit shall be the contents of one filled and sealed envelope. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE IV. Product defects 1/ 2/

Category	Defect
Major	Dehydrated product
151	Not uniformly blended
152	Not free flowing
	Reconstituted product 3/
153	Not typical catsup flavor or aroma
154	Burnt, off-flavor or aroma
155	Not smooth, uniform texture and consistency typical of commercial catsup

1/ Presence of any foreign material (e.g., glass, dirt, insect part, hair, wood, metal, etc.) foreign odor or flavor (e.g., burnt, scorched, stale, sour, rancid, musty, moldy, etc.), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability or overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

3/ Reconstitute in accordance with label instructions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

4.5.7 Product moisture testing. The product shall be tested for conformance to the moisture content requirement in 3.4.1 in accordance with the Moisture in Dried Fruits methods in the Fruit and Fruit Products chapter of the Official Methods of Analysis of the Association of Official Analytical Chemists except that the drying time shall be 16 hours at 60°C in the vacuum oven and the pressure shall not exceed 50 mm of mercury. The results shall be reported to the nearest 0.1 percent. A test result exceeding 2.0 percent shall be cause for rejection of the lot.

4.5.8 Shipping container examination. Examination of the filled and closed shipping container shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable. In addition, the following shall be included in the examination: Minor: (1) Marking missing, incorrect, or illegible. (2) Net weight not marked on container.

4.5.9 Shipping container content examination. The number of envelopes in the shipping containers shall be examined for conformance to the number marked on the shipping container. Any shipping container containing more than 2 percent under the marked quantity shall be classified as a defect. The lot size shall be expressed in shipping containers and the sample unit shall be one shipping container. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0. If the sample average count per container is less than the marked quantity, the lot shall be rejected. If there are more than 1000 envelopes per shipping container, the count may be determined by a weight/count relationship.

4.6 Methods of inspection.

4.6.1 Moisture content test. The moisture content test shall be performed in accordance with the Moisture in Dried Fruits method in the Fruit and Fruit Products chapter of the Official Methods of Analysis of the Association of Official Analytical Chemists.

4.6.2 Sulfur dioxide content test. The sulfur dioxide content test shall be performed in accordance with the Total Sulfurous Acid method in Chemical Preservatives section of the Food Additives: Direct chapter of the Official Methods of Analysis of the Association of Official Analytical Chemists.

4.6.3 Color comparison for rehydrated tomato powder. Color comparison shall be made under a diffused light source of approximately 250 foot candle intensity and having a spectral quality approximately that of daylight under a moderately overcast sky, and color temperature of 7500 $\pm$ 200 kelvins. With the light source directly over the disc and product, observation shall be made at an angle of 45 degrees from a distance of about 24 inches from the product. In the event such light source is not available, north daylight, between the hours of 10:00 a.m. and 4:00 p.m. may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

4.6.4 Particle size. One hundred grams of tomato powder shall be screened through a U.S. Standard No. 20 sieve (0.033 inch openings) equipped with a tight-fitting cover and catch pan. Place a 100 g sample on the sieve. With the left hai hold the sieve assembly at an angle of about 30° from the horizontal so that the upper edge of the tilted plane is towards the right hand. Shake by striking the right side of the sieve assembly with a short, stroke with the right hand moving ir a horizontal plane. Strike at the rate of about 150 times per minute. After each 25 strokes turn the sieve assembly 1/6 of a revolution in the same direction. Continue shaking for 2 minutes. Equivalent machine methods may be substituted for manual sieving. Care shall be exercised to keep moisture absorption by the tomato powder to a minimum.

4.6.5 Basis weight of paper. Paper shall be tested for basis weight in accordance with Method 5022 of FED-STD-101.

5. PACKAGING

5.1 Preservation, level A. (Envelopes for operational rations). Seven grams of dehydrated tomato catsup shall be unit packed in a four seal style envelope fabricated and closed by heat sealing. Each seal shall be a minimum 1/8 inch wide. The envelope material shall be made by hot extruding or laminating 0.0015 inch thick polyethylene on a 0.00035 inch thick aluminum foil and laminating the plain side of the foil to Kraft paper having a basis weight of 25 to 35 pounds per ream (24 x 36 - 500). The envelope exterior color shall be natural Kraft. The filled and sealed envelope shall be not more than 3 inches long by 2-5/8 inches wid by 1/4 inch thick and shall not leak, show evidence of delamination or have seal separation of more than 1/16 inch from the product edge of any seal when tested in accordance with 4.5.5.

5.2 Packing, level C. (Envelopes for shipment to ration assembler). Not more than 40 pounds of catsup, unit packed as specified in 5.1, shall be random packed into fiberboard containers in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Labeling and marking.

5.3.1 Seven gram envelopes. The envelopes shall be printed in black boldface type with an indelible ink. The envelopes shall contain the following information:

Catsup, Dehydrated

7 grams

Use Dry or Reconstitute In Envelope

By Adding 2 Teaspoonfuls of Water

(Name and Address of Producer)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

5.3.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129 and shall include the number of envelopes contained therein.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.2).
c. Provisions for approved preproduction samples (see 3.4.2 and 6.2).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article shall be a preproduction sample. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for selection, inspection, and approval of the first article.

6.3 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8950-0301

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
JS Army Natick Research and Development Laboratories
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44075A	Catsup, Tomato, Dehydrated, For Meal, Ready-To-Eat

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

NATICK/OP/ 1 APR 83

Source: https://assist.dla.mil - Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.