MIL-C-44080
30 March 1982

MILITARY SPECIFICATION

CONTAINER, SHIPPING, MULTIPURPOSE, CANINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a canine, multipurpose, shipping container (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3770

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:46Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

5-13-2866	-	Shipping Container, Canine, Multipurpose
5-13-2867	-	Base Assembly
5-13-2868	-	Pan
5-13-2869	-	Reinforcement, Pan
5-13-2870	-	Angles
5-13-2871	-	Leg
5-13-2872	-	Fastener
5-13-2873	-	Latch
5-13-2874	-	Bracket
5-13-2875	-	Side Panel Assembly
5-13-2876	-	Frame Panel Assembly
5-13-2877	-	Vent Panel
5-13-2878	-	Latch
5-13-2879	-	Spacer
5-13-2880	-	Washer
5-13-2881	-	End Panel Assembly
5-13-2882	-	End Frame Assembly
5-13-2883	-	Door Assembly
5-13-2884	-	Hinge
5-13-2885	-	Pan Feeding
5-13-2886	-	Door
5-13-2887	-	Retainer, Sliding Door
5-13-2888	-	Sliding Door
5-13-2889	-	Spacer
5-13-2890	-	Shelf, Feeding Pan Assembly
5-13-2891	-	Roof Assembly

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN WELDING SOCIETY

Standard Qualification Procedure of the American Welding Society

(Application for copies should be addressed to American Welding Society, 2501 Northwest 7th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:46Z
Check the source to verify that this is the currenversion before use.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS

Welding Qualifications of American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 42nd Street, New York, NY 10017.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Alternate components. Components offered as equivalent to components specified herein and on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal, of equal or better quality with the manufacturer's part number identified. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.2 First article. When specified, the contractor shall furnish a sample for first article inspection (see 4.3, 6.2 and 6.3).

3.3 Materials and components. Materials and components shall be as specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all provisions of this document (see 6.4).

3.4 Design and construction. The design and construction of the containers shall be as specified herein and as shown on the drawings referenced in 2.1. All component parts of any one container shall be so fabricated as to be interchangeable with the like parts of any other unit furnished under any one contract.

3.4.1 Water tight integrity of the container base channel. The maximum allowable water loss for the container base channel shall be 10 cc's per hour, when tested as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:46Z
Check the source to verify that this is the current version before use.

3.4.2 Static load test. The container assembly shall withstand a 400 pound static load test and there shall be no indication of failure or permanent distortion to any part of the container, when tested as specified in 4.5.2.

3.5 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.2.1).

3.6 Marking. Marking for identification shall be permanent and legible and indicate:

Contract number
Contractor's name
Date of manufacturer
National stock number
Item description

3.7 Workmanship. The containers shall be free from fractures, splits, tears, dents, creases, deteriorations or malfunctions. There shall be no sharp edges, burrs or slivers. All bolts, studs, nuts, and screws shall be drawn tight.

3.7.1 Welders. Unless otherwise specified (see 6.2), before assigning any welder to work, the contractor shall provide the Government inspection service with the names of the welders to be employed in the work, together with certification that each of the welders has passed a qualification test as prescribed by either of the following listed codes for the type of welding operation to be performed, and that such qualification is effective as defined by that particular code as follows:

(a) Standard Qualification Procedure of the American Welding Society.
(b) Welding Qualification of the American Society of Mechanical Engineers.

3.7.2 Welding. The surface of parts to be welded shall be free from oxide, scale, paint, grease and other foreign matter. Welds shall be sound, continuous, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits (when flux is used) shall be removed from the finished welds.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20260-21T23:46Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.2), the container shall be examined as specified in 4.4.2.1 and 4.4.2.2 and tested as specified in 4.5.2. The presence of any defects or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase document.

4.4.2 End item inspection. The inspection lot shall be all containers offered for inspection at one time. The sample unit shall be one complete assembled container.

4.4.2.1 Visual examination. The end item shall be examined for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Visual examination

Examine	Defect	Classification Major	Classification Minor
Finish	Type of finish not as specified		X
Design, construction and workmanship, general (applicable to all components and assemblies)	Any component part missing or not specified type or size	X	
	Fractured, split, punctured, torn, dented, creased, deteriorated or malformed	X	
	Component misplaced, or not in proper alignment	X	
	Component loose		X
	Sharp burr or edge or sliver		X
	Any operation omitted or not properly performed	X	
	Any functioning component that is inoperative or will not operate as intended	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:46Z
Check the source to verify that this is the current version before use.

TABLE I. Visual examination (cont'd)

Examine	Defect	Classification Major	Minor
Design, construction and workmanship, general (applicable to all components and assemblies) (cont'd)	Any functioning component that requires abnormal force to operate or not interchangeable	X	
	Any assembly not properly adjusted		X
	Any component not readily accessible for servicing where required		X
Welding	Missing, incomplete, cracked, fractured, not fused	X	
	Undercut, not smooth and uniform or scale or flux deposits not removed		X
Soldering (when applicable)	Missing, not adherent or incomplete		X
	Not clean (flux residue not removed, pinholes in solder)		X
Bolts, nuts, screws, studs and other types of threaded fasteners	Broken, stripped, fractured or not tight		X
Rivets (when required)	Broken, not peened or insufficiently peened or loose	X	
Marking	Missing, incomplete, not legible, not as specified	X	

4.4.2.2 Dimensional examination. The end item shall be examined for conformance to the specified dimensions. Any dimension deviating from the specified dimension shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

4.4.2.3 End item testing. Each end item shall be tested as specified in 4.5.1. Failure to pass the test shall be cause to reject the affected end item.

Source: https://assist.dla.mil -- Downloaded: 20260-21T23:46Z
Check the source to verify that this is the current version before use.

4.4.3 Examination for palletization. An examination shall be made to determine that palletization requirements of section 5 are complied with. The sample unit shall be one palletized unit load fully packaged. The lot shall be the number of palletized unit loads in the end item inspection lot. The inspection lot shall be S-1 and the AQL, expressed in terms of defects per hundred units shall be 6.5.

TABLE II. Examination of palletization

Examine	Defect
Finished dimensions	Length, width, or height exceeding specified maximum requirements
Palletization	Container pattern not as specified Load not bonded with straps as specified

4.5 Methods of inspection.

4.5.1 Water integrity test, container base channel. Place the container base on its legs, on a level surface and fill the drain channel with water. Any nonconformance with the water loss requirements of 3.4.1 shall constitute failure of the test.

4.5.2 Static load test. Place an equally distributed 400 pound load inside the container and on the base. Remove the load and inspect the container to determine compliance with 3.4.2. Any nonconformance with the requirements of 3.4.2 shall constitute failure of this test. Repeat the procedure for each of the side panels, end panels and roof with the doors closed and latched during the test. The container may be turned so that the side being tested is parallel to the ground and the base, sides and roof are to be supported only at the corners during the test.

5. PACKAGING

5.1 Packing. The canine container shall be knocked down and secured as shown on Drawing 5-13-2866.

5.2 Palletization. Canine container, prepared as specified in 5.1 shall be inverted and stacked five (5) containers high. Containers shall be palletized in accordance with load type VIII of MIL-STD-147. A fiberboard cap, storage aid 4, shall be used over and under each palletized load in lieu of wooden double tray cap. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L.

5.3 Marking. In addition to any special marking required by the contract or purchase order, palletized unit loads shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:46Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The container is intended to be used for transporting military dogs and other animals of similar size, as temporary housing, and as secure confinement for quarantining rabies suspect animals of similar size.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this document.
(b) When a first article is required (see 3.2, 4.3 and 6.3).
(c) Contract data requirements (see 3.5 and 6.2.1).

6.2.1 Contract data requirements. Any data item to be delivered under any contract for items should be specifically called for in the contract in accordance with the applicable regulation of the acquisitioning activity (see 3.5 and 6.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one container. The contracting officer should include instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

Custodians:

Army - GL
Navy - MC
Air Force - 99

Preparing activity:

Army - GL

Project No. 3770-0122

Review activities:

Army - MD
Navy - MS
DLA - CS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-44080 Container, Shipping, Multipurpose, Canine

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:46Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Command
ATTN: DRDNA-ES
Natick, MA. 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:46Z
Check the source to verify that this is the current version before use.