INCH-POUND
MIL-DTL-44076B
31 July 2006
SUPERSEDING
MIL-L-44076A
30 July 1990

DETAIL SPECIFICATION

LOWERING LINE ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirement for one type of lowering line with or without an adapter web.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are cited in other sections 3, 4, and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Drawings. The following other Government drawing forms a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

DRAWINGS

NATICK SOLDIER CENTER

11-1-2530 - Lowering Line Assembly

Comments, suggestions, or questions on this document should be addressed to Natick Soldier Center, ATTN: AMSRD-NSC-AD-AD, J. Riley, Natick, MA 01760-5017 or emailed to john.riley@natick.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil

AMSC N/A FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

(Copies of these documents are available from the Natick Soldier Center, ATTN: AMSRD-NSC-AD-AD (DRAWING REQUEST), Natick, MA 01760-5017.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First Article. When specified (see 6.2), a sample shall be subjected to a first article inspection in accordance with 4.2.

3.2 Materials. Materials shall conform to the requirements of the applicable Technical Data Package (TDP), to subsidiary specifications and standards applicable thereto and as specified herein.

3.2.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational requirements, and promotes economically advantageous life cycle costs.

3.3 Construction. Details of construction shall be in accordance with the TDP and the additional requirements as specified herein.

3.3.1 Stitch patterns. Automatic machine stitch patterns providing strength equal to the patterns specified on Drawing 11-1-2530 which conform to the overall dimensions, and which do not adversely affect form, fit, and function of the end item may be used in lieu of those specified, upon approval of the contracting officer. The contractor may be required to provide proof of equivalency.

3.4 Workmanship. The end item shall conform to the quantity of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. First article inspection shall be performed on one complete lowering line assembly, when a first article sample is specified (see 3.1). This inspection shall include the tests and examinations of 4.3.1, 4.3.2, 4.4, and 4.5. Any defect or nonconformance shall be cause for rejection of the first article.

4.3 Conformance inspection. Conformance inspections shall include the examinations of 4.3.1, 4.3.2, 4.4, and 4.5. Sampling plans and acceptance/rejection criteria for 4.4 and 4.5 shall be as specified in the contract or purchase order. Lowering line assemblies which fail the acceptance criteria shall be cause for rejection of the lot.

4.3.1 Component and material inspection. Components and materials shall be inspected in accordance with all of the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details and dimensional requirements, which cannot be examined in the finished product, are in accordance with specified requirements. The Government reserves the right to exclude from consideration of acceptance any material or service for which in-process inspection has indicated nonconformance.

4.4 End item visual examination. The end items shall be examined for the defects listed in TABLE I. Any nonconformance to the TDP shall be classified as a defect.

TABLE I. End item visual defects.

Examine	Defect	Classification Major	Minor
Material	Wrong Color		201
Webbing	Not specified type or class	101	
	Cut, tear, hole, abrasion, or weak area	102	
	Edges not seared as specified		202
Metal components	Fractured, malformed, or bent	103	
	Burrs or sharp edges	104	
	Protective finish omitted or not as specified, any corroded area	105	
Thread	Not type, class, or size specified	106	
	Not specified color		203
Stitches and stitching	Stitching pattern not as specified	107	
	Any row of stitching missing	108	
	One or more stitches per inch under or over		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
	minimum and maximum specified		204
	Two or more stitches per inch under or over minimum and maximum specified	109	
	Thread breaks, bobbin runouts, or runoff stitches, not overstitched or restitched as specified		205
	Ends of stitching not backstitched or secured as specified		206
	Tension loose resulting in loose top or bottom thread, or tight tension causing puckering of material at stitch line	110	
	Needle chews or bunched stitching	111	
Construction and assembly	Any component missing, or not assembled or joined as specified	112	
Marking	Omitted; incorrect; illegible; wrong location, size, or color		207
Workmanship	Grease, oil, ink smears, dirt, or other foreign matter; thread ends not trimmed throughout		208

4.5 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified in the TDP for the associated item. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.

(This section contains information of a general explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Lowering line assemblies are used as the standard method of lowering all individual parachutist's equipment loads when jumping with personnel parachutes.

6.2 Acquisition requirements. Acquisition document should specify the following:

a. Title, number and date of this specification.
b. When a first article is required (see 3.1 and 4.2).
c. Sampling plan (see 4.3).
d. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

Equipment loads
Parachutists

Custodians:
Army – GL2
Navy – AS

Preparing activity:
Army – GL2

(Project No. 1670-2005-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:44Z
Check the source to verify that this is the current version before use.