MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

RELAYS

TO ALL HOLDERS OF DOD-STD-35-8B(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-8B(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	30 JUNE 1992		26 SEPTEMBER 1986
1	26 SEPTEMBER 1986	(Reprinted without change)	
2	30 JUNE 1992	2	26 SEPTEMBER 1986
3	30 JUNE 1992	3	26 SEPTEMBER 1986
4	30 JUNE 1992	4	26 SEPTEMBER 1986
5	30 JUNE 1992	5	26 SEPTEMBER 1986
6	30 JUNE 1992	6	26 SEPTEMBER 1986
7	30 JUNE 1992	7	26 SEPTEMBER 1986
8	20 FEBRUARY 1979	(Reprinted without change)	
9	20 FEBRUARY 1979	(Reprinted without change)	
10	30 JUNE 1992	10	20 FEBRUARY 1979
11	30 JUNE 1992	11	26 SEPTEMBER 1986
12	20 FEBRUARY 1979	(Reprinted without change)	
301	20 FEBRUARY 1979	(Reprinted without change)	
302	30 JUNE 1992	302	20 FEBRUARY 1979
303	30 JUNE 1992	303	20 FEBRUARY 1979
304	20 FEBRUARY 1979	(Reprinted without change)	

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

3. Holders of DOD-STD-35-8B(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

User activity:
Army-AR

Review activities:
Winy-AT
Army-AV
Army-ER
Army-ME
Army-MR
Army-SC
Army-CR

Preparing activity:
Army - MI

(Project EGDS-A396)

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	REFERENCED DOCUMENTS	6
	2.1	Government Documents	6
	2.1.1	Specifications and Standards	6
	2.2	Other Publications	7
	2.3	Order of Precedence	7
	3.	DEFINITIONS	8
	4.	GENERAL REQUIREMENTS	9
	4.1	Introduction	9
	4.2	Specification Requirement Sheet (SRS)	9
	4.3	Configuration	9
	4.3.1	Dimensions	9
	4.3.2	Illustrations	9
	4.4	Units of measure	9
	5	DETAILED REQUIREMENTS	10
	5.1	Introduction	10
	5.2	MSE Formats	10
	5.3	Referenced documents	10
	5.4	Deleted	10
	5.5	Tabulation	12
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	13
	5.6.1	Interrelationship of Codes	13
	5.6.2	Automatic MSE Data	13
	5.6.3	DOD-STD-35 Tables	13

TABLES

Table	I.	Title Index	2
	II.	Deleted	11
	III.	Tabulation Candidates	12

APPENDICES

Appendix	A.	Illustrations	309
	B.	Characteristic Code Index	387
		Index	399

Source: https://assist.dla.mil - Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Relays.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE°s for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on a SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user°s reference. When more than one document is listed for an MSE title, this information will be found usefull in determining which of the documents is most suitable for use as the base document.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
RELAY	022500	MIL-R-2033	NAVAL SHIPBOARD
		MIL-R-5757	FOR ELECTRONIC AND COMM EQUIPMENT
		MIL-R-6106	AEROSPACE, GENERAL SPECIFICATION
		MS21330	12AMP, 3PST
		MS24140	50AMP, 1PST
		MS24141	100AMP, 1PST
		MS24142	200AMP, 1PST
		MS24143	25AMP, 3PST
		MS24149	10AMP, 2PDT
		MS24166	50AMP, 1PST
		MS24168	100AMP, 3PST
		MS24171	200AMP, 1PST
		MS24172	200AMP, 1PST
		MS24178	55AMP, 2PST
		MS24179	400AMP, 1PST
		MS24182	100AMP, 1PST
		MS24183	200AMP, 1PST
		MS24184	300AMP, 1PST
		MS24185	400AMP, 1PST
		MS24187	50/25AMP, 1PST
		MS24192	25AMP, 3PST
		MS24193	50AMP, 3PST
		MS24376	50AMP, 3PST
		MS24568	10AMP, 4PDT
		MS25030	50AMP, 2PDT
		MS25031	100AMP, 2PDT
		MS25032	200AMP, 2PDT
		MS25035	25AMP, 1PST
		MS25267	5AMP, 4PDT
		MS25268	5AMP, 4PDT

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
RELAY (CONT)	022500 (CONT)	MS25269	5AMP, 6PDT
		MS25270	5AMP, 6PDT
		MS25271	10AMP, 4PDT
		MS25272	10AMP, 4PDT
		MS25273	10AMP, 2PDT
		MS25327	10AMP, 4PDT
		MS25329	5AMP, 6PDT
		MS25395	5AMP, 2PDT
		MS25457	10AMP, 2PDT
		MS25459	5AMP, 4PDT
		MS25463	5AMP, 6PDT
		MS25467	5AMP, 4PDT
		MS25468	10AMP, 4PDT
		MS25469	5AMP, 6PDT
		MS25917	3AMP, 4PMT
		MS27222	50AMP, 3PST
		MS27400	10AMP, 4PDT
		MS27401	10AMP, 2PDT
		MS27418	20AMP, 3PST
		MS27706	20AMP, 3PST
		MS27707	50AMP, 6PST
		MS27709	10AMP, 4PDT
		MS27714	75AMP, 3PST
		MS27715	150AMP, 3PST
		MS27742	25AMP, 3PDT
		MS27743	25AMP, 3PDT

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:53Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
RELAY (CONT)	022500 (CONT)	MS27749	50AMP, 3PDT
		MS27750	50AMP, 3PDT
		MS27751	50AMP, 3 POLE
		MS27997	25AMP, 3PST
		MIL-R-7649	3 PHASE, 400 HERTZ
		MIL-R-13718	24VDC
		MIL-R-19309	SENSITIVE
		MIL-R-19523	CONTROL, SHIPBOARD
		MIL-R-19648	TIME DELAY
		MIL-R-21187	DPDT, SENSITIVE
		MIL-R-21335	SENSITIVE, DC
		MIL-R-22527	FIRE CONTROL EQUIPMENT
		MIL-R-26126	OVERVOLTAGE SENSING
		MIL-R-28776	ESTABLISHED RELBL, HYB
		MIL-R-39016	ESTABLISHED RELIABILITY

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
RELAY (CONT)	022500 (CONT)	MIL-R-83407	MERCURY WETTED REED
		MIL-R-83725	VACUUM DIELECTRIC
		MIL-R-83726	TIME DELAY

Source: https://dasiac.dla.mil - Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

2. REFERENCED DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications and Standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-R-5757	Relays, Electrical (For Electronic and Communication Type Equipment), General Specification For
MIL-R-6106	Relays, Electric, Aerospace. General Specification For
MIL-R-19648	Relay, Time Delay, Thermal, General Specification For
MIL-R-22527	Relay Armature
MIL-R-83725	Relay, Vacuum, General Specification For
MIL-R-83726	Relay, Time Delay, Electric and Electronic, General Specification For

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation Systems
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

MIL-STD-461	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-810	Environmental Test Methods for Aerospace and Ground Equipment
MIL-STD-1184	Electical Components for Automotive Vehicles: Waterproofness Tests
MIL-STD-1285	Marking of Electical and Electronic Parts

(Copies of specifications, standards, drawings, and publications required by contractors, in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. The issues of the docments which are indicated as DoD adopted shall be the issue listed in the issue of the DoDISS specified in the solicitation. The issues of documents which have not been adopted shall be those in effect on the date of the cited DoDISS.

ASTME380	Metric Practice Guide
ASTMD1868	Standard Method for Detection and Measurement of Corona Pulses in Evaluation of Insulation

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

(Nongovernment standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of Precedence. In the event of conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

Definitions contained in DOD-STD-35 are applicable to Relays.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Introduction. In order to properly prepare an SRS for Relays, it is necessary to use DOD-STD-35 in conjunction with this dash-numbered part. In the event the instructions or the writing methodology are not followed, an AEDPS edit routine will print error messages rather than the desired MSE document.

4.2 Specification Requirement Sheet (SRS). SRS requirements described in DOD-STD-35 are applicable to Relays.

4.3 Configuration.

4.3.1 Dimensions. SRS requirements for dimensions described in DOD-STD-35 are applicable to Relays.

4.3.2 Illustrations. Illustrations applicable to Relays are contained in Appendix A to this document.

4.4 Units of measure. The International System of Units (SI) or inch-pound units (U.S.), may be used to specify characteristics (e.g. weight, dimensions). Refer to ASTME380 for guidance in using SI. However, when different units of measure are available for specifying a characteristic, only one may be used. Both units of measure cannot appear in the same MSE.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

THIS PAGE DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for Relay characteristics. When different units of measure are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

TABLE III. TABULATION CANDIDATES

CODE 1656	COLUMN HEADING	CODE 1657	COLUMN HEADING	CODE 1616	COLUMN HEADING
	POLE		THROW		ENCLOSURE
3603	RATED OPERATING VOLTAGE (VOLTS)	3609	MAXIMUM OPERATING VOLTAGE (VOLTS)	3642	PICKUP VOLTAGE (VOLTS)
3660	DROPOUT VOLTAGE (VOLTS)				

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1402	MONITORING DURING THE TEST SHALL BE IN ACCORDANCE WITH METHOD 310 OF MIL-STD-202. TEST CIRCUIT LETTER 1402 SHALL APPLY.
1382	TEST CONDITION LETTER 1382 IN ACCORDANCE WITH METHOD 310 OF MIL-STD-202 SHALL APPLY.
3230	OPEN CONTACTS SHALL BE WIRED 3230.
3231	CLOSED CONTACTS SHALL BE WIRED 3231.
4678	THE LOAD SHALL BE 4678 PERCENT OF THE RATED LOAD.
4977	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
4976	MOUNTING SHALL BE BY THE NORMAL METHOD.
4975	MOUNTING SHALL BE IN ACCORDANCE WITH 4975.
3232	MOUNTING SHALL BE 3232.
3233	THE COIL SHALL BE ENERGIZED FOR 3233 HOUR(S).
3234	THE COIL SHALL BE ENERGIZED FOR 3234 MINUTE(S).

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VIBRATION, RANDOM (CONT)	
ELECTRICAL LOAD CONDITIONS (CONT)	
DURATION COIL IS DEENERGIZED (SELECT ONE)	
(HOURS)	3235
(MINUTES)	3236
TEST TEMPERATURE (DEGREES CELSIUS)	3237
WATERPROOFNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3240
NO EVIDENCE OF WATER LEAKABE.	3242
NO CHANGE IN DIELECTRIC WITHSTANDING VOLTAGE REQUIREMENTS.	3244
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3250
PER MIL-STD-1184.	3252

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3235	THE COIL SHALL BE DEENERGIZED FOR 3235 HOUR(S).
3236	THE COIL SHALL BE DEENERGIZED FOR 3236 MINUTE(S).
3237	THE TEST TEMPERATURE SHALL BE 3237 DEGREES CELSIUS.
3240	WATERPROOFNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3240.
3242	WATERPROOFNESS. THERE SHALL BE NO EVIDENCE OF WATER LEAKAGE.
3244	THERE SHALL BE NO CHANGE IN DIELECTRIC WITHSTANDING VOLTAGE REQUIREMENTS.
3250	WATERPROOFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3250.
3252	WATERPROOFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-STD-1184.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WATERPROOFNESS (CONT)	
PER MIL-E-13856. (CONT)	
TYPE (SELECT ONE)	
I.	3253
II.	3254
CLASS (SELECT ONE)	
1.	3255
2.	3256
3.	3257
4.	3258
MOUNTING HARDWARE (SEE TABLE X, DOD-STD-35)	
NOTE: AUTOMATIC WHEN TABLE X IS USED.	
WORKMANSHIP	
(DOC DES)	6870
ADDITIONAL REQUIREMENTS	
A____	7001
B____	7002
C____	7003
D____	7004
E____	7005

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:53Z
Check the source to verify that this is the current version before use.