

TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NUMBER	A	B	HEAT TREATMENT	FORMING 1/ PROCESS	ADDITIONAL 2/ REQUIREMENTS
-001	.125	1.125	INTERMEDIATE TEMPER	H	po
-003	.250	1.125	INTERMEDIATE TEMPER	H	po
-005	.250	.500	ANNEALED	H	po
-007	.375	1.000	ANNEALED	C	po
-009	.500	.750	ANNEALED	H	po
-011	.500	1.000	ANNEALED	H	po
-013	.500	1.438	INTERMEDIATE TEMPER	H	po
-015	.625	2.250	ANNEALED	H	po
-017	1.000	1.500	INTERMEDIATE TEMPER	H	po
-019	2.000	3.000	ANNEALED	H	po

1/ SEE REQUIREMENT 3
2/ SEE REQUIREMENT 4

REQUIREMENTS:

1. MATERIAL: STEEL, CORROSION RESISTANT, TYPE 416 (UNS S41600) AS SPECIFIED IN PROCUREMENT DOCUMENT.
2. LENGTH: STANDARD LENGTH OF WIRE IS 10 FEET MINIMUM, 12 FEET MAXIMUM.
3. FORMING PROCESS: COLD FINISHED - CODE "C"
   HOT FINISHED - CODE "H"
4. ADDITIONAL REQUIREMENTS:

   PICKLED OVERALL - CODE "po"
5. PART NUMBER: THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A DASH NUMBER FROM TABLE I.

   EXAMPLE: MS500135-001
   - (SEE TABLE I)
   - BASIC MS NUMBER
6. MARKING: IRON AND STEEL PRODUCTS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
3. REFERENCED GOVERNMENT (OR NONGOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

USER ACTIVITIES:
NAVY-OS

REVIEWER ACTIVITIES:
ARMY-AR, MI
AIR FORCE-99
DLA-IS

APPROVED 21 APR 87 REVISED

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection (for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P. A. ARMY - MR Other Cust AIR FORCE-20	INTERNATIONAL INTEREST	TITLE BAR,METAL,FLAT, CORROSION RESISTANT STEEL, TYPE 416	MILITARY STANDARD MS500135
PROCUREMENT SPECIFICATION ASTM A582	SUPERSEDES:		PAGE 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:48Z
Check the source to verify that this is the current version before use.