NOTICE - REVIEW/USER INFORMATION IS CURRENT AS OF DATE OF THIS DOCUMENT. FOR FUTURE COORDINATION OF CHANGES TO THIS DOCUMENT, DRAFT CIRCULATION SHOULD BE BASED ON THE INFORMATION IN THE CURRENT DODISS.

USER INTEREST:
ARMY - AV
NAVY - AS, CG, MC
AF - 17

REVIEW INTEREST:
ARMY - MI, EL, MI
NAVY - AS, SH
AF - 11, 85

FED. SUP CLASS
5990




TABLE I - CLAMPING DISC

DASH NO.	B DIA +.0008 -.0000	C DIA	"D" OD +.000 -.003	E	F RADIUS
-1	.6250	.812	1.156	.412	.277
-2	.8750	1.100	1.531	.569	.461
-3	.9375	1.250	1.844	.659	.959

NOTES:

1. MATERIAL: CLAMPING DISC -1, -2 AND -3; STEEL, CORROSION RESISTING, QQ-S-766, CLASS 410, CONDITION A. (COLD FINISH).
2. FINISH: CLAMPING DISC -1, -2 AND -3; PASSIVATE IN ACCORDANCE WITH QQ-P-35, TYPE II OR III.
3. HEAT TREATMENT: HEAT 1800° - 1925° F, QUENCH IN OIL, DRAW TO ROCKWELL C 30 - 35 APPROX. DRAW TEMP-950° F.
4. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
5. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED TOLERANCES: DECIMALS ±.005. INTERPRET DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH MIL-STD-8.
6. EACH CLAMPING DISC ASSEMBLY SHALL INCLUDE MS90402-2 (4 REQUIRED) AND MS35337-78 (4 REQUIRED).

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

This military standard is approved by the Department of Defense and is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 6 JUNE 1967 REVISED

P.A.-NAVY - AS Other Cust ARMY - MI NAVY - AS AF - 11	TITLE CLAMPING DISC ASSEMBLY	MILITARY STANDARD MS90400
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: BUORD 677030, 677031, 677032, 854459, 854460, 854461.	SHEET 1 OF 2

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. W68

PLATE NO. 15370

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:36Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5990




TABLE II - GEAR DATA			
DATA	DASH NO.		
	-1	-2	-3
TOOTH FORM	FULL DEPTH TRUE INVOLUTE	FULL DEPTH TRUE INVOLUTE	FULL DEPTH TRUE INVOLUTE
PRESSURE ANGLE	20°	20°	20°
NO. OF TEETH	72	96	116
DIAMETRAL PITCH	64	64	64
PITCH DIA (DATUM)	1.125	1.500	1.813
ROOT DIA (MAX)	1.086	1.456	1.771
BACKLASH	.0010 +.0015 -.0000	.0010 +.0015 -.0000	.0010 +.0015 -.0000

NOTICE - REVIEW/USER INFORMATION IS CURRENT AS OF DATE OF THIS DOCUMENT. FOR FUTURE COORDINATION OF CHANGES TO THIS DOCUMENT, DRAFT CIRCULATION SHOULD BE BASED ON THE INFORMATION IN THE CURRENT DODISS.

USER INTEREST:
ARMY - AV
NAVY - AS, CG, MC
AF - 17

REVIEWER INTEREST:
ARMY - MU, EL, MI
NAVY - AS, SH
AF - 11, 85

APPROVED 6 JUNE 1967 REVISED

This military standard is approved by the Department of Defense and is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. NAVY - AS Other Cust ARMY - MU NAVY - AS AF - 11	TITLE CLAMPING DISC ASSEMBLY	MILITARY STANDARD MS90400
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: NORD 677030, 677031, 677032, 854459, 854460, 854461	SHEET 2

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. W68

PLATE NO. 15320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:36Z
Check the source to verify that this is the current version before use.