THE TIRE SHALL BE IN ACCORDANCE WITH THE APPLICABLE REQUIREMENTS OF SPECIFICATION MIL-T-5041

FED. SUP CLASS 2620

SIZE	PLY RATING	STATIC LOAD RATING LBS	INFL. PRESS. PSI RATED	BURST PRESS. PSI MIN	BEAD WIDTH IN. MAX	WEIGHT LBS. MAX	STATIC UNBAL. OZ-IN MAX	TREAD	MOLD GAGE DEPTH MIN	DEFLC. +1/ -4/
11.00-10	8TT	5,000	45	1/245	1.25	28	18	2/RIB	.15	35%

1/NEW TIRE
2/AT LEAST THREE BUT NOT MORE THAN SEVEN CONTINUOUS CIRCUMFERENTIAL RIBS.
TT TUBE TYPE TIRE

RIM DATA:

WIDTH BETWEEN FLANGES (INCH)	FLANGE WIDTH (INCH)	LEDGE DIAMETER (INCH)	FLANGE HEIGHT (INCH)	HEEL RADIUS	FLANGE RADIUS	FLANGE EDGE RADIUS
8.50	.688	10	1.00	.250	.500	.125

TIRE DATA:

INFLATED OUTSIDE DIAMETER (INCH)		INFLATED SECTION WIDTH (INCH)		INFLATED SHOULDER DIAMETER (INCH)	INFLATED SHOULDER WIDTH (INCH)
MIN.	MAX.	MIN.	MAX.	MAX.	MAX.
28.10	29.00	10.40	11.00	25.60	9.35

THE TIRE COVERED BY THIS DRAWING SHALL BE SUITABLE FOR USE AND PROVIDE REASONABLE SERVICE LIFE ON NAVY AIRCRAFT DURING ALL NORMAL OPERATIONS AT TAKE-OFF SPEEDS OF NOT MORE THAN 160 MPH AND LANDING SPEEDS OF NOT MORE THAN 140 MPH ON ALL TYPES OF RUNWAYS, UNPREPARED SURFACES, AND ON AIRCRAFT CARRIERS.

DYNAMIC TESTS SHALL BE IN ACCORDANCE WITH MIL-T-5041.

NOTE: REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON THE DATE OF INVITATION FOR BID.

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Air Systems Command, Department of the Navy, and is mandatory for use by the Navy Military activities as required by the activity. Other activities may use it where suitable.

APPROVED 2 May 1966 REVISED

P.A. NAVY - NASC Other Cust	TITLE TIRE - AIRCRAFT, 11.00-10, TYPE III (NAVY)	MILITARY STANDARD MS 90444(AS)
PROCUREMENT SPECIFICATION MIL-T-5041	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Limited coordination) Previous editions may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-Feb-27 20:36Z
Check the source to verify that this is the current version before use.