INCH-POUND

MIL-B-44245B
30 March 1990
SUPERSEDING
MIL-B-44245A
25 March 1988

MILITARY SPECIFICATION

BEANS, GREEN, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers, small, round type, cut style green beans thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8915

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

United States Standards for Condition of Food Containers

(Copies are available from the Chairman, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Grades of Canned Green Beans and Canned Wax Beans

U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans

(Copies are available from the Director, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2077, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 2200 Wilson Boulevard, Suite 400-CD, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Beans, green.

3.2.1.1 Beans, green, fresh. The fresh green beans shall be sizes 3 or 4, round type, well formed, bright, firm, young, and tender. Green beans shall be fresh, sound, clean beans of a variety suitable for canning.

3.2.1.2 Beans, green, cut, individually quick frozen (IQF). The IQF green beans shall be round type, size 3 or 4, cut style, prepared from a variety suitable for canning. The green beans shall be U.S. Grade A of the U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans, except that character shall be a high Grade B (fairly good character). Prior to freezing, the cut green beans shall be blanched only to the extent necessary to ensure production of a conforming end item (see 6.4). The IQF cut green beans shall be held for not more than 6 months from the date of freezing to canning.

3.2.2 Salt. Salt shall be noniodized, white, refined, sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.3 Water. Water used for formulation and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Green bean preparation.

3.3.1.1 Fresh green bean preparation. The clean, fresh green beans shall be snipped at the ends, cut to a length of 0.75 to 1.25 inch, and blanched sufficiently to prevent discoloration and to remove excess air. The blanched beans shall be immediately cooled to the initial temperature of the cooling water and thoroughly drained. The blanched beans shall be handled in a manner to prevent discoloration and filled into the tray pack can within 4 hours after blanching.

3.3.1.2 Frozen green bean preparation. Frozen green beans shall be thawed only to the extent necessary to accommodate the filling operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

3.3.2 Brine preparation.

a. Brine shall be prepared in a manner to ensure compliance with finished product salt requirements. (At the time of filling, salt tablets may be substituted for granular salt in brine preparation.)

b. Brine shall be made fresh daily, and brine remaining at the end of a production day shall be discarded.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with the product to conform to the finished product requirements and to the following requirements:

a. The tray pack can shall be filled with the product and brine to a net weight of 101 ounces. Brine may be filled hot or cold.

b. Immediately after filling, each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to ensure compliance with the finished product requirement (see 3.6 k).

c. The filled and sealed tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 3.4 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for commercial sterility as specified in 4.5.3.4.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odors or flavors such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. No individual can shall contain less than 99 ounces of product.

e. The average net weight shall be not less than 101 ounces.

f. Drained weight of the green beans in any individual tray pack can shall be not less than 61.0 ounces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

g. The average drained weight of the green beans shall be not less than 63.0 ounces.

h. The finished product shall meet the requirements for each grading factor for U.S. Grade A, canned, round type, sizes 3 or 4, cut style, green beans of the U.S. Standards for Grades of Canned Green Beans and Canned Wax Beans, except the character shall be in accordance with U.S. Grade B or better of the U.S. Standards for Grades of Canned Green Beans and Canned Wax Beans.

i. The salt content of an individual tray pack drained product shall be not less than 0.7 percent and not greater than 1.0 percent.

j. The product shall show no evidence of excessive heating (materially darkened or scorched).

k. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing; Packing or Holding Human Food," and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspections. The inspection requi ments specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

4.5.3.1 Net weight examination. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 101 ounces or if the net weight of any individual can is less than 99 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The sample cans shall be selected at random from the lot. The sample cans shall be opened and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ 3/ 4/

Category	Defect
Major	
101	Drained weight of green beans in any individual tray pack can is less than 61.0 ounces 5/ 6/
102	Product shows evidence of excessive heating (materially darkened or scorched)

1/ The presence of any foreign material (for example, dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by a USDA agent.)

3/ Interior of filled and sealed cans shall be examined visually for coating defects during product examination. Suspected rust spots shall be verified by testing in accordance with 4.5.7. Any spot verified as a rust spot shall be cause for rejection of the lot. Any scratch or fracture that penetrates through the coating of a can shall be cause for rejection of the lot.

4/ Product not meeting finished product grade, type, size and/or style requirement specified in 3.6 shall be cause for rejection of the lot.

5/ To determine drained weight, the contents of the tray pack can shall be poured into a U.S. Standard No. 8 sieve in a manner that will distribute the product over the sieve without breaking the vegetable pieces. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

6/ The lot shall be rejected if the sample average drained weight is less than 63.0 ounces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

4.5.3.3 Salt content testing. Three filled and sealed tray pack cans shall be selected at random from the lot. The tray pack cans shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Vegetable Products, Processed, Section: Sodium Chloride in Canned Vegetables, except that preparation of the samples shall be as follows: The tray pack cans shall be opened and the brine solution drained. The remaining drained contents of each can shall be separately blended in a Waring Blendor or equivalent. The test results shall be reported to the nearest 0.1 percent. Any result failing to conform to the salt requirement in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.3.4 Commercial sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The sample cans shall be tested for sterility by incubating the cans at 95° ± 5°F for 10 days. Any evidence of can swelling shall be classified as a critical defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that the inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a major defect.

Evidence of buffing with an abrasive substance (see 5.1.1).

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4) except, for self-adhering labels, the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. One measurement shall be made when examining a ribbed lid; lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Test for rust spots on interior of tray pack cans. Where rust spots are suspected on interior of tray pack cans, the following test shall be performed:

a. Immerse a cotton swab in acetone or methyl ethyl ketone solvent and gently rub suspected spot. Handling of the solvent shall be in strict accordance with the guidelines of the manufacturer's Material Safety Data Sheet (MSDS).

b. If suspected spot immediately disappears, it is not a rust spot.

c. If suspected spot remains, continue gently rubbing with the swab resoaked with solvent, and observe for disappearances or retention of spot. Replenish solvent as necessary.

d. If spot persists, and all but a very thin coating, or no coating remains, it will be scored as a rust spot. This can be confirmed further by rubbing with a finger. The rust spot will be felt as a slight bump over the substrate.

4.5.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. One hundred and one ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. The practice of reconditioning tray pack cans by buffing with an abrasive substance shall not be permitted (see 4.5.4). The interior coating of filled and sealed thermoprocessed cans shall be free of rust spots, scratches, or fractures that penetrate through the coating when examined in accordance with 4.5.3.2.

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1), except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified, except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load, with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three-letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1990, would be coded as 0078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4.1 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently 15 - 20 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven for 35 - 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: For Army Field Feeding, serves 18 portions of 3/4 cup each. For other uses, serves 25 portions of 1/2 cup each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

As an alternate labeling method, a preprinted, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering labels are used, the tray pack can shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Level of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Canning of IQF vegetables. It has been found that IQF cut green beans which received a short "canner's blanch" prior to freezing helped to ensure conformance with the finished product character requirement (see 3.6 h).

6.5 Subject term (key word) listing.

Canned food
Combat field feeding
Food processing
Operational rations
Shelf stable
Vegetables

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, QM
Navy - MC
DP - SS

Preparing activity:

Army - GL

(Project 8915-0841)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-44245B	30 March 1990

3. DOCUMENT TITLE
Beans, Green, Thermostabilized, Tray Pack

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
U.S. Army Natick RD&E Center	508-651-5221	256-5221
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-ES Natick, MA 01760-5014	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil - Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.