MILITARY SPECIFICATION

OMELET WITH BACON PIECES, SMOKE FLAVORING ADDED, ARTIFICIALLY COLORED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers omelet with bacon pieces thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 8920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59)

(Application for copies should be addressed to the Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and/or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

3.2.1 Bacon pieces, cooked. Cooked bacon pieces shall be a USDA inspected product produced from cured bacon with added smoke flavoring. The bacon pieces shall be free flowing and shall possess the color, odor, and flavor of properly cured and smoked bacon with no evidence of off-flavors and off-odors. The bacon pieces shall comply with the following analytical requirements: Moisture content 36.7 ± 6.0 percent, fat content 25.1 ± 3.0 percent, and salt content 7.5 percent (maximum). The particle size shall be such that on a US Standard Series sieve, the following percentages (approximate) are retained:

US Standard Series Sieve	Percentage retained (approximate)
0.265 inch	16.4
0.250 inch (US Standard 1/4)	29.0
0.187 inch (US Standard No. 4)	30.6
0.0937 inch (US Standard No. 8)	23.0

The bacon pieces shall be vacuum packaged in oxygen impermeable bags which have been backflushed with nitrogen. The packaging shall provide protection to the product from the effects of light. The packaged product shall be stored and shipped under refrigerated conditions. Time from manufacture to use of the bacon shall not exceed 120 days.

3.2.2 Citric acid. Citric acid shall comply with the Food Chemicals Codex.

3.2.3 Color, Annatto, dry. Annatto color shall be a reddish-orange water soluble powder of the extractive of Annatto bixa Orellana. The powder shall pass through a U.S. Standard No. 10 sieve. The total color (as percent Norbixin) shall be 15 percent.

3.2.3 Eggs, whole, liquid or frozen. Whole eggs may be liquid or frozen and shall have been processed in accordance with the Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell as evidenced by a USDA Egg Products Inspection Certificate. For liquid whole eggs, the certificate shall state the time of pasteurization. Liquid whole eggs shall be held at a temperature of 40°F or lower and shall be held for not more than 72 hours from the time of pasteurization until the start of formulation of the product in which they are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days. The whole eggs shall be in excellent condition, i.e. free from objectionable odors, such as musty, sour, fruity and free from foreign material.

3.2.5 Oil, vegetable. Vegetable oil shall possess a clean, bland flavor, have a minimum stability of 15 hours (A.O.M.), have a free fatty acid value not to exceed 0.05 percent, have a moisture/volatile matter content not to exceed 0.06 percent, and pass a cold test of 5.5 hours (minimum).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

3.2.6 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner coverings have been removed. The ground pepper shall have a characteristic penetrating odor, a hot, biting, pungent flavor, and a light color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.7 Starch, waxy maize, modified, pregelatinized, instant. The starch shall be a pure, off white to white, odorless, slightly coarse-ground powder. The starch shall be modified, pregelatinized, cross-linked, and stabilized. The starch shall have a maximum moisture content of 9.0 percent and a pH of 4.0 to 6.5. The starch shall be resistant to breakdown under high temperature heating conditions, shall have good low temperature stability, and shall not set to a gel. The starch shall display good clarity and a smooth, short textured, heavy body. The starch shall be bland with no objectionable off-notes and shall comply with MIL-STD-900 (see 6.4).

3.2.8 Water. Water used for formulation, ice making, and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of frozen whole eggs. Frozen whole eggs shall be tempered to 28°F to 40°F and held in the temperature range of 28°F to 40°F for not more than 24 hours prior to product preparation.

3.3.2 Preparation of the product. The omelet with bacon pieces shall be formulated and prepared as follows:

Ingredient	Percent by weight
Eggs, whole	43.000
Water	23.137
Bacon pieces, cooked	23.000
Vegetable oil	7.000
Starch, modified	3.750
Pepper, white, ground	0.060
Citric acid	0.050
Annatto color	0.003

a. All mixing shall be in a manner so as to minimize the incorporation of air into the product.

b. The eggs shall be blended with the pepper, citric acid, and annato color only until smooth.

c. The starch shall be added to the vegetable oil and mixed to form a smooth mixture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

d. The starch-oil mixture shall be blended into the egg mixture until smooth.

e. The water shall be added and mixed in thoroughly.

f. The bacon pieces shall be thoroughly separated and then added to the mixture.

g. Filling shall be completed within 1 hour after mixture preparation. The time from mixture preparation to tray pack can filling may be extended a maximum limit of 4 hours provided the mixture is held under refrigeration in the temperature range of 28°F to 40°F during this time.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with omelet mixture so as to conform to the finished product requirements and to the following requirements:

a. Immediately after filling, each can shall be hermetically sealed under a vacuum of 5 to 8 inches of mercury as determined by presence of visible concavity of the can lid.

b. The filled and sealed tray pack cans shall be in the retort process within 1 hour after filling.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 5 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, rancid, scorched, burnt, stale, sour, musty, moldy, or sulfurous.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 102 ounces.

e. No individual can shall contain less than 100 ounces of product.

f. The finished product shall have a typical yellow cooked egg color.

g. The texture of the product shall not be rubbery.

h. The product shall be free from lumps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

i. Bacon pieces shall be uniformly distributed throughout the product.

j. The product shall show no evidence of excessive heating (materially darkened or scorched).

k. Free liquid in a can shall weigh not more than 1 ounce.

l. The average fat content shall be not greater than 20 percent.

m. The fat content of any individual tray pack shall be not greater than 22 percent.

n. The salt content of an individual tray pack shall not be less than 0.5 percent nor greater than 1.5 percent.

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The pork and egg components and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this document.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

4.4 First article. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5. Quality conformance inspection.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, US Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 102 ounces or if the net weight of any individual can is less than 100 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified by table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for 35 minutes in boiling water, opened, and inspected for the defects listed in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	--	0	2
	8	16	1	2
3201 to 35000	13	--	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Product not typical yellow cooked egg color.
102	Texture is rubbery.
103	Product not free from lumps. 3/
104	Bacon pieces not uniformly distributed throughout the product.
105	Product shows evidence of excessive heating (materially darkened or scorched).
106	Free liquid in an individual can weighs more than 1 ounce. 3/

1/ The presence of foreign material (e.g. glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot. Acceptability of product shall be determined by a Meat and Poultry Inspection Operations employee.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) Agent).

3/ To determine the weight of free liquid and to inspect for lumps, the following procedure shall be used: The can lid shall be removed and a portion (approximately 5 inches by 2-3/8 inches) shall be cut out of a corner of the omelet and removed from the can. The lid shall be replaced, leaving approximately 1/2 inch open at the cut out corner. The can shall be elevated on end, so that all liquid will flow out of the cut out corner, and drained for 1 minute into a tared container. The remaining product shall be divided into nine approximately equal portions and examined for lumps. Report free liquid to the nearest 0.1 ounce.

4.5.3.3 Fat and salt content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows;

- three for laboratory analysis.
- three for submission to the contractor.
- three for retention by an AMS agent as a reserve sample.

The three tray packs for laboratory analyses shall individually be tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The three unopened tray packs shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The test results shall be reported to the nearest 0.1 percent. The lot shall be rejected if:

a. The average fat content of the three tray packs is greater than 20 percent.

b. The fat content of any individual tray pack is greater than 22 percent.

c. The salt content of any individual tray pack is less than 0.5 percent or greater than 1.5 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with CFR 21, Part 113, Subpart D and the can manufacturer's requirement.

4.5.6 Vacuum examination. The sampling plan shall be as specified in table III. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge from bead to bead and verify that the distance from the straight edge to the lid is greater at the middle of the can than near the bead. The inspection lot shall include only tray packs produced in a single day on a single sealing machine.

TABLE III. Sampling plan for can vacuum examination

Lot size (cans)	Sample size (cans)	Acceptance number	Rejection number
0 to 1,200	32	0	1
1,201 to 3,200	50	0	1
3,201 to 10,000	80	1	2

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contact number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKING

5.1 Preservation. The product shall be preserved in accordance with level A or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 102 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.1.1 When specified (see 6.1), the base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 98 pounds per base box. The body design shall be reinforced on the bottom with six longitudinal beads or ribs 0.050 ± 0.010 inches deep. The beads shall be 9 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the bottom. The end design shall be reinforced with eight longitudinal beads 0.018 ± 0.004 inches deep. The beads shall be 11 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the end. The center four beads on the end design shall be interrupted to provide a 5-inch by 5-inch flat center panel for labeling. The apex of all the beads shall be outward on the edge. The interior and exterior can coating requirements shall be as specified in 5.1.1.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box, constructed and closed in accordance with style HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The inside box dimensions shall be 12-3/4 inches in length by 10-1/2 inches in width by 8-1/2 inches in depth. The cans shall be packed flat, four in depth within the box, with the first two cans placed with ends down and the next two cans with ends up. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The dimensions of the fiberboard pads shall be 11-1/4 inches by 9-1/4 inches (± 1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The inside box dimensions shall be 12-3/4 inches in length by 10-1/2 inches in width by 8-1/2 inches in depth. The cans shall be packed flat, four in depth within the box, with the first two cans placed with ends down and the next two cans with the ends up. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade 275 fiberboard. The dimensions of the fiberboard pads shall be 11-1/4 by 9-1/4 inches (± 1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.5.4 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT

a. To heat in water: Submerge sealed can in boiling water. Bring to boil again and continue boiling for 40 to 45 minutes. Remove from water and open lid for serving.

CAUTION: Use care when opening as pressure may have been generated within the can.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

b. To heat in oven: Either punch several holes in lid of tray can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F.

WARNING: Do not place closed can in oven, as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 18 servings. Cut 6 by 3.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, when tray pack cans are fabricated from 90 pounds per base box, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. When tray pack cans are to be fabricated from 98 pounds per base box (see 5.1.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

6.3 First article inspection. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Starch, waxy maize, modified, pregelatinized, instant. It has been found that National 78-0018 Food Starch manufactured by National Starch and Chemical Corporation, Food Products Division, P.O. Box 6500, Bridgewater, NJ 08807, meets the requirements of 3.2.7 and performs satisfactorily in this product.

6.5 Subject term (key word) listing.

Bacon
Canned foods
Combat field feeding
Eggs
Omelet
Tray pack
Thermostabilized

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8920-0490

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-O-44250	Omelet with Bacon Pieces, Smoke Flavoring, Added, Artificially Colored, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:57Z
Check the source to verify that this is the current version before use.