MIL-P-44247(GL)
15 October 1936

MILITARY SPECIFICATION

PACK, PARACHUTIST'S, AT4 ROCKET

This specification is approved for use by the U.S. Army Natick Research~ Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of a reinforced jump pack for AT4 Rocket. The jump pack is fabricated from nylon duck and nylon webbing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
PPP-B-601	- Boxes, Wood Cleated-Plywood
PPP-B-636	- Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

DRAWINGS

U.S ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

11-1-3398	Pack Assembly, Parachutist, AT4 Rocket
11-1-3399	Pocket Assembly, Muzzle
11-1-3400	Pocket Assembly, Butt
11-1-3401	Pocket Assembly, Lowering Line
11-1-3402	Handle Carrying
11-1-3403	Line ,Attachment, Web
11-1-3404	Shock Absorber, Aft End
11-1-3405	Cover, Pocket, Muzzle
11-1-3406	Pad, Pocket, Muzzle
11-1-3407	Cover, Pocket, Butt
11-1-3408	Pad, Pocket, Butt
11-1-3409	Cover, Pocket, Lowering Line

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence, In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence, Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained,

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4,3, 6.2, and 6.4).

3.2 Materials and components. Materials arid components shall conform to the requirements on the applicable drawings, to subsidiary specifications and standards applicable thereto and as specified herein (see 6.5).

3.3 Construction. The construction shall conform in all respects to the drawings listed in Section 2 and as specified herein.

3.3.1 Type 301 stitching. Ends of all stitchings shall be backstitched or overstitched as specified on the Drawing 11-1-3398 except when caught in other stitching or turning under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewed.

3.3.1.1 Repairs of type 301 stitching, Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box, box-x and W-W- stitching) and continue a minimum of 1 inch beyond the defective area onto the existing stitching, Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping or backstitches are used to secure the ends of the stitching.

3.3.1.3 Repairs. Repairs such as mendas, darns, patches or splices are not permitted on the packs.

3.3.1.4 Replacement of defective components. During the spreading, cutting and manufacturing process, components of the pack having material defects or damages that are classified as defects in table I shall be removed from production and replaced with non-defective and properly matched components.

3.4 Workmanship. The pack shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to Prescribed requirements,

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractors overall inspection system or quality program, The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does no authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material,

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements,

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. when a first article is required (see 6.2), it shall be examined for the defects specified in table 1. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 components. and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this document or applicable documents.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements, The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table 1. The lot size shall be expressed in units of packs. The sample unit shall be one pack. The inspection level shall be It and the acceptable quality level (AQL), expressed in terms of defects per hundred units shall be 1.0 for major defects and 6,5 for total (major and minor combined) defects,

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Material defects and damages (cloth)	Any cut, hole, tear, needle chew or weakening defect in material.	x	
	Any abrasion marks, broken or missing yarns or multiple floats.	x	
	Any mend, darn or patch.	x	
	Needle chews.	x	
Felt	Any hole, cut or tears		x
Webbing or tape	Any hole, tear, cut or frayed edges	x	
	Needle chews: up to 1/8 inch in length.		x
	- 1/8 inch or more in length.	x	
	Not continuous, i.e., spliced	x	

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Webbing or tape (cont'd)	Ends of webbing not as required,	x	
	Frayed or scalloped edges not firmly or tightly woven.	x	
Hardware - general	Broken or malformed; corroded area; burrs or sharp edge,	x	
	Finish omitted or not as specified.	x	
	Any required component improperly installed causing failure to serve intended purpose.	x	
Seams and stitchings	Open seams:		
	- 1/2 inch or less,		x
	- more than 1/2 inch.	x	
	NOTE : A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur,		
Raw edge (on edge required to be finished)	More than 1/2 inch in length when securely caught in stitching.		x
	NOTE : Raw edge not securely caught in stitching shall be classified as an open seam.		
Seam and stitch type	not specified seam or stitch type,	x	
	Seam twisted, pleated of badly puckered (unless otherwise classified herein).		x
	Any line of stitching not beginning or ending where specified (unless otherwise classified herein).		x
	Any seam not lapped or finished as specified.		x
Stitch tension	Tension loose, resulting in loos bobbin or top thread.		x
	Tension tight, resulting in puckering of material,		x

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd

Examine	Defect	Classification Major	Classification Minor
Stitches per inch (all types of stitching)	One stitch less than minimum specified. 1/		X
	Two or more stitches less than minimum specified. 1/	X	
	Two or more stitches in excess of maximum specified. 1/		X
	NOTE: Variation in the number of stitches per inch caused by operator speeding up the machine and pulling the material in order to sew over heavy places, or in turning corners shall be classified as follows:		
	Within the minor defect classification no defect.		
	Within the major defect classification minor defect.		
1/ Score only where the condition exists for 3 inches or more or in several areas with an accumulated distance of 5 inches or more in an individual seam.			
Thread breaks,	On stitching other than box-x or W-W stitching, overstitched less than 1 inch in each direction beyond defective stitching area.		X
	On box, box-x or W-W-stitching, overstitched less than 1/2 inch in each direction beyond the defective stitching area.		X
	NOTE : Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Stitching ends	Not secured as specified.		X
ROWS of stitching	One or more required rows of stitching omitted: affecting serviceability seriously.	X	
	- affecting serviceability but not seriously.		X

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Component and assembly	Any component part or required operation omitted (unless otherwise classified herein).	x	
	Any operation not performed as specified (unless otherwise classified herein).		x
	Color of component not as specified.		x
Marking	Omitted, incorrect, illegible, misplaced, or size of characters not as specified,	x	
Cleanness	Any spot or stain on outside.		x
	Thread ends not trimmed as specified or loose threads not removed,		x
Shock absorber	Any cut, tear or hole.	x	
	Cone section not completely adhered (When fabricated separately.	x	

4.4.4 End item dimensional examination. The end item shall be examined for conformance to dimensions annotated with an asterisk on Drawing 11-1-3398. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of packs. The sample unit shall be one pack. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination, The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5,

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or riot as specified.
Workmanship	Inadequate application of components such as; incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling.
Content	Number per container is more or less than required.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. Each jump pack shall be laid flat, felt pad side up. All areas of the felt pad shall be lightly and uniformly sprinkled with napthalene flakes. The quick release snap hook shall be removed and completely wrapped in 30-pound minimum basis weight kraft paper conforming to A-A-203. The wrapped snap hook shall be placed within the jump pack. The pack shall be folded to measure approximately 42-1/2 inches in length, 13-1/4 inches in width and 3 inches in depth. The lowering line attachment web shall be neatly folded and placed into the lowering line pocket. The honeycomb cross securing straps shall be secured by the quick fit adapters. Each folded pack and the end shock absorber shall be placed into a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW, class domestic, grade 200 of PPP-B-636. The inside dimensions of the box shall approximate 52-1/2 inches in length, 13-1/2 inches in width and 7-1/2 inches in depth. Approximate dimensions shall be furnished as a guide only.

5.2 Packing Packing shall be Level A, B or commercial as specified (see 6.2).

5.2.1 Level A packing. Ten jump packs, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container, conforming to overseas type, style A or J, grade A or B, type 2 load of PPP-B-601. The inside dimensions of each container shall approximate 53-1/2 inches in length, 28 inches in width, and 28 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and reinforced in accordance with the appendix of PPP-B-601.

5.2.2 Level B Packing. Ten jump packs, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except that the shipping container shall be domestic type.

5.2.3 Commericial packing,. Jump packs, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special markings required by the contract or purchase order. unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The jump pack is designed to allow the individual parachutist to air deliver the AT 4 Rocket.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6,4).
c. Selection of applicable levels of packing (see 5.2).

6.3 Sample. For access to samples, address the contracting activity issuing the invitation for bids,

6.4 First article. When a first article sample is required, it shall be inspection and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.6 Subject term (key word) listing.

Jump pack
Parachutist's

Custodians:

Army - GL

Preparing activity:

Army - GL

Project No. 1670-A750

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-44247(GL)	Pack, Parachutist's, AT4 Rocket

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:56Z
Check the source to verify that this is the current version before use.