INCH-POUND

MIL-S-44254B
31 December 1990
SUPERSEDING
MIL-O-44254A
9 June 1989

MILITARY SPECIFICATION

SCRAMBLED EGGS WITH CHEESE, WESTERN-STYLE, ARTIFICIALLY COLORED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers western-style scrambled eggs with cheese thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59)

(Copies are available from the Chief, Standardization Branch, Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 3944, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairperson, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-Sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 2200 Wilson Boulevard, Suite 400-CD, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Whole eggs, liquid or frozen. Whole eggs may be liquid or frozen and shall have been processed and labeled in accordance with the Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell eggs as evidenced by a USDA Egg Products Inspection Certificate. For liquid whole eggs, the certificate shall state the date and time of pasteurization. Liquid whole eggs shall be held at a temperature of 40°F or lower and shall be held for not more than 72 hours from the time of pasteurization until the start of formulation of the product in which the liquid whole eggs are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days. The whole eggs shall be free from off-odors, off-flavors, or foreign odors and flavors such as metallic, musty, sour, fruity, or sulfide-like, and shall be free from foreign materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

3.2.2 Ham, canned or cooked. The ham shall be high commercial style. The ham shall not be labeled "water added" and shall not contain dextrose. The canned or cooked ham shall be maintained at an internal temperature of 28° to 40°F for a period of time not to exceed 60 days from the date of pack until preparation of the finished product.

3.2.3 Oil, vegetable. Vegetable oil shall possess a clean, bland flavor, and shall have a minimum stability of 15 hours (A.O.M.), a free fatty acid value not to exceed 0.05 percent, a moisture/volatile matter content not to exceed 0.05 percent, a moisture/volatile matter content not to exceed 0.06 percent and shall pass a cold test of 5.5 hours (minimum).

3.2.4 Starch, waxy maize, modified, pregelatinized, instant. The starch shall be a pure, off-white, odorless, slightly coarse ground powder. The starch shall be modified, pregelatinized, cross-linked, and stabilized. The starch shall have a maximum moisture content of 9.0 percent and a pH of 4.0 to 6.5. The starch shall be resistant to breakdown under high temperature heating conditions, shall possess good low temperature stability, and shall not set to a gel. The starch shall display good clarity and a smooth, short textured, heavy body. The starch shall be bland with no objectionable off-notes. The starch shall comply with MIL-STD-900 (see 6.4).

3.2.5 Cheese, cheddar, sharp, dehydrated, uncolored. Dehydrated cheddar cheese shall be derived from sharp aged cheddar cheese. The dehydrated cheese shall be white in color, uniform in composition and appearance, and free from burnt specks and from lumps that do not fall apart under light finger pressure. The cheese shall possess a characteristic flavor and odor. The dehydrated cheese shall contain not more than 4.0 percent moisture, not more than 6.0 percent salt and not less than 45.0 percent milkfat.

3.2.6 Onions, dehydrated, chopped. Dehydrated chopped onions shall be Fancy Grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.7 Pepper, green, sweet, dehydrated. The peppers shall be 1/4-inch dices of sweet bell peppers which have been air-dried, freeze-dried, or a combination of each. The pepper dices shall be practically free of seeds, seed cells, and diseased or rotted areas. The pepper dices shall possess a fresh, clean, typical sweet green pepper flavor and odor and a green, with minimal brownish color. The moisture content shall be not greater than 5 percent.

3.2.8 Salt. Salt shall be noniodized, white, refined, sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.9 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner covering have been removed. The ground pepper shall have a characteristic penetrating odor, a hot, biting, pungent flavor, and a light

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.10 Citric acid. Citric acid shall comply with the Food Chemicals Codex.

3.2.11 Color, annatto, dry. Annatto color shall be a reddish-orange water soluble powder of the extractive of Annatto bixa Orellana. The powder shall contain not more than 5.0 percent moisture, and 100 percent of the powder shall pass through a U.S. Standard No. 10 sieve. The total color (as % Norbixin) shall be 15 percent.

3.2.12 Water. Water used for formulation, rehydration, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of whole eggs. Frozen whole eggs shall be tempered/thawed and held at an internal temperature of 28° to 40°F for not more than 24 hours prior to product preparation.

3.3.2 Ham preparation. The ham shall be mechanically diced with dicer settings at 3/8 by 3/8 by 3/8 inch.

3.3.3 Product preparation. The western-style scrambled eggs with cheese shall be formulated and prepared as follows:

Ingredients	Percent by weight
Whole eggs, liquid or frozen	43.000
Ham, diced	23.000
Water	19.407
Oil, vegetable	6.000
Starch, waxy maize, modified, pregelatinized, instant	3.500
Cheese, cheddar, sharp, dehydrated, uncolored	2.000
Onions, dehydrated, chopped	1.750
Peppers, green, sweet, dehydrated	0.600
Salt 1/	0.600
Pepper, white, ground	0.090
Citric acid	0.050
Color, annatto, dry	0.003

1/ The total amount of salt in the formula shall be adjusted, as necessary, to produce a product that complies with the finished product salt requirements (see 3.6).

a. All mixing shall be in a manner that will minimize the incorporation of air into the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

b. The whole eggs shall be blended with cheddar cheese, white pepper, salt, citric acid, and annatto color only until smooth.

c. The starch shall be added to the vegetable oil and mixed to form a smooth mixture.

d. The starch/vegetable oil mixture shall be blended into the whole egg mixture until smooth.

e. The sweet green peppers and chopped onions shall be rehydrated with a small amount of formulation water.

f. The remaining water shall be added and mixed in thoroughly.

g. The ham dices, rehydrated green peppers and onions, and rehydration water shall be added to the mixture and uniformly mixed.

h. Filling shall be completed within 1 hour after mixing preparation. The time from mixture preparation to tray can filling may be extended to a maximum limit of 4 hours provided the internal temperature of the product does not exceed 40°F during this time.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product to conform to the finished product requirements and to the following requirements:

a. Immediately after filling, each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to ensure compliance with the finished product requirement (see 3.6m).

b. The filled and sealed tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

d. The color of the finished product shall be only slightly darker than a typical yellow cooked egg color.

e. Texture of the scrambled eggs shall not be rubbery.

f. Free liquid weight in any individual tray pack can shall be not more than 3.0 ounces.

g. The ham dice, onion, and green pepper pieces shall be uniformly distributed throughout the product.

h. The average net weight shall be not less than 102 ounces.

i. No individual can shall contain less than 100 ounces of product.

j. The average fat content of the finished product shall be not greater than 13.5 percent and no individual tray pack can shall have a fat content greater than 15.5 percent.

k. The salt content of any individual tray pack shall be not less than 0.5 percent nor greater than 1.5 percent.

l. The product shall show no evidence of excessive heating (materially darkened or scorched).

m. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The meat component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

4.5.3.1 Net weight examination. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 102 ounces or if the net weight of any individual can is less than 100 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The sample cans shall be selected at random from the lot. The sample cans shall be heated in accordance with heating instructions on the can label, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ 3/

Category	Defect
Major	
101	Product is more than slightly darker than typical yellow cooked egg color
102	Texture of scrambled eggs is rubbery
103	Free liquid weight in any individual tray pack can is more than 3.0 ounces 4/
104	Ham dice, onion, and green pepper pieces not uniformly distributed throughout the product
105	Product shows evidence of excessive heating (materially darkened or scorched)

1/ The presence of foreign material (for example, dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by a USDA agent.)

3/ Interior of filled and sealed cans shall be examined visually for coating defects during product examination. Suspected rust spots shall be verified by testing in accordance with 4.5.7. Any spot verified as a rust spot shall be cause for rejection of the lot. Any scratch or fracture that penetrates through the coating of a can shall be cause for rejection of the lot.

4/ To determine the weight of free liquid, the following procedure shall be used. The can lid shall be removed and a portion (approximately 5 inches by 2-3/8 inches) shall be cut out of one corner of the product and removed. The lid shall be replaced, leaving approximately 1/2 inch open at the cut out corner. The can shall be elevated on end, so that all liquid will flow out of the cut out corner, and drained for 1 minute into a tared container. The free liquid weight shall be reported to the nearest 0.1 ounce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

4.5.3.3 Fat and salt content testing. Three filled and sealed tray pack cans shall be selected at random from the lot. The tray pack cans shall be individually tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The unopened tray pack cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring Blendor, or equivalent. The test results shall be reported to the nearest 0.1 percent. Any result failing to conform to the fat and salt requirements in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that the inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a major defect:

Evidence of buffing with an abrasive substance (see 5.1.1).

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4) except, for self-adhering labels, the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closure shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D, or 9 CFR Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

the center of the tray pack can. One measurement shall be made when examining a ribbed lid; lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Test for rust spots on interior of tray pack cans. Where rust spots are suspected on interior of tray pack cans, the following test shall be performed:

a. Immerse a cotton swab in acetone or methyl ethyl ketone solvent and gently rub suspected spot. Handling of the solvent shall be in strict accordance with the guidelines of the manufacturer's Material Safety Data Sheet (MSDS).

b. If suspected spot immediately disappears, it is not a rust spot.

c. If suspected spot remains, continue gently rubbing with the swab resoaked with solvent, and observe for disappearances or retention of spot. Replenish solvent as necessary.

d. If the spot persists, and all but a very thin interior can coating or no interior can coating remains, the spot shall be scored as a rust spot. This can be confirmed further by rubbing with a finger. The spot will be felt as a slight bump over the substrate.

4.5.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

5.1.1 Level A preservation. One hundred and two ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. The practice of reconditioning tray pack cans by buffing with an abrasive substance shall not be permitted (see 4.5.4). The interior coating of filled and sealed thermoprocessed cans shall be free of rust spots, scratches, or fractures that penetrate through the coating when examined in accordance with 4.5.3.2.

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three digit-letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1990, would be coded as 0078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4.1 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently 40 - 45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven 35 - 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions of 2/3 cup each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

As an alternate labeling method, a preprinted, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering labels are used, the tray pack cans shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Level of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Starch, waxy, maize, modified, pregelatinized, instant. It has been found that National 78-0018 Food Starch manufactured by National Starch and Chemical Corporation, Food Products Division, P.O. Box 6500, Bridgewater, NJ 08807, meets the requirements of 3.2.4 and performs satisfactorily in this product.

6.5 Subject term (key word) listing.

Canned foods
Combat field feeding
Food processing
Operational rations
Shelf stable

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, QM
Navy - MC
DP - SS

Preparing activity:

Army - GL

(Project 8940-0711)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-44254B	1990 December 31

3. DOCUMENT TITLE

Scrambled Eggs With Cheese, Western-Style, Artificially Colored, Thermostabilized, Tray Pack

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION

c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
U.S. Army Natick RD&E Center	508-651-4501	256-4501

c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:
Commander, U.S. Army Natick RD&E Center ATTN: STRNC-WTP Natick, MA 01760-5018	Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:59Z
Check the source to verify that this is the current version before use.