INCH-POUND

MIL-T-44243A
AMENDMENT 1
24 February 1992

MILITARY SPECIFICATION

TENT SECTIONS, TENT, EXTENDABLE, MODULAR,

PERSONNEL (TEMPER)

This amendment forms a part of MIL-T-44243A, dated 23 November 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2: Delete and substitute:

"1.2 Classification. Tent sections shall be of the following items, and part numbers as specified (see 6.2):

Items	Item Part Numbers for tents with Camouflage Green Exterior	Item Part Numbers for tents with Tan Exterior
1. - End section	5-4-3350-1	5-4-3350-2
2. - Window section (temperate)	5-4-3363-1	5-4-3363-2
3. - Door section (desert/tropical)	5-4-3351-1	5-4-3351-2
4. - Window section (desert/tropical)	5-4-3352-1	5-4-3352-2
5. - Door section (temperate)	5-4-3362-1	5-4-3362-2
6. - Tent fly (16 feet)	5-4-3353-1	5-4-3353-2
7. - Tent fly (8 feet)	5-4-8486-1	5-4-8486-2
8. - End section liner (temperate)	5-4-3364	5-4-3364
9. - End section liner (desert/tropical)	5-4-3365	5-4-3365
10. - Intermediate liner (temperate)	5-4-3366	5-4-3366
11. - Intermediate liner (desert/tropical)	5-4-3367	5-4-3367
12. - Tent floor (single ply): 1/		
8 feet	5-4-3368-1or-2	5-4-3368-1 or-2
24 feet	5-4-3984-1or-2	5-4-3984-1 or-2
40 feet	5-4-3985-1or-2	5-4-3985-1 or-2

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:54Z
Check the source to verify that this is the current version before use.

Items	Item Part Numbers for tents with Camouflage Green Exterior	Item Part Numbers for tents with Tan Exterior
13. - Tent floor (insulated), 8 feet	5-4-3369	5-4-3369
14. - Vestibule	5-4-3370-1	5-4-3370-2
Vestibule door	5-4-3371-1	5-4-3371-2
15. - Vestibule floor (single ply) 1/	5-4-3372-lor-2	5-4-3372-1 or-2
16. - Vestibule floor (insulated)	5-4-3373	5-4-3373
17. - Partition	5-4-3391	5-4-3391
18. - Tent cover	5-4-3359-1	5-4-3359-2
19. - Vestibule container	5-4-3374-1	5-4-3374-2
20. - Pin container	5-4-8487-1	5-4-8487-2
21. - Modesty curtain	5-4-3613	5-4-3613
22. - Plenum, end wall, 16 feet	5-4-3614	5-4-3614
23. - Plenum, extendable, 16 feet	5-4-3618	5-4-3618
24. - Vestibule door sliding blackout curtain	5-4-3621-1	5-4-3621-2
25. - Plenum, side entrance, 16 feet	5-4-3620	5-4-3620
26. - Vestibule door cap	5-4-3983-1	5-4-3983-2

1/ For items 12 and 15; specify part number with "-1" when green shade is required for these items or part number with "-2" when gray shade is required for these items."

2.1.2, under "DRAWINGS", delete list and substitute the following new list:

"5-4-3342 - Hitch Pin Clip and Holder
5-4-3349 - Tent Sections, Tent, Extendable, Modular, Personnel (TEMPER)
5-4-3350 - End Section
5-4-3351 - Door Section (Desert/Tropical)
5-4-3352 - Window Section (Desert/Tropical)
5-4-3353 - Tent, Fly (16'0")
5-4-3354 - Screen Door
5-4-3355 - Vent Flap Assembly
5-4-3356 - Window and Flap Assembly
5-4-3357 - Becket, Ridge to Eave (8'4")
5-4-3358 - Erection Instructions
5-4-3359 - Tent Cover
5-4-3360 - Weather Seal Flap (6'11-1/4")
5-4-3361 - Purlin Flaps (8'0")
5-4-3362 - Door Section (Temperate)
5-4-3363 - Window Section (Temperate)
5-4-3364 - End Section Liner (Temperate)
5-4-3365 - End Section Liner (Desert/Tropical)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:54Z
Check the source to verify that this is the current version before use.

5-4-3366 - Intermediate Liner (Temperate)
5-4-3367 - Intermediate Liner (Desert/Tropical)
5-4-3368 - 8 Ft. Tent Floor (Single Ply)
5-4-3369 - Tent Floor (Insulated)
5-4-3370 - Vestibule
5-4-3371 - Vestibule Door
5-4-3372 - Vestibule Floor (Single Ply)
5-4-3373 - Vestibule Floor (Insulated)
5-4-3374 - Vestibule Container
5-4-3375 - Adapter
5-4-3376 - Adapter
5-4-3377 - Vent Flap
5-4-3378 - Window and Flap
5-4-3379 - Sleeve, ECU-DUCT
5-4-3380 - Door/Window
5-4-3381 - Stove Pipe Flap
5-4-3382 - End Liner
5-4-3383 - Door/Window Section Liner (Temperate)
5-4-3384 - Door
5-4-3386 - Stove Pipe Shield Flap
5-4-3387 - Door/Window Section Liner (Desert/Tropical)
5-4-3388 - Vent Flap
5-4-3389 - Flap
5-4-3390 - Suspension Strap
5-4-3391 - Partition
5-4-3613 - Modesty Curtain
5-4-3614 - Plenum, End Wall
5-4-3615 - Body, End Wall
5-4-3616 - Cover, Plenum
5-4-3617 - Extension 12 Inch Dia., End Wall
5-4-3618 - Plenum, Extendable, 16 Feet
5-4-3619 - Body, Extendable
5-4-3620 - Plenum, Side Entrance, 16 Feet
5-4-3621 - Vestibule Door Sliding Blackout Curtain
5-4-3981 - Body, Side Entrance
5-4-3982 - Exterior, 12 Inch Dia., Side Entrance
5-4-3983 - Vestibule Door Cap
5-4-3984 - 24 Ft. Tent Floor (Single Ply)
5-4-3985 - 40 Ft. Tent Floor (Single Ply)
5-4-8480 - Becket, Eave to Ground (6'4")
5-4-8481 - Becket, Vestibule (9'0")
5-4-8482 - Weather, Seal Flap (8'8")
5-4-8483 - Weather, Seal Flap (9'1/2")
5-4-8484 - Weather, Seal Flap (9'2")
5-4-8485 - Purlin, Flap (22'0")
5-4-8486 - Tent, Fly (8'0")
5-4-8487 - Pin Container
5-4-8488 - Sleeve, Electrical"

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:54Z
Check the source to verify that this is the current version before use.

PAGE 5

3.3: Delete and substitute:

"3.3 Construction. Tent sections shall comply with the provisions of the drawings in 2.1.2 applicable to the item, and part number specified, all subsidiary drawings thereto, and as specified herein."

PAGE 26

6.1: Delete and substitute:

"6.1 Intended use. Item part numbers for tents with camouflage green exterior are intended for use in tent systems covered by types I through XVI, class 1 of MIL-T-44271. Item part numbers for tents with tan exterior are intended for use in tent systems covered by types I through XVI, class 2 of MIL-T-44271."

6.2, sub letter "b." Delete and substitute:

"b. Item and part number required (see 1.2)."

6.4, Delete and substitute:

"6.4 Repair of leaking seams. A satisfactory method of applying seam sealer for the repair of leaking seams is as follows:

Observe the following warnings and apply K Kote Seam Sealer per P/N 83-234C or equal (see 6.9) to fabric assemblies as described below.

WARNING

Do not smoke or use seam sealer or solvent near open flame.

Be sure to observe all warnings and instructions that come with sealer and solvent.

Use seam sealer and solvent in an open, well ventilated area, away from sources of combustion. Avoid direct sunlight if possible.

NOTE

Tent can be erected or fabric assemblies can be removed and laid flat.

Do not use a foam brush. Use a bristle brush only.

Sealer may be applied to outside or inside of fabric assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:54Z
Check the source to verify that this is the current version before use.

Sealer should only be applied to new stitches, patches, etc., or those areas that have shown water leakage.

Two light coats of sealant are more effective than one thick coat. Do not use excessive amounts of sealer, as this does not increase effectiveness and will give the tent a poor appearance.

Do not leave original sealer container open, as sealer will thicken and become unusable. Limit the amount of time container is open.

(1) Surface to be sealed should be cleaned as thoroughly as practical and completely dry before applying sealer.

(2) Pour small amount of sealer into a clean container and immediately reseal the gallon container.

(3) Apply sealer to stitching or repair to be sealed, overlapping seam stitching or edges of repair by 1/2".

(4) Allow first coat to dry to the touch.

(5) Apply second coat as described in step (3)."

PAGE 28

6.9, Add the following new paragraph:

"6.9 Seam sealer supply source. A source of supply for seam sealer used in 6.4 is:

Kenyon Consumer Products
P.O. Box 3715
1425 Kingstown Road
Peace Dale, Rhode Island 02883"

Custodians:

Army - GL
Navy - NU

Preparing activity:

Army - GL

(Project 8340-0558)

Review activities:

Army - MD
DLA - CT

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:54Z
Check the source to verify that this is the current version before use.