COMMERCIAL ITEM DESCRIPTION

SEALS, STRAPPING (HEAVY DUTY, STEEL, FLAT)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification QQ-S-781, Seals.

This description covers steel strapping seals.

Salient characteristics.

The heavy duty steel strapping seals shall be supplied in the following duty, joint styles, grades, finishes, sizes (width and thickness), and strengths:

Duty

Heavy duty

Joint Style

Notch
Crimp
Combination (notch and crimp)

Grades

Standard grade	- For hand operated tensioning and sealing.
Automatic power machine grade	- For power machine with automatic feed.

Finishes

See table I.

Strengths

The seals shall be designed to have a strength based on the seal type (shown below), joint type (notch or crimp) and duty (heavy) (see table I). Notch and crimp joints style shall be single, double, or triple. The length of a seal shall be compatible with the joint style and design. Fo single notch or crimp seals, the seal strength shall be 40 percent of strapping breaking strength and double and triple notch or crimp seals shall have a seal strength equal to 75 percent of the strapping breaking strength when the seal is properly applied to the strapping and tested in accordance with ASTM E8.

Seal Type

See table I.

Workmanship. Seals shall be free of burrs or slivers. Seals shall be straight, smooth, and clean and shall be free from cracks, grooves, waves, edge curvature, indentations, and excessive oils.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance wit Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note. Purchasers should specify strapping size design for grade, finish, and seal type, and joint style.

This commercial item description supersedes in part, A-A-800 , dated May 13, 1980. A-A-800 is being revised to reflect changes.

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

FSC 8135

TABLE I. Steel strapping seal (heavy duty)

Seal sized to be with following steel strapping		Typical lowest average strapping breaking strength	Joint type		Seal type*				Painted only	Galvanized		Zinc painted
Width	Thickness		Notch	Crimp	Snap on or open	Thread on or closed	Push type	Magazine feed		Std. commrcl.	Govt. grade 2 waxed	
3/8		985		triple		X			X			
1/2		2,250	double			X			X			
3/4		2,510	double	double	X				X			
		2,200	single	single		X			X			
		3,250	single or double		X	X	X	X	X	X	X	
		4,650		triple		X			X			
1-1/4		5,450	single		X		X		X	X	X	
		7,700	double	double		X	X	X	X		X	
		9,500		triple	X	X			X			
2		12,300	double	double		X			X		X	
		15,500	triple	triple		X			X			

*Cross tie available.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.