A-A-2229
August 21, 1984

COMMERCIAL ITEM DESCRIPTION

LAMP, PHOTO PROJECTION

The General Services Administration has authorized the use of this commercial item description.

This description covers a clear projection photo lamp.

Salient characteristics.

The salient characteristics shall be in accordance with Table I.

Type 1 (CBA) photo lamp shall be in accordance with ANSI Standard C78.1408.

Type 2 and 3 should be used in equipment designed to maintain bulb and base temperature within safe limits.

The issues of ANSI Standard C78.1408 in effect on the date of solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packin, labeling, and marking shall be as specified in the contract or order.

Notes. The National Stock Numbers (NSNs) for: Type 1 is 6240-00-471-5399
Type 2 is 6240-00-069-3505
Type 3 is 6240-00-143-3044
Type 4 is 6240-00-351-3375

ANSI Standard C78.1408 is available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

The commercial item certification clause is not required when this commercial item description is used.

MILITARY INTERESTS:

Military Coordinating Activity
None. DoD has waived coordination on this commercial item description until further notice.

PREPARING ACTIVITY

GSA-FSS

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.

TABLE I

Type	ANSI Code	Watts	Volts	Bulb	Base ***	Filament Design	Avg. Life	Rated (hrs)	Max. Over-all length (inches)	Approx. Initial Lumens Candle Power	Approx. Color Temp.	Description
1	CBA*	500	120	T-6**	4-pin	C-13 D		50	3-5/8	-	3,200	Slide projection, opaque end
2	DKM	250	21.5	T-14	4-pin	CC-6		25	3-7/8	-	3,300	16mm projection, opaque end, internal dichroic reflector
3	DRS	1,000	120	T-20**	med. pre-focus	C-13 D		25	5-3/4	28,500	3,325	Overhead projection
4	EHA*	500	120	T-6**	2-pin pre-focus	C-13 D		50	3.0	-	3,300	Overhead projection proximity reflector
5	DDM*	80	19	MR-16	2-pin	CC-6		50	1-3/4	-	3,350	Slide projection 2 inch diameter dichroic reflector
6	FCZ	500	120	T-3	Recessed single contact	CC-6		2,000	4-11/16	-	-	

* Lamp should be protected from scratches and abrasions and should not be used at over 110 percent of rated voltage.

** Lamp has a special heat-resistant glass bulb.

*** Burn types 1, 4, and 5 base down to horizontal and types 2 and 3 base down.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.