COMMERCIAL ITEM DESCRIPTION

KEY, SOCKET HEAD SCREW

The General Services Administration has authorized the use of this commercial item description in preference to types I and II, classes 1 and 2 of *Federal Specification* GGG-K-275.

This commercial item description covers L-shaped keys with hexagonal and splined cross-sections used for installing and removing socket head cap screws and setscrews.

Salient characteristics:

Design and dimensions. Design and dimensions shall comply with figures 1, tables 8 or 9 (as applicable) of American National Standards Institute (ANSI) Standard B18.3 - 1982.

Sizes. Sizes shall be as follows for the National Stock Number (NSN) specified:

Nominal Size (Inches)	Hexagon Keys (Table 8) Short Series	Long Series
0.028	5120-00-555-2639	--
0.035	5120-00-198-5400	5120-00-596-1236
0.050	5120-00-198-5401	5120-00-541-5556
1/16	5120-00-198-5398	5120-00-293-1476
5/64	5120-00-224-2504	5120-00-293-0080
3/32	5120-00-242-7410	5120-00-221-8036
7/64	5120-00-889-2162	5120-00-951-6589
1/8	5120-00-240-5292	5120-00-198-5412
9/64	5120-00-889-2163	5120-00-984-0247
5/32	5120-00-198-5392	5120-00-198-5413
3/16	5120-00-240-5300	5120-00-198-5410
7/32	5120-00-242-7411	5120-00-241-3179
1/4	5120-00-224-4659	5120-00-241-3180
5/16	5120-00-240-5274	5120-00-198-5409
3/8	5120-00-198-5390	5120-00-198-5406
7/16	5120-00-240-5277	--
1/2	5120-00-198-5391	5120-00-198-5407
9/16	5120-00-240-5268	5120-00-198-5404
5/8	5120-00-224-2510	5120-00-198-5405
3/4	5120-00-222-1489	5120-00-198-5402
1	5120-00-198-5387	5120-00-198-5403

Nominal Size (Inches)	Spline Key (Table 9) Short Series	Nominal Size (Inches)	Spline Key (Table 9) Short Series
0.033	5120-00-901-6633	0.145	5120-00-277-1724
0.048	5120-00-288-9085	0.168	--
0.060	5120-00-293-0195	0.183	5120-00-224-4660
0.072	5120-00-249-9670	0.216	5120-00-277-1723
0.096	5120-00-223-6995	0.251	5120-00-224-2480
0.111	5120-00-224-2482	0.291	5120-00-240-5284

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.

Finish. The keys shall have a black oxide coating with a subsequent coating of nondrying petroleum oils containing corrosion inhibitors.

Marking. Hexagon keys, sizes 0.078 inch and larger, shall be stamped or engraved in a legible and permanent manner with the size and manufacturer's name or U. S. registered trademark of such known character that the source of manufacture may be readily determined. Spline keys need not be marked.

Workmanship. Keys shall be free from rust, scale, burrs, fins, pits, defects in coating, or other defects which may affect their durability or serviceability

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes:

Copies of ANSI Standards can be obtained from American National Standards Institute, Incorporated, 1430 Broadway, New York, NY 10018.

DoD coordination waived

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.