INCH-POUND
MS24152K
w/AMENDMENT 1
23 January 2025
SUPERSEDING
MS24152K
2 May 2018

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 3 PDT, 25 AMPERES, TYPE II, NONHERMETICALLY SEALED (MECHANICALLY INTERLOCKED)

INACTIVE FOR NEW DESIGN AFTER 27 MAY 1994.
NO SUPERSEDING SPECIFICATION.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM
DE-ENERGIZED POSITION

Inches	mm	Inches	mm	Inches	mm
.062	1.57	.625	15.88	2.468	62.69
.125	3.18	.922	23.42	2.750	69.85
.218	5.54	1.062	26.97	4.094	103.99
.250	6.35	1.531	38.89	4.187	106.35
.310	7.87	2.062	52.37	4.750	120.65
.344	8.74	2.141	54.38		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031 inch (0.79 mm).
4. Additional washer may be used for terminal seat.
5. Terminal covers and barriers are required at power terminals.
6. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.
7. Copies of referenced documents are available online at https://quicksearch.dla.mil/.
8. Cadmium or cadmium compounds are prohibited on external hardware.
9. Spring washer on drawing is a spring lock washer.

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Dash number and general characteristics: See table I.

TABLE I. Dash number and general characteristics.

PIN MS24152-	Type	Coil type	Terminal type	Mounting or mating socket	Auxiliary terminals	Max weight (pounds)
D1	II	dc	Stud	Flange	None	2.3

Contact data:

Load ratings: See table II.

Maximum contact drop, initial: 0.150 V.

After life test: 0.175 V.

Overload current (NO): 200 amperes.

Rupture current (NO): 250 amperes.

TABLE II. Rated contact load (amperes per pole) (case grounded). 1/

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 2/			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz
Resistive	50	25				25				25			
Inductive	10	25				25				25			
Motor	50	25				25				25			
Lamp													
Transfer load 3/													
Mechanical life reduced current	100	6.3				6.3			6.3				
Mixed loads	50	2.5				2.5				2.5			

1/ Absence of value indicates parameter is not applicable to this specification.
2/ Absence of value indicates relay is not rated for three phase applications.
3/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.

Coil data: See table III.

Duty rating: Continuous.

RFI specification: MIL-STD-461 (applicable to coil circuits of ac operated relays).

TABLE III. Operating characteristics.

PIN MS 24152-	Coil data													Time - (milliseconds maximum)					
	Coil	Rated				Max			Max pick-up voltage			Drop out volt-age 2/	Hold volt-age 2/	Oper-ate 3/	Re-lease 4/	Contact bounce 3/			
		Volts 1/	Freq. Hz	Ω Res +15% - 10		Volts	Amp		Nor-mal 2/	High Temp test	Cont cur-rent test					Main		Aux	
				In-rush	Steady state		1.46	0.45								NO	NC	NO	NC
D1	X1,X2 Y1,Y2	28	dc	22	92	29	0.25		18	21	22.5	1.5	7.0	20	15	3.0 5/	2		

1/ Caution: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With rated coil voltage.
4/ From rated coil voltage.
5/ 6.0 milliseconds after electrical life.

Environmental characteristics:

Temperature range: -55°C to +71°C.

Maximum altitude rating: 50,000 feet.

Shock, g-level: 25 g's.

Duration: 6-9 ms.

Maximum duration contact opening: 2 ms.

Vibration, sinusoidal: See table IV.

Vibration, random: N/A.

High shock: N/A.

Acceleration: 10 g's.

Terminal strength (high temperature pull and torque test): Not applicable.

TABLE IV. Vibration levels (sinusoidal).

PIN MS24152-	Frequency			
	5-10 Hz	10-55 Hz	55-250 Hz	250-500 Hz
D1	.08 DA	.06 DA	2 g's	2 g's

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.

Electrical data:

Minimum insulation resistance:

Initial: 100 megohms.

After life or environmental test: 50 megohms.

Dielectric strength:

Sea level, 2-5 seconds:

	Initial		After life tests	
	28 V dc	115 V ac	28 V dc	115 V ac
Coil to case	1,250	N/A	1,000	N/A
Aux. contacts	1,250	N/A	1,000	N/A
All other points	1,250	1,500	1,000	1,125

Altitude, 1 minute:

	28 V dc	115 V ac
Coil to case	500	N/A
Aux. contacts	500	N/A
All other points	700	700

Part or Identifying Number (PIN): MS24152-D1.

Qualification by similarity: See MIL-PRF-6106.

Supersession data: MS24152-D1 replaces AN3340-2.

Performance of group B and group C tests is not applicable. Group A acceptance reports shall be submitted to the preparing activity on a yearly basis to retain qualification.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

In addition to MIL-PRF-6106, this document references the following:
MIL-STD-461

Custodian activities:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2025-014)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.