INCH-POUND

MS27254K
24 November 2025
SUPERSEDING
MS27254J
21 October 2020

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT
TYPE I, PLUG-IN, HERMETICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 5 JUNE 1987.
NO SUPERSEDING SPECIFICATION.
FOR NEW DESIGN, USE MIL-PRF-83536/15, 16, 17.

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall
consist of this specification and the latest issue of MIL-PRF-6106.






FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:19Z
Check the source to verify that this is the current version before use.



PIN LAYOUT



CIRCUIT -2



CIRCUIT -1
SEE NOTE 6

Inches	mm	Inches	mm	Inches	mm
.001	0.03	.156	3.96	.630	16.00
.002	0.05	.157	3.99	.734	18.64
.004	0.10	.210	5.33	.921	23.39
.005	0.13	.230	5.84	1.047	27.38
.031	0.79	.281	7.14	1.078	28.58
.040	1.02	.314	7.98	1.140	28.96
.047	1.19	.315	8.00	1.359	34.52
.062	1.57	.362	9.19	1.437	36.50
.105	2.67	.420	10.67		
.144	3.66	.524	13.31		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Terminal numbers need not appear on relay headers provided there is affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. Pins to be perpendicular to header within one inch.
6. The use of diodes on ac relays is optional. Actual application must be shown on label.
7. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
8. Referenced Government documents of the issue listed in that issue of the Acquisition Streamlining and Standardization Information System (ASSIST) specified in the solicitation forms a part of this standard to the extent specified herein.
9. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 20 ±5, thickness .047. Gasket material according to SAE-AMS3332 has been considered acceptable.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:19Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and characteristics.

Dash number MS27254-	Type	Coil	Terminal type	Max weight in pounds
1	I	ac	Plug-in	.20
2	I	dc	Plug-in	.20

TABLE II. Operating characteristics.

Part no. MS 27254-	Coil data											Time - (milliseconds maximum)					
	Coil	Nominal			Max		Max pick-up voltage			Hold voltage 2/	Drop out voltage 2/	Operate 3/	Release 4/	Contact Bounce			
														Main		Aux	
		Volts 1/	Freq Hz	Ω Res	Volts	Amp	Normal 2/	High temp test	Cont current test					NO	NC	NO	NC
1	ac	115	400	N/A	120	.04	90	95	103	30	5	15	30	3	5	---	---
2	dc	28	dc	160	29	.20	18	19.5	22.5	7	1.5	10	10	3	5	---	---

1/ Caution: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With nominal coil voltage.
4/ From nominal coil voltage.

TABLE III. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appropriate notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	
Resistive	100	10	10			10				10				
Inductive	50	10	10			10				10				
Inductive														
Motor	100	5	5			5				5				2/
Lamp	100	3	3			3				3				2/
Transfer load														3/
Mechanical life reduced current	400	2.5	2.5											
Mixed loads	100	Applicable per specification MIL-PRF-6106												

1/ Absence of value indicates relay is not rated for 3 phase applications.
2/ 100,000 operations - on NO contacts, and 50,000 operations on NC contacts at 28 V dc.
3/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:19Z
Check the source to verify that this is the current version before use.

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 80,000 feet.

Shock g-level: 25 g's.

Duration: 11 ms.

Max duration contact opening: 10 μs.

Vibration - sinusoidal:

G-level: 20 g's.

Frequency range: 10 - 2,000 Hz.

Vibration - random.

Applicable specification	N/A.
Power spectral density	N/A.
RMS G min	N/A.
Frequency range	N/A.
Curve	N/A.

High shock N/A.

Acceleration: 15 g's.

Electrical characteristics:

Insulation resistance, initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric strength (sea level):

	Initial	After life tests
Coil to case	1,000 V rms	1,000 V rms
Aux contacts	N/A	N/A
All other points	1,500 V rms	1,125 V rms

Dielectric strength (altitude):

	Initial	After life tests
Coil to case	N/A	250 V rms
Aux contacts	N/A	
All other points	N/A	350 V rms

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:19Z
Check the source to verify that this is the current version before use.

Maximum contact drop initial: 0.150 volt.

After life test: 0.175 volt.

Overload current: 40 amperes dc, 60 amperes ac.

Rupture current: 50 amperes dc, 80 amperes ac.

Duty rating: Continuous.

RFI specification MIL-STD-461.
(applicable to coil circuits of ac operated relays)

Conformance inspection:

Performance of groups B and C tests are not applicable.

Group A acceptance reports shall be submitted to the qualifying activity on a yearly basis in order to retain qualification for this military specification sheet.

Qualification by similarity: See MIL-PRF-6106.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:
MIL-STD-461 SAE-AMS3332

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2025-044)

Review activity:
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:19Z
Check the source to verify that this is the current version before use.