
FED. SUP CLASS
2540



OPTIONAL DESIGN MS 53015-1
NORMALLY USED WITH ARM MS 51388

REVIEW ACTIVITIES: DLA-CS; AF-84
USFR ACTIVITIES: ARMY-ME, MI; NAVY-MC

APPROVED 28 JUNE 1962 REVISED (D) 24 JULY 1969 (E) 24 FEB 1975 (F) 28 JULY 1979 (G) 17 APR 84


(G) ENTIRE STANDARD REVISED

P.A. ARMY - AT Other Cust AF- 99 NAVY-YD	TITLE MIRROR ASSEMBLY, REARVIEW	MILITARY STANDARD MS 53015
PROCUREMENT SPECIFICATION: SUPERSEDES MIL-M-46728 (AT)		SHEET 1 OF 4


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:20Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2540



CROSS-SECTION VIEW OF
MIRROR INSTALLATION



MS 53015-2
NORMALLY USED WITH
BRACKET MS53016


APPROVED 28 JUNE 1962 REVISED (G) FOR CHANGES SEE SHEET 1,2,3, AND 4

P.A. ARMY-AT Other Cust AF-99 NAVY-YD	TITLE MIRROR ASSEMBLY, REARVIEW	MILITARY STANDARD MS53015
PROCUREMENT SPECIFICATION MIL-M-46728(AT)	SUPERSEDES	SHEET 2 OF 4

Source: https://assist.dla.mil -- Downloaded: 20260-23T20:20Z
Check the source to verify that this is the current version before use.

DD FORM 672-1

FED. SUP CLASS
2540



MS53015-3	RH SHOWN
MS53015-4	LH OPPOSITE

NORMALLY USED WITH BRACKET MS53016

ANGLE BETWEEN PLANE OF FLAT MIRROR AND CHORD PLANE OF CONVEX MIRROR AS SHOWN ABOVE:
5° IN PLAN VIEW
4.1° IN VERTICAL ELEVATION VIEW

RIGHT HAND MIRROR ASSEMBLY IS SHOWN. LEFT HAND MIRROR IS IDENTICAL EXCEPT OF OPPOSITE HAND WITH RESPECT TO VERTICAL AXIS.

COMBINATION MIRROR ASSEMBLY SEE REQUIREMENT NO.6.

APPROVED 28 JUNE 1962 REVISED (G) FOR CHANGES SEE SHEET 1,2,3, AND 4

P.A. ARMY-AT Other Cust AF-99 NAVY-YD	TITLE MIRROR ASSEMBLY, REARVIEW	MILITARY STANDARD MS53015
PROCUREMENT SPECIFICATION MIL-M-46728(MU)	SUPERSEDES	SHEET 3 OF 4

Source: https://assist.dla.mil -- Downloaded: 20260-23T20:20Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. BALL, STUD AND SOCKET ASSEMBLY SHALL BE PROVIDED WITH MEANS OF ADJUSTING TENSION SUFFICIENTLY TO HOLD MIRROR IN FIXED POSITION.
2. SYNTHETIC RUBBER CUSHION, GRADE RS515 B-C_1-F_1, OF MIL-STD-417. METHOD OF CUSHION RETENTION OPTIONAL.
3. MANUFACTURER MAY SUPPLY SPACERS AS REQUIRED TO MEET THE DIMENSIONS BETWEEN MOUNTING EARS AS SHOWN.
4. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON THE DATE OF INVITATION FOR BIDS.
5. MARKING SHALL CONSIST OF THE MS PART NUMBER AND MANUFACTURER'S IDENTIFICATION IN ACCORDANCE WITH MIL-STD-130.
6. THE COMBINATION (PLANE AND CONVEX) MIRROR ASSEMBLY WILL BE CAPABLE OF BEING INDEPENDENTLY ADJUSTED.
7. MIRROR ASSEMBLY SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE REQUIREMENTS OF MIL-STD-1180, REQUIREMENT NO. 111.
8. MARKING SHALL BE AT THE LOWER EDGE OF MIRROR'S REFLECTIVE SURFACE, IN LETTERS NOT LESS THAN 3/16 INCH NOR MORE THAN 1/4 INCH HIGH.

NOTES:

1. DIMENSIONS ARE IN INCHES.
2. FOR DESIGN PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
3. THIS STANDARD IS NOT INTENDED TO LIMIT CONSTRUCTION TO FEATURES OTHER THAN AS SHOWN HEREON BY DIMENSIONS, NOTATIONS OR REFERENCED DOCUMENTS.

APPROVED REVISED (G) FOR CHANGES SEE SHEET 1,2,3, AND 4

P.A. ARMY-AT Other Cust AF-99 NAVY-YD	TITLE MIRROR ASSEMBLY, REARVIEW	MILITARY STANDARD MS 53015
PROCUREMENT SPECIFICATION MIL-M-46728(AT)	SUPERSEDES:	SHEET 4 OF 4

Source: https://assist.dla.mil -- Downloaded: 20260-23T20:20Z
Check the source to verify that this is the current version before use.