NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/43G
13 July 2020
SUPERSEDING
MIL-DTL-11484/43F
8 September 2015

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, MATERIALS HANDLING AND CONSTRUCTION EQUIPMENT OPERATORS SAFETY AWARD, U.S. NAVY AND U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.




MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Epoxy resin (Stoning epoxy) 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

DIMENSION:
HEIGHT (Overall): 5/8 inch (REF)
WIDTH (Overall): 21/32 inch (REF)
THICKNESS (At edge): 0.035 inch $\pm$ 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:18Z
Check the source to verify that this is the current version before use.

| DASH NO. | YEAR (S) | DASH NO. | YEAR (S) |
|---|---|---|---|
| -1: | 1 | -19 | 19 |
| -2: | 2 | -20 | 20 |
| -3: | 3 | -21 | 21 |
| -4: | 4 | -22 | 22 |
| -5: | 5 | -23 | 23 |
| -6: | 6 | -24 | 24 |
| -7: | 7 | -25 | 25 |
| -8: | 8 | -26 | 26 |
| -9: | 9 | -27 | 27 |
| -10: | 10 | -28 | 28 |
| -11: | 11 | -29 | 29 |
| -12: | 12 | -30 | 30 |
| -13: | 13 | -31 | 31 |
| -14: | 14 | -32 | 32 |
| -15: | 15 | -33 | 33 |
| -16: | 16 | -34 | 34 |
| -17: | 17 | -35 | 35 |
| -18: | 18 | | |

ATTACHING DEVICE:

1. The attaching device shall be a prong with pick and wing type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above, and well match TIOH Hard Enamel Color Chip Numbers listed below.

| **TIOH HARD ENAMEL COLOR CHIPS** | |
|---|---|
| **COLOR** | **CHIP NUMBER** |
| Blue | #20 |

NOTES:

1: The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2: If hard cloisonné enamel is used, the base material must be Gilding Metal 95/5 (UNS Alloy No. C-210).

3: The use of any type of plastic packaging material is prohibited.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:18Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-2020-397)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:18Z
Check the source to verify that this is the current version before use.