NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/47G
14 May 2025
SUPERSEDING
MIL-DTL-11484/47F
9 July 2020

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, VICTORY MEDAL

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



DASH NO.
-1: Bronze
-2: Silver

MATERIAL:
-1: Red Brass 85/15 (UNS Alloy No. C-230)
-2: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver (UNS Alloy No.C-752)

FINISH:
-1: Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.
-2: Nickel Plated, (C-230 only) Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSION:
DIAMETER: 5/8 inch (REF)
THICKNESS (At center): 0.075 inch $\pm$ 0.005 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:19Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. The attaching device shall be a prong with pick and wing type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTE:
The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - NU
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Navy - MC, CG1
DLA - CT

(Project No. 8455-2025-103)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:19Z
Check the source to verify that this is the current version before use.